



Zoom Dialer

for Prepaid and Dial-around Phone Services

MODEL 26

- **Easy Routing**
with Store-and-Forward speed
- **Easy Plug-in
Installation**
Through any jack on the
phone line
- **Easy To Use**
Works for all phones on the line
- **Easy Programming**
- **Easy Price**

The **Zoom Dialer 26** simplifies the use of prepaid and dial-around phone services by automatically dialing the extra digits required to place a call. Patented technology allows a single dialer to work for all of the phones or extensions on a line.

With the dialer, alternate long distance services are as easy to use as pre-subscribed services.

The inexpensive device plugs into any RJ-11 jack, just like a telephone, and provides store-and-forward dialing to all of the telephones plugged into the same phone line. The dialer's auto-learn mode programs a prepaid card's access phone number and PIN by simply using the prepaid card one time.

Non-toll calls are passed through without action by the dialer. Users can choose to have the dialer handle toll calls in auto-mode or manual mode. In auto-mode, toll calls are dialed by the user with only the destination phone number, and the dialer automatically routes toll calls using the prepaid account. In manual mode, the user presses a * before dialing any phone number the user wants handled by the prepaid service, the dialer then routes the call.

A single dialer can be used with up to 8 prepaid phone accounts, so that roommates with different phone cards can all use the dialer. Each user assigns their password to the dialer.

The dialer cuts dialing time by fifty percent or more when compared to manually dialing a prepaid call. The dialer also prevents mistakes in entering an access number and account number, which eliminates the frustrating need to re-enter a long number. And because the dialer can automatically route all toll calls to an alternate service provider, households are assured that every call is placed at a money-saving rate.

Dialer Sales
Ron Polli
Tel: 732-255-3969
E-mail: rpolli@zoom.com

Founded in 1977, Zoom Telephonics, Inc. designs, produces and markets a broad range of communications products under the Zoom, Hayes and Global Village brands. Zoom Telephonics is publicly traded on the NASDAQ National Market, and its trading symbol is ZOOM.



International Headquarters
Zoom Telephonics
207 South Street
Boston, MA 02111
www.zoom.com

Model 26 Dialer

Specifications

Dialer Operation:

The Model 26 dialer makes phone calls through prepaid and dial-around services as easy to place as a local call. The dialer can be configured to ignore local phone numbers, including local calls consisting of the digit "1" plus ten following digits.

The dialer can output a dialing string of up to 96 digits, and act upon logical operators and observed events such as pauses, or programmed detection of voice and/or tone prompts.

The dialer can route calls for up to eight prepaid service accounts or networks. The dialer can be set to: route all calls; route calls preceded by *; route calls preceded by a Personal Identification Number.

Dialer Programming:

Simply place the dialer into Learn Mode™ and dial a number using a prepaid service. The dialer remembers the long distance access sequence, including access number, PIN and other variables in the dialing sequence needed to place the prepaid call.

Tones detected:	DTMF (touch tones): 0 through 9, #, *, A, B, C, D; Voice and Dialtone
Dialing Speed:	Programmable tone duration of 50 ms to 250 ms
Dimensions:	Dialer: 3.3 inches by 2.6 inches by 1.25 inches 110 V adapter: 2.2 inches by 1.7 inches by 1.6 inches
Weight:	Dialer: 2.9 ounces Power supply: 5.8 ounces
Connectors:	Two RJ-II phone jacks One DC power supply barrel connector, size 5.5mm outer diameter with a 2.1mm inner diameter with positive center.
Status Reporting:	Line Polarity: Phone line on/off hook; Sending DTMF
Regulatory Compliance:	FCC Part 15B and Part 68, CE (EN55022, EN55024, EN60950), UL and CUL
Transformer Output:	22-24 Volt DC, 65 mA
Mounting bracket:	Provides for optional wall mounting by using the adhesive pad provided or by using screws
Package Contents:	Dialer 26 Phone cord -18 inches (45 cm), RJ-11 to RJ-11 connectors Mounting Bracket Instruction Manual Power Transformer Compliance Flyer