



FOR GENERAL REFERENCE ONLY  
 Models shown may not match the  
 model features or manuf year of the  
 item offered by AERE.

401 Delaware, Quincy, IL 62301  
 800.521.2665 217.228.2421 Fax: 217.228.2424 www.uscooler.com

Qty	SqFt	Description	Weight
1		Walk-In Combination: 11ft. 5in. X 7ft. 10in. X 7ft. 6in. - 1 Cooler(s) 1 Freezer(s)	0
1	247.84	STD. NOM. WALK-IN COOLER: 5'-8 1/2" X 7'-10" X 7'-6" - 4" EXTRUDED POLYSTYRENE, STUCCO EMBOSSED GALVALUME 26 GAUGE EXTERIOR, STUCCO EMBOSSED GALVALUME 26 GAUGE INTERIOR, NSF APPROVED.	595
1	44.715	FLOOR: 5FT. 8.5IN. X 7FT. 10IN. - 4" EXTRUDED INSULATION, 22 GAUGE STAINLESS STEEL INTERIOR, STUCCO EMBOSSED GALVALUME 26 GAUGE EXTERIOR	123
1		DOOR, 34 in. X 76 in.; MED TEMP INSIDE WITH FLOOR, LIGHT, SWITCH, THERMOMETER, DOOR CLOSURE, SPRING LOADED HINGE RIGHT 1' 0.25" FROM RIGHT CORNER ON FRONT LENGTH WALL	220
1		REMOTE INSIDE REFRIGERATION COPELAND MCFH0056IAB252 SYSTEM, MED TEMP 1 PHASE, 1/2 HP, HERMETIC, 208-230 VOLT. INCLUDES: COPELAND CONDENSING UNIT, RUSSELL AA18-53B-AE EVAPORATOR, THERMOSTATIC EXPANSION VALVE, SIGHT GLASS, DRIER, SOLENOID VALVE, THERMOSTAT. MAXIMUM LOW 35 DEGREES. DRAIN LINE NEEDS TO BE FIELD INSTALLED. DOES NOT INCLUDE REFRIGERANT - R22. EISA COMPLIANT	126
1		EXTENDED 2ND-5TH YEAR EQUIGUARD REFRIGERATION WARRANTY COMPRESSOR ONLY CRHC-05-.5P (3304)	0
1	247.84	STD. NOM. WALK-IN FREEZER: 5'-8 1/2" X 7'-10" X 7'-6" - 4" EXTRUDED POLYSTYRENE, STUCCO EMBOSSED GALVALUME 26 GAUGE EXTERIOR, STUCCO EMBOSSED GALVALUME 26 GAUGE INTERIOR, NSF APPROVED.	595
1	92.285	FLOOR: 5FT. 8.5IN. X 16FT. 2IN. - 4" EXTRUDED INSULATION, 22 GAUGE STAINLESS STEEL INTERIOR, STUCCO EMBOSSED GALVALUME 26 GAUGE EXTERIOR	254
1		DOOR, 34 in. X 76 in.; LOW TEMP INSIDE, WITH FLOOR, WITH LIGHT, SWITCH, HEATER WIRE, THERMOMETER, & DOOR CLOSURE, SPRING LOADED HINGE RIGHT 9.5 INCHES FROM LEFT CORNER ON FRONT LENGTH WALL	220
1		DOOR, 34 in. X 76 in.; LOW TEMP INSIDE, WITH FLOOR, WITH LIGHT, SWITCH, HEATER WIRE, THERMOMETER, & DOOR CLOSURE, SPRING LOADED HINGE RIGHT 9.5 INCHES FROM LEFT CORNER ON FRONT LENGTH WALL	220
1		PRESSURE RELIEF (USC 591) Installed	1
1		REMOTE INSIDE REFRIGERATION COPELAND FJALA101CAV050 SYSTEM, NON-CHARGED, LOW TEMP, 1 PHASE, 1 HP, HERMETIC, 208-230 VOLT. INCLUDES: COPELAND CONDENSING UNIT, RUSSELL AE16-41B-DE EVAPORATOR, THERMOSTATIC EXPANSION VALVE, THERMOSTAT, LOW PRESSURE CONTROL, SIGHT GLASS, DRIER, SOLENOID VALVE, DRAIN HEATING CABLE, TIMER. DRAIN LINE INCLUDED SHIPPED LOOSE, DOES NOT INCLUDE REFRIGERANT - R404A. EISA COMPLIANT	171
1		EXTENDED 2ND-5TH YEAR EQUIGUARD REFRIGERATION WARRANTY COMPRESSOR ONLY CRHC-05-1P (3303)	0
1		TEST ASSEMBLY, PACKAGING, AND HANDLING - 4' X 8'6" Flat Stack LTL	156
1		TEST ASSEMBLY, PACKAGING, AND HANDLING - 4' X 13" Flat Stack LTL	280
REFRIGERATION SIZED TO HOLD COOLER AT 35* WITH MISC ENTERING AT 55*			
REFRIGERATION SIZED TO HOLD FREEZER AT -10* WITH MISC ENTERING AT 20*			