

A6E/V6E Series

Bill Acceptor

- Auto-calibrating.
- Four-way bill insertion.
- Numerous interfaces available.
- High acceptance rate up to 96%.
- Easy installation and maintenance.



ICT

A6E/V6E Series

Bill Acceptor

A6E/V6E Series is a bill acceptor which features not only high-security module with bill box but also outstanding recognition, acceptance rate up to 96% or even greater.

Specifications



Acceptance Rate

96% or greater



Bill Insertion

Four-way



Bill Width Accepted

60-67 mm/ 2.36-2.63 inches



Capacity

Approx. 100 bills (40- 140)
300 bills (200- 300)
500 bills (300- 500)
550 bills (440- 640)
800 bills (750- 850)
1000 bills (1000-1140)



Dimension

100 bills:
(W)94 x (D)81 x (H)235.9 mm/
(W)3.70 x (D)3.56 x (H)9.28 inches

300 bills:
(W)94 x (D)115 x (H)235.9 mm/
(W)3.70 x (D)4.53 x (H)9.28 inches

500 bills:
(W)94 x (D)130 x (H)235.9 mm/
(W)3.70 x (D)5.12 x (H)9.28 inches

550 bills:
(W)94 x (D)153 x (H)235.9 mm/
(W)3.70 x (D)6.02 x (H)9.28 inches

800 bills:
(W)94 x (D)190 x (H)235.9 mm/
(W)3.70 x (D)7.48 x (H)9.28 inches

1000 bills:
(W)94 x (D)232 x (H)235.9 mm/
(W)3.70 x (D)9.13 x (H)9.28 inches



Acceptance Speed

Approx. 3 sec. to cashbox



Interface

A6E: Standard Pulse, 5V Enable, ICT Protocol
VE: MDB



Power Source

A6E: 12V DC (11.4-12.8V DC)
117V AC (105.3-128.7V AC)
VE: 24V/34V DC (20V-42.5V DC)



Power Consumption

A6E: 12V DC Standby : 0.3A, 4W
 Operation: 0.9A, 11W
 Maximum: 2.6A, 32W
117V AC Standby : 0.06A, 7W
 Operation: 0.112A, 14W
 Maximum: 0.4A, 47W

VE: 24V/34V DC Standby : 0.15A, 8W
 Operation: 0.4A, 14W
 Maximum: 1.35A, 46W



Weight

Approx. 2 kg/ 4.4 lbs



Environmental

Operating Temperature:
0°C/32°F - 55°C/131°F
Storage Temperature:
-30°C/-22°F - 70°C/158°F
Humidity: 30%-85% RH (No Condensation)



Recommended Applications

Indoor Vending, Gaming, Amusement

Specifications are subject to change without prior notice.



International Currency Technologies

No.28, Ln. 15, Sec. 6, Minquan E. Rd., Neihu Dist., Taipei City 114, Taiwan

Phone: +886-2-2793-1236

Fax: +886-2-2793-6125

Email: sales@ictgroup.com.tw (Product Information)

fae@ictgroup.com.tw (Technical Service)

Website: www.ictgroup.com.tw