

CSD Drop type RS232									
Retry times	RS232 ID	Retry times		RS232 ID				N/A	
		1	2	3	4	5	6	7	8
1	No.1	OFF	OFF	OFF	OFF	OFF	OFF	OFF	OFF
2	No.2	ON	OFF	ON	OFF	OFF	OFF	OFF	OFF
4	No.3	OFF	ON	OFF	ON	OFF	OFF	OFF	OFF
8	No.4	ON	ON	ON	ON	OFF	OFF	OFF	OFF

Manufacture Setting:SW1,SW2 ON, SW3~SW8 OFF

CSD Drop type 3 in 1											
Retry times	Interface	Outlet signal setting	RS232 ID	Retry times		Interface		Outlet signal	RS232 ID		N/A
				1	2	3	4		5	6	
1	Pulse	High	No.1	OFF	OFF	OFF	OFF	OFF	OFF	OFF	OFF
2	Hopper	Low	No.2	ON	OFF	OFF	ON	ON	OFF	ON	OFF
4	RS232	N/A	No.3	OFF	ON	ON	OFF	NA	ON	OFF	OFF
8	N/A	N/A	No.4	ON	ON	ON	ON	NA	ON	ON	OFF

CSD Standard type 3 in 1												
Retry times	Interface	Outlet signal setting	RS232 ID	Send credit	Retry times		Interface		Outlet signal	RS232 ID		Send Credit
					1	2	3	4		5	6	
1	Pulse(EL)	High	No.1	before take off card	OFF	OFF	OFF	OFF	OFF	OFF	OFF	OFF
2	Hopper	Low	No.2	after take off card	ON	OFF	OFF	ON	ON	OFF	ON	ON
4	RS232	NA	No.3	NA	OFF	ON	ON	OFF	NA	ON	OFF	NA
8	Pulse(E)	NA	No.4	NA	ON	ON	ON	ON	NA	ON	ON	NA