

# L70-USD6

## L70/P5 DIP SWITCHES SETTING : 1(Pulse/RS232 A0/V2.2)

Supported bill USD 1, 5, 10, 20, 50, 100 6bills.

| FUNCTION                                    | SW1 | SW2 | SW3 | SW4 | SW5 | SW6 | SW7 | SW8 | SW9 | SW10 |
|---|-----|-----|-----|-----|-----|-----|-----|-----|-----|------|
| ★ 1 Pulse / USD 1                           | OFF | OFF | OFF |     |     |     |     |     |     |      |
| 2 Pulses / USD 1                            | OFF | OFF | ON  |     |     |     |     |     |     |      |
| 3 Pulses / USD 1                            | OFF | ON  | OFF |     |     |     |     |     |     |      |
| 4 Pulses / USD 1                            | OFF | ON  | ON  |     |     |     |     |     |     |      |
| 5 Pulses / USD 1                            | ON  | OFF | OFF |     |     |     |     |     |     |      |
| 10 Pulses / USD 1                           | ON  | OFF | ON  |     |     |     |     |     |     |      |
| 20 Pulses / USD 1                           | ON  | ON  | OFF |     |     |     |     |     |     |      |
| 100 Pulses / USD 1                          | ON  | ON  | ON  |     |     |     |     |     |     |      |
| Fast output Pulse<br>Lo= 30ms<br>Hi= 50ms   |     |     |     | ON  |     |     |     |     |     |      |
| ★ Slow output Pulse<br>Lo= 50ms<br>Hi=100ms |     |     |     | OFF |     |     |     |     |     |      |
| Inhibit level Active Low                    |     |     |     |     | ON  |     |     |     |     |      |
| ★ Inhibit level Active High                 |     |     |     |     | OFF |     |     |     |     |      |
| ★ Accept USD 1                              |     |     |     |     |     | ON  |     |     |     |      |
| Reject USD 1                                |     |     |     |     |     | OFF |     |     |     |      |
| ★ Accept USD 5                              |     |     |     |     |     |     | ON  |     |     |      |
| Reject USD 5                                |     |     |     |     |     |     | OFF |     |     |      |
| ★ Accept USD 10                             |     |     |     |     |     |     |     | ON  |     |      |
| Reject USD 10                               |     |     |     |     |     |     |     | OFF |     |      |
| ★ Accept USD 20                             |     |     |     |     |     |     |     |     | ON  |      |
| Reject USD 20                               |     |     |     |     |     |     |     |     | OFF |      |
| ★ Accept USD 50 & 100                       |     |     |     |     |     |     |     |     |     | ON   |
| Reject USD 50 & 100                         |     |     |     |     |     |     |     |     |     | OFF  |

★ Manufacture setting

Note: (1) Please reset the bill acceptor after any changes on Dip switch.

(2) Dip switches 1 to 5 are only for Pulse mode.

# L70-USD6(Pulse/RS232 A0/V2.2)

## DIP SWITCHES SETTING : 2(Pulse)

| FUNCTION                   | SW1 | SW2 | SW3 | SW4 |
|----------------------------|-----|-----|-----|-----|
| ★ Credit-Pulse Normal High | ON  |     |     |     |
| Credit-Pulse Normal Low    | OFF |     |     |     |
| ★ Pulse Mode               |     | ON  | OFF |     |
| RS232 A0 Mode              |     | ON  | ON  |     |
| V2.2 Mode                  |     | OFF | ON  |     |
| Reserved                   |     | OFF | OFF |     |
| Disable Inverse Mode       |     |     |     | ON  |
| ★ Enable Inverse Mode      |     |     |     | OFF |

★ Manufacture setting

## DIP SWITCHES SETTING : 2(RS232 A0)

| FUNCTION              | SW1 | SW2 | SW3 | SW4 |
|-----------------------|-----|-----|-----|-----|
| ★ Reserved            | ON  |     |     |     |
| Reserved              | OFF |     |     |     |
| Pulse Mode            |     | ON  | OFF |     |
| ★ RS232 A0 Mode       |     | ON  | ON  |     |
| V2.2 Mode             |     | OFF | ON  |     |
| Reserved              |     | OFF | OFF |     |
| Disable Inverse Mode  |     |     |     | ON  |
| ★ Enable Inverse Mode |     |     |     | OFF |

★ Manufacture setting

## DIP SWITCHES SETTING : 2(V2.2)

| FUNCTION              | SW1 | SW2 | SW3 | SW4 |
|-----------------------|-----|-----|-----|-----|
| ★ Reserved            | ON  |     |     |     |
| Reserved              | OFF |     |     |     |
| Pulse Mode            |     | ON  | OFF |     |
| ★ RS232 A0 Mode       |     | ON  | ON  |     |
| V2.2 Mode             |     | OFF | ON  |     |
| Reserved              |     | OFF | OFF |     |
| Disable Inverse Mode  |     |     |     | ON  |
| ★ Enable Inverse Mode |     |     |     | OFF |

★ Manufacture setting

## Currency Assign Data

| Interface    | Pulse  | RS232 A0 | V2.2   |
|--------------|--------|----------|--------|
| ★ Bill value |        |          |        |
| BV1          | USD 1  | USD 1    | USD 1  |
| BV2          | USD 5  |          | USD 5  |
| BV3          | USD 10 | USD 5    | USD 10 |
| BV4          | USD 20 | USD 10   | USD 20 |
| BV5          | USD 50 | USD 20   | USD 50 |
| BV6          | USD100 | USD 50   | USD100 |
| BV7          |        | USD100   |        |

### RS232 A0 INFORMATION

| BillType Data |              |
|---------------|--------------|
| Code          | Denomination |
| 1             | USD 1        |
| 2             | Reserved     |
| 3             | USD 5        |
| 4             | USD 10       |
| 5             | USD 20       |
| 6             | USD 50       |
| 7             | USD 100      |
| 8             | Reserved     |
| 9             | Reserved     |