

NE77 B2B-USD6

NE77 B2B DIP SWITCHES SETTING : (MDB/ICT104R)

Supported bill USD 1, 5, 10, 20, 50, 100 6 bills.

Diagnostic mode

FUNCTION			
Diagnostic mode	Normal mode	SW1	SW2
★ Accepted banknotes -> stacker	MDB Interface	OFF	OFF
Accepted banknotes -> Recycler escrow buffer area. (Bill acceptor will disable while recycler is full.)	ICT Interface	ON	OFF
Banknote(s) dispensing mode.	Reserved	OFF	ON
Recycler -> Stacker.(Empty Recycler mode.)	Reserved	ON	ON

Currency Assign Data

Interface Bill value	MDB	ICT104R
BV1	USD 1	USD 1
BV2		
BV3	USD 5	USD 5
BV4	USD 10	USD 10
BV5	USD 20	USD 20
BV6	USD 50	USD 50
BV7	USD 100	USD 100

Operation mode

FUNCTION	SW3	SW4	SW5	SW6	SW7	SW8	SW9	SW10
★ Normal	ON							
Diagnostic mode	OFF							
Optical anti-fishing malfunction, BA will be still in working order		ON						
★ BA will stop to work when it acknowledges Optical anti-fishing malfunction		OFF						
★ Scaling Factor (SF) = 100 Decimal Point Position (DPP) = 2	(MDB only)		ON					
Scaling Factor (SF) = 1 Decimal Point Position (DPP) = 0			OFF					
★ Accept USD 1 & 5				ON				
Reject USD 1 & 5				OFF				
★ Accept USD 10 & 20					ON			
Reject USD 10 & 20					OFF			
★ Accept USD 50 & 100						ON		
Reject USD 50 & 100						OFF		
★ Reserved							ON	
Reserved							OFF	
★ Virtual MDB Recycler Function (Note.2)								ON
Standard MDB Recycler Function								OFF

★ Manufacture setting

Note 1: Please restart the bill acceptor after any changes on dip switch(s) has been made.

Note 2: Recycled Banknote represents as a virtual MDB coin type.