

# NK682/NK77

---

# Bill Acceptor

- ▣ Four way bill insertion acceptable.
- ▣ High transaction speed.
- ▣ Highlight LED Bezel.
- ▣ NK682T/NK77F support update firmware using a USB flash drive.



# NK682/NK77

## Bill Acceptor

NK Series features a high currency verification and recognition with new verification unit to be a new generation bill acceptor.

### Specifications



#### Acceptance Rate

96% or greater



#### Bill Insertion

Four-way



#### Bill Width Accepted

NK77- 68-77 mm  
NK682- 62-68 mm



#### Acceptance Speed

NK77- Approx. 2 sec. to stack  
NK682- Approx. 3 sec. to stack



#### Dimension

**NK77-**  
(Bezel Part Number: 3RBA-FAC4100X)  
(W)100x(H)134x(D)135.7 mm /  
(W)3.94x(H)5.28x(D)5.34 inches  
(Bezel Part Number: 3ZBA-FAC6200X)  
(W)120x(H)104x(D)135.7 mm /  
(W)4.72x(H)4.09x(D)5.34 inches  
(Bezel Part Number: 3ZBA-FAC3600X)  
(W)85x(H)88x(D)128.7 mm /  
(W)3.3x(H)3.5x(D)5.1 inches

**NK682-**  
(Bezel Part Number: 3ZBA-FAC3600X)  
(Without Stacker)  
(W)85.3x(H)88x(D)128.7 mm /  
(W)3.75x(H)3.46x(D)5.07 inches  
(With Stacker)  
(W)116x(H)188.2x(D)311.2 mm /  
(W)4.56x(H)7.40x(D)12.25 inches  
(Bezel Part Number: 3ZBA-FAC6600X)  
(Without Stacker)  
(W)100x(H)134x(D)133.7 mm /  
(W)3.94x(H)5.28x(D)5.26 inches



#### Interface

**NK77-**  
Pulse, Parallel, RS232(ICT Protocol),  
ccTalk(NK77F), MDB  
**NK682-**  
Pulse, Parallel, RS232(ICT Protocol)



#### Power Source

12V DC(10.8V-13.2V DC)



#### Power Consumption

**NK77-** Standby : 0.2A, 2.4W  
Operation: 1.41A, 17W  
Maximum: 1.5A, 18W  
**NK682-** (Without Stacker)  
Standby : 0.2A, 2.4W  
Operation: 1.42A, 17W  
Maximum: 1.5A, 18W  
(With Stacker)  
Standby : 0.4A, 4.8W  
Operation: 2.2A, 26.4W  
Maximum: 3.0A, 36W



#### Weight

**NK77-** Approx. 0.76kg  
**NK682-** Approx. 0.7kg (Without Stacker)  
Approx. 1.8kg (With Stacker)



#### Environmental

**NK77-** Operating Temperature: -10°C-60°C  
Storage Temperature : -20°C-70°C  
Humidity: 30%-85%RH  
(no condensation)  
**NK682-** Operating Temperature: -15°C-60°C  
Storage Temperature : -30°C-75°C  
Humidity: 30%-85%RH  
(no condensation)



#### Recommended Applications

Indoor Vending, Gaming, Kiosk



Specifications are subject to change without prior notice.



### International Currency Technologies

No.28, Ln. 15, Sec. 6, Minquan E. Rd., Neihu Dist., Taipei City 114, Taiwan

Phone: +886-2-2793-1236

Fax: +886-2-2793-6125

Email: sales@ictgroup.com.tw (Product Information)

fae@ictgroup.com.tw (Technical Service)

Website: www.ictgroup.com.tw