

# MATERIAL SAFETY DATA SHEET

Prepared to U.S. OSHA, CMA, ANSI, Canadian WHMIS Standards, Australian WorkSafe, Japanese Industrial Standard JIS Z 7250:2000, and European Directives

## 1. PRODUCT IDENTIFICATION

**TRADE NAME (AS LABELED):** Gator-Stain™ Concrete Acid Stain  
**PRODUCT USE:** Concrete Stain  
**PACKAGE SIZES:** 16 oz, 1 gal  
**CHEMICAL SHIPPING NAME/CLASS:** Corrosive Liquid, Acidic, Inorganic, N.O.S. Class 8  
**U.N. NUMBER:** UN3264  
**MANUFACTURER'S NAME:** Legacy Industrial Corp.  
**ADDRESS:** 12386 State Rd 535. 450, Orlando. FL 32836  
**EMERGENCY PHONE:** (800) 535-5053 InfoTrac  
**BUSINESS PHONE:** (888) 652-0333  
**DATE OF PREPARATION:** October, 11, 2023  
**DATE OF REVISION:** January 20, 2016

## 2. HAZARD IDENTIFICATION

### EMERGENCY OVERVIEW: Warning!

**Product Description:** This product is a dark red-brown liquid with a pungent odor.

**Health Hazards:** Harmful if swallowed or inhaled. Affects lungs, central nervous system, blood and kidneys. Causes irritation to skin, eyes and respiratory tract.

**Flammability Hazards:** Non-Flammable product.

**Reactivity Hazards:** This product is slightly reactive.

**Environmental Hazards:** Release of the product is not expected to cause adverse effects to the aquatic environment.

**Emergency Recommendations:** Emergency responders must have personal protective equipment and fire protection appropriate for the situation to which they are responding.

**EU LABELING AND CLASSIFICATION:** This product meets the definition of a hazardous substance or preparation according to EU Regulations (EC) No 1272/2008.

EC# 231-869-6 is not classified in the Annex I of Directive 67/548/EEC

EC# 231-595-7 is classified in the Annex I of Directive 67/548/EEC

Index # 017-002-01-X

### GHS CLASSIFICATIONS:

Carcinogen Category 2

Skin Corrosive Category 1B


Acute Toxicity Inhalation Category 3


Skin Irritation Category 3

Eye Irritation Category 2B

**SIGNAL WORD :** Warning



HAZARDOUS MATERIAL IDENTIFICATION SYSTEM			
HEALTH HAZARD (BLUE)		3	
FLAMMABILITY HAZARD (RED)		0	
REACTIVITY (YELLOW)		1	
PROTECTIVE EQUIPMENT			
EYES	RESPIRATORY	HANDS	BODY
	SEE SECTION 8		SEE SECTION 8
For Routine Industrial Use and Handling Applications			



### HAZARD STATEMENT:

H316 May cause skin irritation  
H320 May cause eye irritation  
H335 May cause respiratory irritation  
H351 Suspected of causing cancer

Scale: 0 = Minimal 1 = Slight 2 = Moderate  
3 = Serious 4 = Severe \* = Chronic hazard

### PREVENTION STATEMENT :

P202 Do not handle until all safety precautions have been read and understood.  
P261 Avoid breathing dust/fume/gas/mist/vapor/spray.

# **MATERIAL SAFETY DATA SHEET**

P272  
P280

Contaminated work clothing should not be allowed out of the workplace.  
Wear protective gloves/protective clothing/eye protection/face protection.

# MATERIAL SAFETY DATA SHEET

P281 Use personal protective equipment as required.

## RESPONSE STATEMENT:

P321 Specific treatment is advised – see first aid instructions.

P363 Wash contaminated clothing before reuse.

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.

P308 + P313 IF exposed or concerned : Get medical advice/attention.

P333 + P313 IF skin irritation or rash occurs : Get medical advice/attention.

## HEALTH EFFECTS OR RISKS FROM EXPOSURE:

**ACUTE:** Inhalation may irritate the respiratory tract. May cause allergic respiratory reaction. May cause liver and kidney damage. Ingestion may cause gastrointestinal tract irritation with nausea, vomiting, and possible burns. Skin and eye contact may cause irritation with redness and pain. Possible burns to both skin and eyes.

**CHRONIC:** Chronic manganese poisoning can result from excessive inhalation and ingestion exposure and involves impairment of the central nervous system. Kidney effects, blood changes and manganese psychosis also may occur as a result of chronic exposure. Chronic inhalation exposure can cause lung damage.

## 3. COMPOSITION AND INFORMATION ON INGREDIENTS

Hazardous Ingredients:	WT%	CAS#	EINECS #	Hazard Classification	Risk Phrases
Water	<85%	7732-18-5	231-791-2	NA	None
Manganese Chloride	5 – 15%	7773-01-5	231-869-6	[Xi] Irritant	R36/37/38
Sodium Dichromate	5 – 15%	7789-12-0	Unlisted	[Xn] Harmful, [T] Toxic	R21, R25, R26, R34, R37/38, R42/43, R45
Hydrochloric Acid	<2%	7647-01-0	231-595-7	[Xi] Irritant	R36/37/38
Balance of other ingredients is less than 1% in concentration (or 0.1% for carcinogens, reproductive toxins, or respiratory sensitizers).					None

NOTE: ALL WHMIS required information is included in appropriate sections based on the ANSI Z400.1-2004 format. This product has been classified in accordance with the hazard criteria of the CPR and the MSDS contains all the information required by the CPR, EU Directives and the Japanese Industrial Standard JIS Z 7250: 2000.

## 4. FIRST-AID MEASURES

**SKIN EXPOSURE:** If this product contaminates the skin, begin decontamination with running water. Minimum flushing is for 5 minutes. Remove exposed or contaminated clothing, taking care not to contaminate eyes. The contaminated individual should seek medical attention if any adverse effect occurs.

**EYE EXPOSURE:** If this product enter the eyes, open contaminated individual's eyes while under gently running water. Use sufficient force to open eyelids. Remove contact lenses if worn. Have contaminated individual "roll" eyes. Minimum flushing is for 15 minutes. Contaminated individual must seek immediate medical attention.

**INHALATION:** If fumes/vapors or mists generated by this product are inhaled, remove contaminated individual to fresh air. If necessary, use artificial respiration to support vital functions. Seek medical attention if breathing distress continues.

**INGESTION:** Routine use of this product is not expected to cause any situation which could lead to ingestion. If this product is swallowed, CALL PHYSICIAN OR POISON CONTROL CENTER FOR MOST CURRENT INFORMATION.

If professional advice is not available, do not induce vomiting. Never induce vomiting or give diluents (milk or water) to someone who is unconscious, having convulsions, or unable to swallow.

**MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE:** Persons with impaired respiratory function, skin or eye conditions may be more susceptible to the effect of this substance.

**RECOMMENDATIONS TO PHYSICIANS:** Treat symptoms and eliminate overexposure.

## 5. FIRE-FIGHTING MEASURES

**FLASH POINT:** Non-Flammable

**AUTOIGNITION TEMPERATURE:** Not Applicable

**FLAMMABLE LIMITS (in air by volume, %):** Lower NA Upper NA

**FIRE EXTINGUISHING MATERIALS:** Use fire extinguishing methods below:

Water Spray: Yes

Carbon Dioxide: Yes

# MATERIAL SAFETY DATA SHEET

Foam: Yes

Dry Chemical: Yes

Halon: Yes

Other: Any "C" Class

**UNUSUAL FIRE AND EXPLOSION HAZARDS:** Not considered a fire or explosion hazard.

Explosion Sensitivity to Mechanical Impact: No

Explosion Sensitivity to Static Discharge: No

**SPECIAL FIRE-FIGHTING PROCEDURES:** Incipient fire responders should wear eye protection. Structural firefighters must wear Self-Contained Breathing Apparatus and full protective equipment. Isolate materials not yet involved in the fire and protect personnel. Move containers from fire area if this can be done without risk; otherwise, cool with carefully applied water spray. If possible, prevent runoff water from entering storm drains, bodies of water, or other environmentally sensitive areas.

## 6. ACCIDENTAL RELEASE

### MEASURES

**SPILL AND LEAK RESPONSE:** Proper protective equipment should be used. Stop the flow of material, if this can be done safely. Contain discharged material. Absorb spill using an absorbent, non-combustible material such as earth, sand, or vermiculite. Do not use combustible materials such as sawdust. Provide ventilation. Place in a proper container for reclamation or disposal. Dispose of in accordance with U.S. Federal, State, and local hazardous waste disposal regulations and those of Canada and its Provinces, those of Australia, Japan and EU Member States (see Section 13, Disposal Considerations).

## 7. HANDLING and STORAGE

**WORK PRACTICES AND HYGIENE PRACTICES:** As with all chemicals, avoid getting this product ON YOU or IN YOU. Wash thoroughly after handling this product. Do not eat, drink, smoke, or apply cosmetics while handling this product. Avoid breathing dusts generated by this product. Use in a well-ventilated location. Remove contaminated clothing immediately.

**STORAGE AND HANDLING PRACTICES:** Containers of this product must be properly labeled. Empty containers should be handled with care. Store containers in a cool, dry location. Keep container tightly closed when not in use.

## 8. EXPOSURE CONTROLS - PERSONAL PROTECTION

Chemical Name	CAS#	ACGIH TLV	OSHA TWA
Manganese compounds	NA	0.2 mg/m <sup>3</sup>	5 mg/m <sup>3</sup>
Sodium Dichromate	7789-12-0	0.05 mg/m <sup>3</sup>	0.001 mg/m <sup>3</sup>
Hydrochloric Acid	7647-01-0	2 ppm	7 mg/m <sup>3</sup> Ceiling

**VENTILATION AND ENGINEERING CONTROLS:** Use with adequate ventilation to ensure exposure levels are maintained below the limits provided below. Use a chemical fume hood or local exhaust ventilation, and process enclosure if necessary, to control airborne dust. Ensure eyewash/safety shower stations are available near areas where this product is used.

*The following information on appropriate Personal Protective Equipment is provided to assist employers in complying with OSHA regulations found in 29 CFR Subpart I (beginning at 1910.132) or equivalent standard of Canada, or standards of EU member states (including EN 149 for respiratory PPE, and EN 166 for face/eye protection), and those of Japan. Please reference applicable regulations and standards for relevant details.*

**RESPIRATORY PROTECTION:** Maintain airborne contaminant concentrations below guidelines listed above, if applicable. If necessary, use only respiratory protection authorized in the U.S. Federal OSHA Respiratory Protection Standard (29 CFR 1910.134), equivalent U.S. State standards, Canadian CSA Standard Z94.4-93, the European Standard EN149, or EU member states.

**EYE PROTECTION:** Safety glasses or goggles are recommended. If necessary, refer to U.S. OSHA 29 CFR 1910.133, Canadian Standards, and the European Standard EN166, Australian Standards, or relevant Japanese Standards.

**HAND PROTECTION:** Use chemically-resistant gloves when handling this product. If necessary, refer to U.S. OSHA 29 CFR 1910.138, the European Standard DIN EN 374, the appropriate Standards of Canada, Australian Standards, or relevant Japanese Standards.

**BODY PROTECTION:** Use body protection appropriate for task (e.g. lab coat, overalls). If necessary, refer to appropriate Standards of Canada, or appropriate Standards of the EU, Australian Standards, or relevant Japanese Standards. If a hazard of injury to the feet exists due to falling objects, rolling objects, where objects may pierce the soles of the feet or where employee's feet may be exposed to electrical hazards, use foot protection, as described in U.S. OSHA 29 CFR 1910.136.

# MATERIAL SAFETY DATA SHEET

## 9. PHYSICAL and CHEMICAL

### PROPERTIES

**VAPOR DENSITY:** No Data

**DENSITY:** No Data

**SOLUBILITY IN WATER:** No Data

**VAPOR PRESSURE, mm Hg @ 20°C (68°F):** No Data

**ODOR THRESHOLD:** Odorless

**APPEARANCE and COLOR:** Dark red-brown liquid with a pungent odor

**EVAPORATION RATE (n-BuAc=1):** No Data

**MELTING POINT:** No Data

**BOILING POINT:** No Data

**pH:** No Data

**SPECIFIC GRAVITY:** No Data

## 10. STABILITY and

### REACTIVITY

**STABILITY:** Stable under conditions of normal storage and use.

**HAZARDOUS DECOMPOSITION PRODUCTS:** Oxides of the contained metal and halogen, possibly also free or ionic halogen, hydrogen chloride, chlorine, hydrogen gas.

**MATERIALS WITH WHICH SUBSTANCE IS INCOMPATIBLE:** Strong reducing agents, hydrogen peroxide, potassium, sodium and zinc.

**POSSIBILITY OF HAZARDOUS REACTIONS:** Will not occur.

**CONDITIONS TO AVOID:** Incompatible materials

## 11. TOXICOLOGICAL

### INFORMATION

#### TOXICITY DATA:

Water CAS# 7732-18-5:

Oral, rat: LD50 = >90 mL/kg;

Manganese Chloride CAS# 7773-01-5:

Oral, mouse: LD50 = 1031 mg/kg;

Oral, mouse: LD50 = 450 mg/kg;

Oral, rat: LD50 = 250 mg/kg;

Sodium Dichromate CAS# 7789-12-0:

Oral, rat: LD50 = 50 mg/kg;

Hydrochloric Acid CAS# 7647-01-0:

Inhalation, mouse: LC50 = 1108 ppm/1H;

Inhalation, mouse: LC50 = 20487 mg/m<sup>3</sup>/5M;

Inhalation, mouse: LC50 = 3940 mg/m<sup>3</sup>/30M;

Inhalation, mouse: LC50 = 8300 mg/m<sup>3</sup>/30M;

Inhalation, rat: LC50 = 3124 ppm/1H;

Inhalation, rat: LC50 = 60938 mg/m<sup>3</sup>/5M;

Inhalation, rat: LC50 = 7004 mg/m<sup>3</sup>/30M;

Inhalation, rat: LC50 = 45000 mg/m<sup>3</sup>/5M;

Inhalation, rat: LC50 = 8300 mg/m<sup>3</sup>/30M;

Oral, rabbit: LD50 = 900 mg/kg;

**SUSPECTED CANCER AGENT:** Ingredients within this product are found on the following lists: FEDERAL OSHA Z LIST, NTP, IARC, or CAL/OSHA and therefore are considered to be, or suspected to be, cancer-causing agents by these agencies.

**CARCINOGENIC EFFECTS:**

CAS# 7789-12-0:

- **ACGIH:** A1 - Confirmed Human Carcinogen (listed as 'Chromium (VI) compounds- watersoluble').
- **California:** carcinogen, initial date 2/27/87 (listed as Chromium (VI) compounds).
- **NTP:** Known carcinogen (listed as Chromium (VI) compounds).
- **IARC:** Group 1 carcinogen (listed as Chromium (VI) compounds).

**IRRITANCY OF PRODUCT:** This product can be irritating to the skin, eyes, and respiratory system with prolonged contact.

**SENSITIZATION TO THE PRODUCT:** This product may cause sensitization by skin contact and inhalation.

**REPRODUCTIVE TOXICITY INFORMATION:** No information concerning the effects of this product and its components on the human reproductive system.

## 12. ECOLOGICAL

### INFORMATION

# MATERIAL SAFETY DATA SHEET

ALL WORK PRACTICES MUST BE AIMED AT ELIMINATING ENVIRONMENTAL CONTAMINATION.

**ENVIRONMENTAL STABILITY:** No specific data available on this product.

**CHEMICAL EFFECT ON PLANTS, ANIMALS AND AQUATIC LIFE:** This product is expected to be harmful to aquatic life with possible long lasting effects.

# MATERIAL SAFETY DATA SHEET

## 13. DISPOSAL

### CONSIDERATIONS

**PREPARING WASTES FOR DISPOSAL:** Waste disposal must be in accordance with appropriate U.S. Federal, State, and local regulations, those of Canada, Australia, EU Member States and Japan.

## 14. TRANSPORTATION

### INFORMATION

US DOT, IATA, IMO, ADR:

**U.S. DEPARTMENT OF TRANSPORTATION (DOT) SHIPPING REGULATIONS:** This product is classified (per 49 CFR 172.101) by the U.S. Department of Transportation, as follows.

**PROPER SHIPPING NAME:** CORROSIVE LIQUID, INORGANIC, N.O.S. (CONTAINS SODIUM DICHROMATE AND HYDROCHLORIC ACID)

**HAZARD CLASS NUMBER and DESCRIPTION:** CLASS 8 CORROSIVE

**UN IDENTIFICATION NUMBER:** UN 3264

**PACKING GROUP:** III

**DOT LABEL(S) REQUIRED:** Corrosive

**NORTH AMERICAN EMERGENCY RESPONSE GUIDEBOOK NUMBER:** 154

**RQ QUANTITY:**

**MARINE POLLUTANT:** The components of this product are not designated by the Department of Transportation to be Marine Pollutants (49 CFR 172.101, Appendix B).

**INTERNATIONAL AIR TRANSPORT ASSOCIATION SHIPPING INFORMATION (IATA):** This product is considered as dangerous goods.

**INTERNATIONAL MARITIME ORGANIZATION SHIPPING INFORMATION (IMO):** This product is considered as dangerous goods.

**EUROPEAN AGREEMENT CONCERNING THE INTERNATIONAL CARRIAGE OF DANGEROUS GOODS BY ROAD (ADR):** This product is considered by the United Nations Economic Commission for Europe to be dangerous goods.

## 15. REGULATORY INFORMATION

### UNITED STATES REGULATIONS:

**U.S. SARA REPORTING REQUIREMENTS:** The components of this product are Not subject to the reporting requirements of Sections 302, 304, and 313 of Title III of the Superfund Amendments and Reauthorization Act.

This material contains Manganese chloride (listed as Manganese compounds, n.o.s.), 5 – 15% and is subject to SARA 313 Reporting.

**U.S. SARA THRESHOLD PLANNING QUANTITY:** There are no specific Threshold Planning Quantities for the components of this product. The default Federal MSDS submission and inventory requirement filing threshold of 10,000 lbs (4,540 kg) therefore applies, per 40 CFR 370.20.

**U.S. CERCLAREPORTABLE QUANTITY (RQ):** Sodium Dichromate CAS# 7789-12-0, 10 Lbs (4.54 kg).

**U.S. TSCA INVENTORY STATUS:** The components of this product are listed on the TSCA Inventory or are exempted from listing.

### OTHER U.S. FEDERAL REGULATIONS:

**CLEAN AIR ACT:** CAS# 7773-01-5 (listed as Manganese compounds, n.o.s.) is listed as a hazardous air pollutant (HAP). CAS# 7647-01-0 is listed as a hazardous air pollutant (HAP).

**CLEAN WATER ACT:** CAS# 7647-01-0 is listed as a Hazardous Substance under the CWA.

**CALIFORNIA SAFE DRINKING WATER AND TOXIC ENFORCEMENT ACT (PROPOSITION 65):** Ingredients within this product are on the Proposition 65 Lists.

**WARNING!** This product contains ingredients that are known to the State of California to cause cancer or reproductive harm.

### CANADIAN REGULATIONS:

**CANADIAN DSL/NDL INVENTORY STATUS:** The components of this product are on the DSL Inventory, or are exempted from listing.

**OTHER CANADIAN REGULATIONS:** Not applicable.

### CANADIAN ENVIRONMENTAL PROTECTION ACT (CEPA) PRIORITIES SUBSTANCES LISTS:

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all of the information required by those regulations.

# MATERIAL SAFETY DATA SHEET

**CANADIAN WHMIS CLASSIFICATION and SYMBOLS:** This product has a WHMIS classification of D1A, D2A, C



# MATERIAL SAFETY DATA SHEET

## EUROPEAN ECONOMIC COMMUNITY INFORMATION:

**EU LABELING AND CLASSIFICATION:** This product meets the definition of the following hazard class as defined by the European Economic Community Guidelines.

**EU CLASSIFICATION:** [Xi] Irritant, [Xn] Harmful, [T] Toxic

**EU RISK PHRASES:** R21: Harmful in contact with skin; R25: Toxic if swallowed; R26: Toxic by inhalation; R34: Causes burns; R36/37/38: Irritating to eyes, respiratory system and skin; R42/43: May cause sensitization by inhalation and skin contact; R45: May cause cancer.

**EU SAFETY PHRASES:** S37/39: Wear suitable gloves and eye/face protection; S45: In case of accident or if you feel unwell, seek medical advice immediately; S53: Avoid exposure; S61: Avoid release to the environment.



**AUSTRALIAN INFORMATION FOR PRODUCT:** The components of this product are listed on the International Chemical Inventory list.

## JAPANESE INFORMATION FOR PRODUCT:

**JAPANESE MINISTER OF INTERNATIONAL TRADE AND INDUSTRY (MITI) STATUS:** The components of this product are not listed as Class I Specified Chemical Substances, Class II Specified Chemical Substances, or Designated Chemical Substances by the Japanese MITI.

**JAPANESE ENCS INVENTORY:** The components of this product are on the ENCS Inventory as indicated in the section on International Chemical Inventories, below.

**POISONOUS AND DELETERIOUS SUBSTANCES CONTROL LAW:** No component of this product is a listed Specified Poisonous Substance under the Poisonous and Deleterious Substances Control Law.

## INTERNATIONAL CHEMICAL INVENTORIES:

Listing of the components on individual country Chemical Inventories is as follows:

Asia-Pac: Listed or exempt

Australian Inventory of Chemical Substances (AICS): Listed or exempt

Korean Existing Chemicals List (ECL): Listed or exempt

Japanese Existing National Inventory of Chemical Substances (ENCS): Listed or exempt

Philippines Inventory of Chemicals and Chemical Substances (PICCS): Listed or exempt

Swiss Giftliste List of Toxic Substances: Listed or exempt

U.S. TSCA: Listed or exempt

## 16. OTHER INFORMATION

**PREPARED BY:** R. Engle

**DATE OF PRINTING:** 10/11/23

The information contained herein is believed to be accurate but is not warranted to be so. Data and calculations are based on information furnished by the manufacturer of the product and manufacturers of the components of the product. Users are advised to confirm in advance of the need that information is current, applicable and suited to the circumstances of use. Legacy Industrial Corp. assumes no responsibility for injury to vendee or third party person proximately caused by the material if reasonable safety procedures are not adhered to as stipulated in the data sheet. Furthermore, Legacy Industrial Corp. assumes no responsibility for injury caused by abnormal use of this material even if reasonable safety procedures are followed.

**END OF MSDS SHEET**