Cali-Clear™ Concrete Sealer

Product Description

Cali-Clear™ is a gloss finish, non-yellowing, acrylic, water-based, sealer. **Cali-Clear™** is highly durable and traffic resistant. It is designed for use on interior surfaces including concrete and epoxy-coated surfaces. **Cali-Clear™'s** UV resistant formula will not yellow or cloud over time. Useful over raw/stained or epoxy-coated concrete in a multitude of applications.

Features and Benefits

Dustproofs and helps to eliminate efflorescence in concrete
Creates a topical barrier to stains
Attractive gloss finish
Low VOC, 24 Hour Pot-Life, Fast Cure
Useful over raw concrete, stained concrete, epoxy coatings, flake systems

Recommended Applications

Cali-Clear™ is recommended for all interior concrete or epoxy coated surfaces. Especially useful for stained concrete applications and flake floors. Low smell is useful for basements & enclosed spaces

Technical Data

Solids: 25%
VOC Level: <65 g/l
Dry time: 1-2 hour
Recoat time: 2 to 3 hours
Pot-Life: 24 Hours
Finish: satin

Appearance: milky white
Abrasion Resistance: Good
Concrete Adhesion: Good
Foot traffic: 4 hours
Wheel traffic: 48 hours
Application temp: 55-100 degrees f

Coverage Rates

Coat 1: 300 sq ft (raw concrete) 400 sq ft (coated concrete)
Coat 2: 400 sq ft (raw concrete) 425 sq ft (coated concrete)

Shelf-Life

Cali-Clear™ has a one year shelf life in an unopened container. Protect from freezing or extreme heat.

Packaging

One gallon, 2 5 Gallon & 50 Gallon units

Legacy Industrial Products LLC
570 Lake Cook Rd. Ste 300, Deerfield, IL 60015
1-(888)-652-0333 - sales@legacyindustrial.co - www.legacyindustrial.co

Instructions for Use

All dirt, oil, dust, foreign contaminants and laitance must be removed to assure a trouble free application. The substrate should show no visible moisture prior to application. Pressure washing equipment can be used as well. Interior or smooth-texture surfaces should always be etched prior to use. Epoxy-Coated floors less than 24 hours old, no further prep, if older, de-gloss prior to use. Stir material before using. Apply material to the horizontal surface without thinning with a 3/8" roller or low-pressure sprayer. When applying the material, always maintain a wet edge as this will reduce any chance of lap marks. Do not allow to puddle. Normally two coats is all that is required. However multiple coats are acceptable. Non-skid media can be added to this product. Soft-Skid is recommended and should be mixed in prior to rolling.

Clean-Up

Use soap & water

Product Removal

This product can be stripped using an aggressive stripper or mechanically removed using grinding equipment

Precautions and Limitations

Restrict the use of the floor to light traffic and non-harsh chemicals 24 hours has passed. Keep the floor dry for this period. Always test cleaners prior to use. This product is not suitable for exterior use. Do not apply too thick or it will fracture, peel and or fail. Water based products are not suitable for water immersion.

NOTICE TO BUYER: DISCLAIMER OF WARRANTIES AND LIMITATIONS ON OUR LIABILITY

We warrant that our product is manufactured to the specifications as stated her or in other publications. All other information supplied by us is accurate to the best of our knowledge. Such information supplied about our products is not a representation or a warranty. It is supplied on the condition that you shall make your own tests to determine the suitability of our product for your particular purpose. ***NO WARRANTY IS MADE, EXPRESSED OR IMPLIED, REGARDING SUCH OTHER INFORMATION, THE DATA ON WHICH IT IS BASED, OR THE RESULTS YOU WILL OBTAIN FROM ITS USE. NO WARRANTY IS MADE, EXPRESSED OR IMPLIED, THAT OUR PRODUCT SHALL BE MERCHANTABLE OR THAT OUR PRODUCT SHALL BE FIT FOR ANY PARTICULAR PURPOSE. NO WARRANTY IS MADE THAT THE USE OF SUCH INFORMATION OR OUR PRODUCT WILL NOT INFRINGE UPON ANY PATENT****. We shall have no liability for incidental or consequential damages, direct or indirect. Our liability is limited to the net selling price of our product or the replacement of our product, at our option. Acceptance of delivery of our product means that you have accepted the terms of this warranty whether or not purchase orders or other documents state terms that or other documents state terms that vary from this warranty. No representative is authorized to make any representation or warranty or assume any other liability on our behalf with any sale of our products. Any use or application other than recommended herein is the sole responsibility of the user. Uncured epoxy resins, polymers and their curing agents may be* ***ALKALINE, TOXIC or BOTH****, depending on the particular system. They may cause* ***ALLERGIC REACTIONS or HYPERSENSITIVITY REACTIONS. BEFORE USING*** *any material,* ***READ THE MATERIAL SAFETY DATA SHEET AND FOLLOW ALL PRECAUTIONS TO PREVENT BODILY HARM.*** COPYRIGHT Legacy Industrial Products LLC.