HACKING IOT FOR BUG **BOUNTIES** bugcrowd





I am Aditya Gupta
I hack IoT devices for a living.

ABOUT ME?

- Run Attify pentesting IoT devices for companies ranging from Startups to Fortune 100s
- Author of books "Learning Pentesting for Android Devices" and "IoT Hacker's Handbook"
- Speaker and Trainer at BlackHat,
 Defcon, OWASP AppSec, ClubHack,
 PhDays, Syscan, ToorCon, InfoSec
 South West, Nullcon, CoCon and more
- IoT Pentesting Guide && Upcoming free video course

- Have pentested over 150+ IoT devices so far
- Found "critical" vulnerabilities in close to 95% of them
- Developed the "Offensive IoT Exploitation" training course
- Built <u>Attify-Store</u> to help other security researchers get tools and devices for learning IoT Hacking
- Publish videos and content online for information sharing

WHAT THIS PRESENTATION CONTAINS?

WHY?

Why you should use perform IoT bug bounties?

Why it's the "best" thing to happen for bug bounties?

WHAT?


What should you look for while doing loT security research?

What tools, techniques and devices to use? HOW?

How to actually find vulnerabilities?

Describing all the "what" sections?

How to start?



WHY TO DO IOT BUG BOUNTY HUNTING

- Yes the best thing to do in 2017
- × Easiest targets
- × Entry barrier is more than other categories though
- × There is going to be enormous growth very very very soon
- × Be prepared!

WHY TO DO IOT BUG BOUNTY HUNTING

- Less competition as of now
- Manufacturers not making secure devices
- Once you know the methodology, you can jump into it straight away



News Sport Guilty Pleasures Entertainment Life & Style

News

JK World

Weird

Money

Tech

A fridge full of spam: Hacked domestic appliances send a torrent of junk email

Monday 20 Jan 2014 10:24 pm

245 shares f Share on Facebook









When 'Smart Homes' Get Hacked: I Haunted A Complete Stranger's House Via The Internet











Kashmir Hill, FORBES STAFF 9

Welcome to The Not-So Private Parts where technology & privacy collide FULL BIO ✓ Opinions expressed by Forbes Contributors are their own.

"I can see all of the devices in your home and I think I can control them," I said to Thomas Hatley, a complete stranger in Oregon who I had rudely awoken with an early phone call on a Thursday morning.

He and his wife were still in bed. Expressing surprise, he asked me to try to turn the master bedroom lights on



The Hatleys' home was at my command after a Google search

and off. Sitting in my living room in San Francisco, I flipped the light switch with a click, and resisted the Poltergeist-like temptation to turn the television on as well.

"They just came on and now they're off," he said. "I'll be darned."



Billy Rios @XSSniper · Nov 2

As seen in a medical device update utility! #YesWeCan cc:@bobthebuilder @scotterven @charley_koontz


```
+ using ...
  namespace Upgrade Utility
      internal class FileInterface
         private const string PASSWORD = "bobthebuilder";
          private static string[] upgradeList;
          private static bool downloadKernel = true;
          private static string _upgradeVersionKeyword = string.Empty;
          private static string upgradeVersionNumber = string.Empty;
```












While on a drive through Shodan, Shawn Merdinger, a security researcher at the University of Florida, found a bunch of Caterpillar trucks that were "parked" on the open Internet. Their onboard monitoring systems were accessible with an easily guessed username/password:

CATERPILLAR®		Communicator	
	Authenticatio	on Required	×
<u>Home</u>	2	A username and password are being requested by realm"	
<u>Network</u>	User Name:		
Auto File DL	Password:	177.7	
Man File DL		ОК Са	
Manage VIMS		VIMS Ophoard T	Time 2013/09/05 11:13:55
<u>Diagnostic</u>		VIIVIS CHOUNTED	IIII 2010/07/03 11:10:30
Manage Unit Display Log Fil	<u>e</u>		



WHAT DO YOU SEE WHEN YOU SEE A DEVICE?


When you look at a device, you can figure out the possible attack vectors.


Just look closely!



WHAT TO DO ONCE YOU HAVE A TARGET

- Find out various ways to compromise the security of the entire IoT device solution
- × Don't just focus on one small part, rather look at the entire solution
- Which areas do you think would be most probably vulnerable – start there.





HOW TO START IOT BUG BOUNTY HUNTING

- Quite different from a typical pentest
- You have to focus on the entire device (not just a single component)
- × But there's a methodology for that
- × The IoT pentesting methodology iotpentestingguide.com
- Consists of 5 phases

HOW TO START IOT BUG BOUNTY HUNTING

- Attack Surface Mapping
- × Hacking the Embedded Device
- × Hacking Firmware
- × Hacking Mobile, Web and Cloud components
- Hacking Radio Communications

ATTACK SURFACE MAPPING - STEP 1

Recon

- Understand the device
- × Any visible ports
- What are the components
- × Communication mediums?


Available info

- × Google
- × Datasheets
- × Support groups
- × Community center
- Social Engineering
- × FCC ID

ATTACK SURFACE MAPPING - STEP 2

- Map out the attack surface (Architecture diagram)
- What are the various entry points
- × What are the various communication mediums used?
- × Are there any additional web endpoints?
- × What is the protocol/standard which is used?
- × Are their security specifications on the product?

CREATING AN ARCHITECTURE DIAGRAM





This is what Philips Hue Hub looks like

EW780-8913-00 Is the FCC-ID printed on the device

WHAT'S NEXT?

- Now that we have done the Attack Surface mapping, next steps are performing actual exploitation
- Need to perform it in a systematic way
- × Often one component would lead to insights into others
- × Device => Dump firmware.
- × Firmware => How does the communication works

HOW TO APPROACH IOT DEVICES TO FIND BUGS





Pentesters

HACK THE EMBEDDED DEVICE


- × Always start with the Embedded Device
- × I know most of you are not hardware hackers
- × But getting started is not "tough"
- Look for the entry points
- * How about a quick crash course in Embedded Device hacking?
- × And then point to the resources you need to learn more.


HACKING EMBEDDED DEVICE - GET STARTED

- Open up the device
- There could be physical tampering protections
- Various kind of screws get your screwdriver toolkit
- × Look at the chipsets
 - Use USB microscope (or actual ones)
 - Use phone's flashlight to read off the component names

HACKING EMBEDDED DEVICE - DIG DEEP

- Once you open up the device, look for exposed ports
- VART interfaces are the easiest to find and exploit
- Use a multimeter to find out Tx, Rx and GND
- Connect it to Attify Badge (or any USB-TTL)
- × Identify the baudrate
- Run Minicom to get shell access
- × Quick demo?





HACKING EMBEDDED DEVICE - STAG

- × Find out JTAG interface
- Can be a bit tougher compared to UART
- Can also be scattered across the board
- × Use JTAGulator or Arduino Nano flashed with JTAGEnum
- × Easily identify pinouts for JTAG

HACKING EMBEDDED DEVICE - DEBUG STAG

- Once pins are identified, make the connections
- × Runopenocd -c "telnet_port 4444" -f badge.cfg -f target-chip.cfg
- × In another terminal telnet localhost 4444
- Halt and thenflash banksdump_image firmware.bin [address] [size]

```
oit@oit:~/jtag$ sudo arm-none-eabi-gdb --eval-command="target remote localhost:3333" -----
GNU qdb (7.6.50.20131218-0ubuntu1+1) 7.6.50.20131218-cvs
Copyright (C) 2013 Free Software Foundation, Inc.
License GPLv3+: GNU GPL version 3 or later <a href="http://gnu.org/licenses/gpl.html">http://gnu.org/licenses/gpl.html</a>
This is free software: you are free to change and redistribute it.
There is NO WARRANTY, to the extent permitted by law. Type "show copying"
and "show warranty" for details.
This GDB was configured as "--host=x86 64-linux-gnu --target=arm-none-eabi".
Type "show configuration" for configuration details.
For bug reporting instructions, please see:
<a href="http://www.gnu.org/software/gdb/bugs/">http://www.gnu.org/software/gdb/bugs/>.</a>
Find the GDB manual and other documentation resources online at:
<http://www.gnu.org/software/gdb/documentation/>.
For help, type "help".
Type "apropos word" to search for commands related to "word"...
Reading symbols from stm.elf...done.
Remote debugging using localhost:3333
0x080009f0 in Reset Handler ()
(gdb) info registers
r0
                0x0
r1
                0x200004bc
                                   536872124
r2
                0x0
r3
                0x1
```

HACKING EMBEDDED DEVICE - DUMP FLASH


- Can also look for Flash chips
- You will be able to find these by reading the component name and looking online for their datasheet
- Use flashrom or spiflash.py (part of libmpsse) to dump the flash content which would contain sensitive information
- Reverse engineer the firmware

HACKING EMBEDDED DEVICE - DUMP FLASH



DUMPING FIRMWARE - LOOK AT THE DATASHEET

Package Types




DUMPING FIRMWARE - LOOK AT THE DATASHEET

root@oit:/home/attify/Downloads/libmpsse/src/examples# python spiflash.py -s 5120000 -w new.bin FT232H Future Technology Devices International, Ltd initialized at 15000000 hertz Writing 5120000 bytes from new.bin to the chip starting at address 0x0...done.

NAND GLITCHING

- × A number of devices fall vulnerable to glitching based attacks
- A way to generate fault scenario and have the processor behave in an unexpected way
- × If the bootloader fails to boot kernel, it will jump back to the bootloader shell, which is extremely useful for us as pentesters
- Short the pins and get bootloader shell
- × Flash your own kernel or bypass login + more.



http://console-cowboys.blogspot.com/2013/01/swann-song-dvr-insecurity.html

;=ph	ysı	tap	-fla	ish	.0:	414	(b	oot),	12M	(E	001	ifs),	141	f (a	pр),	2M	(pa	ra) 1	ous	c1	k=	220	000	00	00	Sĺ	ngl	e	
nux	ŧ	pr.	inte	nv																													ı
		99	Ω	20	Ω	98	88	20		99	98	8	Ω	98	8	Ω	98	\mathcal{R}		38	\mathcal{R}	99	88	\mathcal{R}	99	88	∞	99	88	88	20	Ω	

nilinux # setenv bootargs mem=68M console=ttyAMA0,115200 root=1f01 rootfstype=jffs2 mtdp

Environment size: 520/131068 butes

```
bootdelay=1
baudrate=115200
DODULTIC UTHAGE
bootcmd=showlogo;bootm 0x80100000
jpeg size=0x20000
logo addr=0x81f00000
ethaddr=06:91:36:74:DE:7B
filesize=3028
fileaddr=81F80000
gatewayip=192.168.1.1
netmask=255.255.0.0
ipaddr=192.168.1.88
serverip=192.168.1.99
stdin=serial
stdout=serial
stderr=serial
verify=n
ver=U-Boot 2008.10 (Dec 8 2011 - 15:55:01)
bootargs-mem=68M console-ttyAMA0,115200 root-1f01 rootfstype-jffs2 mtdparts-physmap-fla:
h.0:4M(boot),12M(rootfs),14M(app),2M(para) busclk=220000000 single
Entri comment eige 527/131068 bytes
hilinux # bootm 0x80100000
```

hilinux # printenv



HACK THE FIRMWARE

- Firmware analysis is extremely straight-forward (to find basic vulns)
- × If you're good in RE you would be able to identify more vulns
- × Learn ARM and MIPS RE
- Sensitive hardcoded values in firmware API keys, Encryption mechanisms, verification process, integrity checks, logins etc.)

FIRMWARE METHODOLOGY

- × Tool by Craig Heffner (@devttys0)
- × binwalk -e firmware-name.bin to extract the firmware
- × Then run "firmwalker" to look for interesting entries
- Can also try to modify the firmware with Firmware-Mod-Kit
 And flash it back to the device
- × Does the device detects firmware modifications?

EXTRACTING THE FIRMWARE

- Firmware contains file system which could be a source of tons of useful info
- Extract it using Binwalk or FMK
- × Audit it like you would look at a normal Linux file system
- × Look for additional vulns which could affect the device
- Advanced topics signature & integrity verification, OTA
 Update mechanism and more

ENCRYPTION?

- Firmware could be encrypted sometime
- Let's take a quick look at one of the encryptions
- Vuln discovered by Roberto Paleari(@rpaleari) and Alessandro Di Pinto (@adipinto)

ENCRYPTION?

WinFi Gigabit Router N300 | WLRn4004







A fast wireless-N router with speed of up to 300 Mbps

Wireless speed: 300 MbpsGood wireless coverage: 2 internal antennas

• Wired speed: 4 Gigabit (1000 Mbps) ports


HARDCODED SENSITIVE VALUES

- One of the easiest bugs to identify
- For ex this IoT device I was pentesting it had creds to its
 FTP server to download firmware updates
- You can find ton of hardcoded sensitive values API keys, backdoors, SSL certs, Staging URLs, source code of files to find more vulns, interesting binaries to perform reverse eng.

QUICK BINARY ANALYSIS OF ANOTHER FW




QUICK BINARY ANALYSIS OF ANOTHER FW



QUICK BINARY ANALYSIS OF ANOTHER FW

```
🗾 🚄 🖼
loc D4714
ADD
                R3, R2, #0x22C0
ADD
                R2, R2, #0x2280
ADD
                R2, R2, #0x28
ADD
                R3, R3, #0xC
LDR
                R1, =aUsrSbinAdslCon; "/usr/sbin/adsl-config eth0 %s %s"
MOV
                RO, R8
BL
                sprintf 👉
MOV
                RO, R8
BL
                printf
MOV
                 RO, R8
                syst<mark>em   </mark>
BL
MOV
                RO, #0x3E8
BL
                usleep
LDR
                R0, =aSbinIfconfig 2; "/sbin/ifconfig eth0 up mtu 1500"
BL
                system
LDR
                RO, =aUsrSbinAdslSta ; "/usr/sbin/adsl-start&"
```



```
.text:000267B0
                                  LW
                                            $ra, 28($sp)
                                  MOVE
.text:000267B4
                                            $t9,
                                                                         ; PRE: $s0=socket /POST: $t9=socket
                                            $a0, 2h
.text:000267B8
                                            $s0, 18h($sp)
.text:000267BC
                                  LW
                                                                            Points to next gadget
.text:000267C0
                                            $a1, 1h
.text:000267C4
                                  MOVE
                                            $a2, $zero
                                                                         ; -:$sp.+ 28:(+144:+54)
                                            $t9
$sp, 20h
.text:000267C8
                                  JR
                                  ADDIU
.text:000267CC
.text:000267D0
                  loc_267D0:
.text:000267D0
                                  LW
                                            $ra, 28($sp)
                                                                         ; xref: loc_267A4
.text:000267D4
                                  LW
                                            $s0, 18h($sp)
.text:000267D8
                                            $ra
                                            $sp, $sp, 20h
.text:000267DC
                                  ADDIU
                                                                       Controllable via $s0 (previous
.text:000267DC
                  sub 26770
.text:000267DC
                                  endp
                                                                       gadget) => should point-to-----
                                                                       sleep
                                    ROUTINE
                                                 032 int inet aton/chart
```

```
.text:000171CC
                                    ADDIU
                                              $a0, $sp, 24
.text:000171D0
                                    MOVE
                                              $t9. $s3
                                                                            ; PRE: $s3=_pthread_cleanup_pop_restore
.text:000171D4
                                    JALR
                                             $t9
                                                                            ; -> _pthread_cleanup_pop_restore /PRE:
                                              $a1, 1h
.text:000171D8
.text:000171DC
                                    LW
                                              $gp, 10h($10)
                                                                            ; xref: loc_171D4
.text:000171E0
                  loc_171E0:
                                             $v0, $s2
.text:000171E0
                                    MOVE
                                                                            ; PRE: $s2=gvar_30 /POST: $v0=gvar_30
                                                                            ; xref: loc_171C0
.text:000171E4
                                    LW
                                              $ra, 5Ch($sp)
                                              $fp, 58h($sp)
.text:000171E8
                                                                               System arg
.text:000171EC
                                              $s7, 54h($sp)
                                              $s6, 50h($sp)
.text:000171F0
                                              $s5, 4Ch($sp)
.text:000171F4
                                              $s4, 48h($sp)
.text:000171F8
                                             $s3, 44h($sp)
.text:000171FC
.text:00017200
                                              $s2, 40h($sp)
                                              $s1, 3Ch($sp)
.text:00017204
                                              $s0, 38h($sp)
.text:00017208
                                                                           Can control $s3 via 1st
.text:0001720C
                                              $ra
                                    ADDIU
.text:00017210
                                             $sp, $sp, 60h
                                                                           gadget => system
.text:00017210
.text:00017210
                   freopen
                                    endp
.text:00017214
                                    db 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0
                                    ; Signature: __o32 int fseek(FILE* __stream, long __off, int __whence)
.text:00017220
                   fseek
                                    proc
```


```
140 + 54 = 194 (Address of gadget 2) -> libc + 267b0

104 + 54 = 158 (Address of sleep) -> libc + 2f2b0

28 + 144 + 54 = 226 (Address of gadget 3) -> libc + 171cc

24 + 32 + 144 + 54 = 254 (argument to system)

116 + 54 = 170 (Address of system) -> libc + 2bfd0
```



ANALYZING MOBILE APPS

- × Mobile apps can help you find tons of useful information
- × Native libraries also store secrets <== so look at that too</p>
- × RE the ARM native library
- Understand the Java code
- × Make connections
- × Exploit the device

THESE KIND OF UULNS

WeMo also uses a GPG-based, encrypted firmware distribution scheme to maintain device integrity during updates.


Unfortunately, attackers can easily bypass most of these features due to the way they are currently implemented in the WeMo product line. The command for performing firmware updates is initiated over the Internet from a paired device. Also, firmware update notices are delivered through an RSS-like mechanism to the paired device, rather than the WeMo device itself, which is distributed over a non-encrypted channel. As a result, attackers can easily push firmware updates to WeMo users by spoofing the RSS feed with a correctly signed firmware.

The firmware updates are encrypted using GPG, which is intended to prevent this issue. Unfortunately, Belkin misuses the GPG asymmetric encryption functionality forcing it to distribute the firmware-signing key within the WeMo firmware image. Most likely, Belkin intended to use the symmetric encryption with a signature and a shared public key ring. Attackers could leverage the current implementation to easily sign firmware images.

Belkin uses STUN/TURN and an exposed firmware signing key. IOActive discovered an unfortunate configuration relating to this. A lack of entropy on the device results on less-than-random GUIDs. IOActive also discovered that the WeMo restful service endpoint is vulnerable to attack. We reported to Belkin an arbitrary file download flaw relating to this.

http://www.ioactive.com/pdfs/IOActive_Belkin-advisory-lite.pdf

DIFFING FOR VULNS






MQTT, CoAP, Radio, ZigBee, BLE and 100 others.

HACKING COMMUNICATION

- × Can start with something that you are already familiar with
- × Reverse engineer the mobile app <==> device communication
- × Does it also uses things like MQTT? Or CoAP?
- × Allows you to view resources unauthenticated?
- × Publish messages or subscribe to topics?

```
oit@ubuntu [01:33:22 PM] [~]
-> % mosquitto_sub -v -h -p 1883 -t '#'
ActiveMQ/Advisory/MasterBroker (null)
ActiveMQ/Advisory/Consumer/Topic/# (null)
VirtualTopic/tim/chat/ctc {"MsgBody":[{"MsgType":"TIMCustomElem","MsgContent":{"
Desc":"", "Data": "CAMQABpLCkk8YSBocmVmPSJ1aWQ60TkxMzIxOHxuYW110umYv+epuiI+6Zi/56m
6PC9hPue7meS9oOmAgeS6huekvOeJqeeUnOeUnOWciFgx", "Ext": ""}}], "CallbackCommand": "C2
C.CallbackAfterSendMsg", "From Account": "1", "To Account": "1464954", "MsgTime": 1498
941204}
VirtualTopic/tim/chat/ctc {"MsgBody":[{"MsgType":"TIMCustomElem","MsgContent":{"
Desc":"有一条新的消息","Data":"CGoQABoRCgo0MTq1MTq1MzMzEM7S3QQ=","Ext":""}}],"Ca
11backCommand": "C2C.CallbackAfterSendMsg", "From_Account": "9922894", "To_Account":
"2048143", "MsqTime":1498941204}
VirtualTopic/tim/chat/ctc {"MsgBody":[{"MsgType":"TIMCustomElem","MsgContent":{"
Desc":"有一条新的消息","Data":"CGoQABoQCgk5MTE2NjUwNzEQ3ozSBA==","Ext":""}}],"Ca
11backCommand": "C2C.CallbackAfterSendMsg", "From_Account": "9733726", "To_Account":
"9687415", "MsqTime":1498941204}
VirtualTopic/tim/chat/ctc {"MsqBodv":[{"MsqTvpe":"TIMCustomElem","MsqContent":{"
Desc":"妹子hhh同意与你成为假装情侣","Data":"CC0QABqEAQqBAQjj1N4DEqnlprnlrZBoaGqa
Zmh0dHA6Ly83eHFkZjcuY29tMS56MC5nbGIuY2xvdWRkbi5jb20vd2VIZWFkSW1hZ2UvMjAxNy8wMi8x
MS82NDQ00WNhZTU0MjUzYTI1YzAwMTFiYTM0NTMwNmFjNi1pY29uLmpwZyACMNnR7v7PKw==","Ext":
""}}], "CallbackCommand": "C2C.CallbackAfterSendMsg", "From_Account": "1", "To_Accoun
t":"6841714","MsqTime":1498941204}
VirtualTopic/tim/chat/ctc {"MsgBody":[{"MsgType":"TIMCustomElem","MsgContent":{"
Desc":"有一条新的消息","Data":"CGoQABoRCgoyNjE1MjczNDA0EJzpmwE=","Ext":""}}],"Ca
```






[Chōu chéngfá] qǐng zuìhòu yī míng jiēshòu chéngfá zài 3 gè chéngfá zhōng rènyì xuǎnzé yīgè

- 1. Qĭng pāi yī zhāng pīchā de zhàopiàn
- 2. Pāi yīgè ràng duìfāng mănyì de guǐliǎn
- 3. Qǐng yòng yǔyīn shēnqíng de shuō: Wǒ màishēn bù màiyì ō%








```
oit@ubuntu [03:43:16 PM] [~]
-> % ./exploit.sh
home/Bed_room/3 off
home/Bed_room/3/stat off
home/Bed_room/2 on
home/Bed_room/2/stat on
```

```
oit@ubuntu [03:43:16 PM] [~]
-> % ./exploit.sh ******************
home/Bed_room/3 off
home/Bed_room/2/stat off
home/Bed_room/2/stat on
home/Bed_room/3 on
```



HACKING RADIO

- × Radio analysis and exploitation needs special hardware
- Depends on what protocol you're analyzing
- × But BLE and ZigBee are most common so focus on those
- What kind of vulnerabilities can you identify?

HACKING ZIGBEE

- One of the most common Radio communication protocols used in IoT devices
- × 2.4 GHz (mostly), 868 MHz (EU) and 933 (US and Australia)
- × KillerBee firmware for RzRaven and API
- × Sniff, MITM and replay ZigBee packets
- Philips Hue Demo



HACKING BLE

- × Hacking BLE is extremely straightforward (don't I say that to everything):)
- × Get a BLE sniffer Ubertooth or Adafruit BLE Sniffer
- × Sniff BLE traffic
- × See which handles are being written with what data
- Rewrite those handles by yourself using Gatttool Quick demo

ADITYA'S PENTESTING METHODOLOGY

- × Here's how I pentest:
 - Focus on "Attacker Simulated Exploitation" rather than just a pentest
 - × Look at both "macro" and "micro"
 - 95% success rate so far Critical vulns identified, devices compromised and more
 - Follow the guide



I started writing the techniques and methodology I use to pentest IoT devices to help fellow community members!





WWW.IOTPENTESTINGGUIDE.COM going to be adding more details soon!

RECENT PENTESTS (1ST WEEK OF JULY '17)

	FIRMWARE	HARDWARE	RADIO				
xx Smart home system	Password to decrypt fw and update URLs	JTAG & SPI giving full firmware access	BLE replay, ZigBee replay				
xx enterprise communication platform	Config files revealing credentials	NAND glitching leading to custom fw loading	Cellular vulnerable to sniffing				
xx payment system	No secure integrity protection & command injections	Bypassing tamper resistance and JTAG re-enabled	Insecure CRC verification – cracked				



coz it won't be always like the 2017s...



CONCLUDING - VULNS

H/W

- × UART exploitation
- JTAG debugging and exploitation
- Firmware dumping via Flash
- × NAND Glitching
- Power and Voltage analysis

Firmware

- × Reversing file system
- Hardcoded sensitive values
- Emulating the firmware and real-time debugging
- Binary analysis and Reverse Engineering ARM and MIPS

Radio

- Sniffing Radio communication
- Making sense out of radio data
- Sniffing and Exploiting BLE devices
- Sniffing and Exploiting ZigBee devices

THANK YOU!

Special thanks to BugCrowd & all the people who joined this session:

- × Reach out to me on Twitter @adi1391
- For training/pentesting <u>secure@attify.com</u>
- × For learning kits: <u>attify-store.com</u>
- × For slides & materials http://iotpentestingguide.com