



ASENSE ROOM

CO2 Room Sensor with Relay Option

The ASENSE Room series monitors the carbon dioxide (CO2) levels in commercial, school, and office type environments. The concentration of CO2 is a strong indication of the overall indoor air quality. The ASENSE Series is based on a single beam non-dispersive infrared technology and is a cost-optimized solution for the climate control of buildings and other processes. In addition, ABC software eliminates the need for manual calibration. The ASENSE Series measures the CO2 concentration in the ambient air up to 2,000 ppm and converts the data into an analog output. This data can be used in conjunction with a Building Automation or Demand Control Ventilation System to create a healthier indoor climate. This series features an analog temperature output (32 to 122°F) and come with combined output options of 0-10 VDC and 0

to 20 mA (4 to 20 mA and 2-10 VDC are field selectable via an onboard jumper) or 0-5 VDC for "-5" versions. A relay option is available for this series as well. The UIP5 software and programming cable offer a configuration/test utility and provide access to the main features of the ASENSE series.

Applications: Commercial Office Buildings, Gymnasiums, Shopping Malls, Auditoriums, Theaters, Hospitals & Schools

The ASENSE Room Series is covered by ACI's Five (5) Year Limited Warranty. The warranty can be found in the front of ACI's Sensors & Transmitters catalog, as well as on ACI's website, www.workaci.com.

PRODUCT SPECIFICATIONS

Supply Voltage:	24 VAC/VDC ±20%; 50/60 Hz, 10.5 to 40 VDC maximum (Half-wave rectified)
Power Consumption:	<1W
Wiring Connections:	0.00232 in ² (1.5 mm ²) screw terminals
Operating Environment:	Residential, commercial and industrial spaces
Operating Temperature:	32°F to 122°F (0°C to 50°C)
Operating RH:	0 to 85% RH Non-condensing
Warm-Up Time:	<5 minutes (@ full specs 15 minutes)
Accuracy:	CO2: ±30 ppm ±3% of reading Temperature: ±1.8°F (1°C)
Repeatability:	±20 ppm ±1% of measured value
Annual Zero Drift:	<± 0.3% of measurement range
Operating Pressure:	+1.6% per 0.145 psi (1 kPa) deviation from normal pressure (1 Atmosphere = 14.7 psi (1.013 KPa))
Sensing Method:	Single beam Non-dispersive Infrared (NDIR)
Sensor Life ²:	>15 years
Response Time (T1/e):	<10 seconds @ 30 cc/minutes flow rate, <3 minutes diffusion time
Sensing Range:	CO2: 0 to 2000 ppm Temperature: -4 to 140°F (-20 to 60°C)
Extended CO2 Ranges:	Up to 10,000 ppm (factory set or programming cable required)
Extended Range Accuracy:	Typically < (+/- 30 ppm +/- 20% of measured value)
Coverage Area:	7500 sq. ft. maximum
Mounting Height:	4-6' off the floor
Self-Diagnostics:	Complete function check, yellow LED; LCD error indication (display model only)
Display (Optional):	4 digits, 7 segments LCD with ppm indicator
Calibration ³:	Senseair ABC algorithm (Automatic Baseline Correction)
Outputs:	Output 1 (CO2): 0/2 to 10V, 0/4 to 20 mA, 0 to 2000 ppm Output 2 (Temperature): 0/2 to 10V, 0/4 to 20 mA, 32 to 122°F (0 to 50°C) Output 3: N.O. or N.C. rated 0.5A @ 125 VAC; 1A @ 24 VDC
Relay (Optional):	
Relay Trip Point:	1000 ppm (factory set)
Relay Deadband/Hysteresis:	100 ppm (factory set)
Relay Durability:	Mechanical: 5,000,000 operations minimum (at 36,000 operations/hr) Electrical: 100,000 operations minimum (under rated load, at 1,800 operations/hr)
Storage:	Standard Versions: -40 to 158°F (-40 to 70°C) LCD Versions: -4 to 122°F (-20 to 50°C) 0 to 85% RH Non-condensing
Enclosure:	ABS, Flammability Rating UL94-HB
Product Dimensions:	ASENSE-R & ASENSE-R-LCD: (H) 5.12" (130 mm) x (W) 3.35" (85.1 mm) x (D) 1.18" (30 mm) ASENSE-IP54: (H) 5.95" (151.9 mm) x (W) 3.33" (84.6 mm) x (D) 1.85" (47 mm)
Product Weight:	ASENSE-R: 0.300 lbs (0.136 kg) ASENSE-R-LCD: 0.314 lbs (0.142 kg)
Agency Approvals:	EMC Directive 2014/30/EC, RoHS Directive 2011/65/EU & RoHS 3 Directive 2015/863/EU




Note 1: Accuracy is defined after minimum three (3) ABC periods (1 period = 8 days) of continuous operations | **Note 2:** In normal Indoor Air Quality (IAQ) applications | Corrosive environments are excluded | **Note 3:** Building CO2 levels must drop to 400 ppm some time during the week for ABC to work properly | If the building is occupied 24 hrs/day, ABC must be turned off | Changes can be made using TTL-232R-3V3 cable and UIP5 software








DIMENSIONAL DRAWING

ASENSE Room (Standard)



ASENSE-IP54



Front View

Right View

Top View

STANDARD ORDERING

Model # Example: **A**SENSE-R-REL -OR- 130529

Model #	Item #	Description
ASENSE-R	131189	CO2 Room, 0-10 VDC or 0-20 mA Output, 4-20mA or 2-10 VDC Field Selectable
ASENSE-R-REL	130529	CO2 Room, 0-10 VDC or 0-20 mA Output, Relay, 4-20mA or 2-10 VDC Field Selectable
ASENSE-R-LCD	131191	CO2 Room, with Display, 0-10 VDC or 0-20 mA Output, 4-20mA or 2-10 VDC Field Selectable
ASENSE-R-LCD-REL	130530	CO2 Room, with Display, 0-10 VDC or 0-20 mA Output, Relay, 4-20mA or 2-10 VDC Field Selectable
ASENSE-R-5	133946	CO2 Room, 0-5 VDC Output
ASENSE-R-5-REL	130393	CO2 Room, 0-5 VDC Output, Relay
ASENSE-R-5-LCD	133511	CO2 Room, with Display, 0-5 VDC Output
ASENSE-R-5-LCD-REL	130531	CO2 Room, with Display, 0-5 VDC Output, Relay
ASENSE-IP54	---	CO2 Industrial Room, 0-10 VDC or 0-20 mA Output, 4-20mA or 2-10 VDC Field Selectable
ASENSE-IP54-REL	---	CO2 Industrial Room, 0-10 VDC or 0-20 mA Output, Relay, 4-20mA or 2-10 VDC Field Selectable
ASENSE-IP54-LCD	---	CO2 Industrial Room, with Display, 0-10 VDC or 0-20 mA, 4-20mA or 2-10 VDC Field Selectable
ASENSE-IP54-LCD-REL	134678	CO2 Industrial Room, with Display, 0-10 VDC or 0-20 mA, Relay, 4-20mA or 2-10 VDC Field Selectable
ASENSE-IP54-5	132732	CO2 Industrial Room, 0-5 VDC Output
ASENSE-IP54-5-REL	143962	CO2 Industrial Room, 0-5 VDC Output, Relay
ASENSE-IP54-5-LCD	---	CO2 Industrial Room, with Display, 0-5 VDC Output
ASENSE-IP54-5-LCD-REL	---	CO2 Industrial Room, with Display, 0-5 VDC Output, Relay

Note*: IP54 models not shown in Dimensional Drawings above

ACCESSORIES ORDERING

Model # Example: **A**/CUSTOM CAL GAS -OR- 140970

Model #	Item #	Description
A/CUSTOM CAL GAS*	140970	Custom Calibration
TTL-232R-3V3	134207	Programming Cable
UIP5	---	Free Software Download (Contact ACI)

Note*: Contact ACI's Technical Support for custom calibration ranges

