



5,2,1 GUARANTEE









COACHMEN RV - FOR OVER 50 YEARS...











- 4 -

X-EDITION

Model	25RE	274BH	284RL	30RLS	30BHS
Shipping Weight (lbs.)	7,213	8,632	8,848	8,921	9,475
Carrying Capacity (lbs.)	2,527	2,308	2,592	2,019	1,965
UVW (lhs.)	7,273	8,692	8,908	8,981	9,535
GVWR (lbs.)	9,800	11,000	11,500	11,000	11,500
Hitch Weight (lbs.)	1,115	1,420	1,434	1,445	1,553
Exterior Height (Includes A/C)	12'	12'	12'	12'	12'
Fresh Water Capacity (gal.)	40	40	40	40	40
Grey Water Capacity (gal.)	33	66	66	66	66
Waste Water Capacity (gal.)	33	33	33	33	33
Awning Length	13'	16'	11'	11'	15'
Wheel Size	16"	16"	16"	16"	16"
Exterior Length (Includes Bumper to Cap)	29' 10"	35' 11"	34' 2"	34' 2"	37'
Interior Height (Coach)	81"	81"	81"	81"	81"
Axles (lbs. Capacity)	5,100	5,100	5,100	5,100	5,100
Tire Size	ST235/80R16E	ST235/80R16E	ST235/80R16E	ST235/80R16E	ST235/80R16E

Model	355FBX	393MBX	
Shipping Weight (lbs.)	11,482	13,020	
Carrying Capacity (lbs.)	2,958	2,420	
UVW (lbs.)	11,542	13,080	
GVWR (lbs.)	14,500	15,500	
Hitch Weight (lbs.)	2,008	2,498	
Exterior Height (Includes A/C)	12' 5"	12' 5"	
Fresh Water Capacity (gal.)	48	48	
Grey Water Capacity (gal.)	135	85	
Waste Water Capacity (gal.)	90	45	
Awning Length	20'	20'	
Wheel Size	16"	16"	
Exterior Length (Includes Bumper to Cap)	42' 6"	42' 6"	
Interior Height (Coach)	85"	85"	
Axles (lbs. Capacity)	7,000	7,000	
Tire Size	ST235/80R16G	ST235/80R16G	


R-15+ SIDEWALL AIRCRAFT GRADE Double Welded Aluminum Frame 2LB. DENSITY Closed Cell Structural Foam CHAPARRAL "AZDEL® ROT PROOF COMPOSITE Sidewall Panel UV PROTECTED GEL COAT Exterior Panel

24/7 EMERGENCY **ROADSIDE ASSISTANCE** WITH VEHICLE PURCHASE JUMP-STARTS MOBILE MECHANIC TIRE CHANGES TECHNICAL FLUID DELIVERY SUPPORT DEALER LOCATOR SERVICES LOCKOUT SAFERIDERV

MOTOR CLUB ***VALID FOR 1 YEAR FROM DATE OF PURCHASE**

MID-PROFILE

Model	298RLS	334FL	336TSIK	360IBL	367BH	373MBRB	381RD
Shipping Weight (lbs.)	9,515	12,340	10,460	11,390	12,268	12,971	12,186
Carrying Capacity (lbs.)	2,425	2,600	2,980	2,550	3,172	1,969	2,254
UVW (lbs.)	9,575	12,400	10,520	11,450	12,328	13,031	12,246
GVWR (lbs.)	12,000	15,000	13,500	14,000	15,500	15,000	14,500
Hitch Weight (lbs.)	1,935	2,708	1,880	2,100	2,194	2,219	2,310
Exterior Height (Includes A/C)	12' 4"	12' 5"	12' 4"	12' 4"	12' 5"	12' 6"	12' 6"
Fresh Water Capacity (gal.)	48	48	48	48	48	48	48
Grey Water Capacity (gal.)	90	85	90	90	112	120	90
Waste Water Capacity (gal.)	45	45	45	45	72	75	45
Awning Length	15'	20'	16'	18'	15'	17'	20'
Wheel Size	16"	16"	16"	16"	16"	16"	16"
Exterior Length (Includes Bumper to Cap)	34' 8"	42' 6"	37'	39' 9"	42' 6"	42' 6"	42' 6"
Interior Height (Coach)	85"	85"	85"	85"	85"	85"	85"
Axles (lbs. Capacity)	5,100	7,000	7,000	7,000	7,000	7,000	7,000
Tire Size	ST235/80R16E	ST235/80R16G	ST235/80R16G	ST235/80R16G	ST235/80R16G	ST235/80R16G	ST235/80R16G



FREE MEMBERSHIP www.coachmenowners.com



PRE-DELIYERY INSPECTION FACILITY
20,000 square feet of quality assurance. The bare essentials for a premium product.
This state-of-the-art facility gives immediate daily feedback to production for quality assurance in every unit built.



YOUR LOCAL DEALER