

PALM IMPACT WRENCH



Dimensions	139×63×87mm
Weight	1.04kg
Recommended Operating Pressure	90psi (6.2bar)
Air Consumption @90psi	3.46cfm / 98l/min
Square Drive	3/8" (EQ-294 110) 1/2" (EQ-294 111)
Max. Torque	350 ft-lb / 474Nm
Free Speed	9.200rpm
Min. Hose Size	3/8" (10 mm)
Breakaway torque	550Nm
Noise Values according to EN ISO 15744	
A-weighted Sound Pressure Level at Workstation	91.3dB
A-weighted Sound Power Level	102.3dB
Vibration Values according to EN ISO 28927-2 /	
Vibration Value	9.43m/s ²

Applications: For hard to reach threaded connections on vehicles, motorcycles, machinery, steel constructions, etc.. Specially designed for: connections on brake calipers, strut mounts, shock absorbers, steering, wheel alignment, engine, suspension arms - especially on rear axles.

Technical Features:

- Maximum loosening torque: 550 Nm
- Torque even in confined spaces
- Enhanced accessibility in tight work areas
- Superior torque transmission for stubborn connections
- Universal application for automotive, truck, and industrial use
- Mueller-Tool quality guarantee, all replacement parts available from stock

EQ-294 110 3/8" Palm Impact Wrench

EQ-294 111 1/2" Palm Impact Wrench