



NOTES:

- 316 SS MAIN BODY PARTS, 18-8 SS FASTENERS, PLASTICS & ELASTOMERS
- WEIGHT: 10 lbs
- INLET: 1-1/2" SANITARY INLET & 2" CAMLOCK ADAPTER/1-1/2" FNPT
- FLOW RANGE: 30-120+ GPM
- PRESSURE: 30-500+ PSI
- MINIMUM FULL WASH CYCLE: 8-15 MINS
- TRIPLE NOZZLE MACHINE AVAILABLE
- CLEARANCE: 3.825" ID WITH CLUTCH, 6.800" ID WITH PIN, 3.790" ID WITH LOW PROFILE PARTS

THIS DRAWING IS THE PROPERTY OF GAMAJET CLEANING SYSTEMS, INC. REPRODUCTIONS AND USE OTHER THAN BORROWER'S AGREEMENT IS PROHIBITED. THIS DOCUMENT SHALL NOT BE LENT OR DISPOSED OF DIRECTLY OR INDIRECTLY NOR USED FOR ANY PURPOSE OTHER THAN THAT WHICH IS SPECIFICALLY FURNISHED.

REVISIONS TABLE			
DRAWN BY	DATE	REV.	DESCRIPTION
GES	10/15/13	1	NEW PRINT



UNLESS OTHERWISE SPECIFIED	
* DIMENSIONS ARE IN INCHES	
* DIMENSIONS REFERENCE THEORETICAL SHARP CORNERS	
* FILLET RAD.: 0.015 ±0.005	
* TOLERANCES:	
.XX ±0.01	
.XXX ±0.005	
ANGLE ±0.5°	
MATERIAL:	
316 SS	
FINISH (UNLESS OTHERWISE SPECIFIED):	
32 Ra	
SCALE 1:4	

GAMAJET CLEANING SYSTEMS, INC.		
NAME GAMAJET FLOW-THRU POWERFLEX CUT-SHEET		
EQUIPMENT GAMAJET POWER-FLEX		
DRAWN BY GES	DRAWN DATE 12/15/2010	REV 1
DWG. NO. GJ 10-2000-PF		SHEET 1 OF 18