

R Wood Windows



- Exterior wood primed and ready to accept paint.
- Interior natural wood can be painted or stained
- Foam filled weather-stripping between top and bottom sash
- Compression balance provides tilting of sash for hassle-free cleaning of exterior glass
- Entire length of bottom sash rail routed with finger lift for easy operation
































- Grill options include 1LT, GBG, or SDL. SDL may be 7/8" or 1 1/4", PVC or wood.











- Cardinal Insulated double pane glass, available clear IG or Low-E. Some sizes may be tempered.

- Non-rot Marley PVC sill standard
- Truth sash lock standard

- Primed brickmould standard. PVC brickmould & 1x4bb available
- Primed blindstop standard, PVC blindstop available

Stock Window Sizes

		Double Hung					
Masonry Opening		2 ⁰	2 ⁴	2 ⁸	3 ⁰	3 ⁴	3 ⁸
	Rough Opening	1 ¹⁰	2 ²	2 ⁶	2 ¹⁰	3 ²	3 ⁶
3 ⁶ ¼	3 ⁵ ½	 1 ⁸ x 3 ²	 2 ⁰ x 3 ²	 2 ⁴ x 3 ²	 2 ⁸ x 3 ²	 3 ⁰ x 3 ²	
4 ² ¼	4 ¹ ½		 2 ⁰ x 3 ¹⁰	 2 ⁴ x 3 ¹⁰	 2 ⁸ x 3 ¹⁰	 3 ⁰ x 3 ¹⁰	
4 ¹⁰ ¼	4 ⁹ ½	 1 ⁸ x 4 ⁶	 2 ⁰ x 4 ⁶	 2 ⁴ x 4 ⁶	 2 ⁸ x 4 ⁶	 3 ⁰ x 4 ⁶	 3 ⁴ x 4 ⁶
5 ⁶ ¼	5 ⁵ ½	 1 ⁸ x 5 ²	 2 ⁰ x 5 ²	 2 ⁴ x 5 ²	 2 ⁸ x 5 ²	 3 ⁰ x 5 ²	 3 ⁴ x 5 ²
5 ¹⁰ ¼	5 ⁹ ½		 2 ⁰ x 5 ⁶	 2 ⁴ x 5 ⁶	 2 ⁸ x 5 ⁶	 3 ⁰ x 5 ⁶	
6 ⁶ ¼	6 ⁵ ½	 1 ⁸ x 6 ²	 2 ⁰ x 6 ²	 2 ⁴ x 6 ²	 2 ⁸ x 6 ²	 3 ⁰ x 6 ²	 3 ⁴ x 6 ²

Picture		
3 ⁴	4 ⁴	5 ⁴
3 ²	4 ²	5 ²
 3 ⁰ x 3 ¹⁰	 4 ⁰ x 3 ¹⁰	
	 4 ⁰ x 4 ⁶	 5 ⁰ x 4 ⁶
 3 ⁰ x 5 ²	 4 ⁰ x 5 ²	 5 ⁰ x 5 ²
 3 ⁰ x 6 ²	 4 ⁰ x 6 ²	 5 ⁰ x 6 ²



Double Hung Sash (boot glazed)
Wood frame, double glazed
Low E coating (e=0.042, s2)

Energy Performance Ratings	
U-Factor (U.S./I-P)	Solar Heat Gain coefficient
0.38	0.31
Additional Performance Ratings	
Visible Transmittance	Condensation Resistance
.52	52

