



Jeld-Wen Product Approvals

Wind Borne Debris Regions (WBDR) Product Approvals

Pro Series Fiberglass Smooth and Textured) WBDR Impact Rated Opaque (Solid) Doors

FL Number	Maximum Door Size	Unit Config	Swing	DP Rating
16674.2	3'0" x 6'8"	X	IS/OS	+50/-50
16674.4	6'0" x 6'8"	XX	IS/OS	+50/-50
16674.6	3'0" x 6'8"	O	Fixed	+65/-65
16674.6	6'0" x 6'8"	OX	IS/OS	+50/-50
16674.6	9'0" x 6'8"	OXO	IS/OS	+50/-50
16674.8	9'0" x 6'8"	OXX	IS/OS	+50/-50
16674.8	12'0" x 6'8"	OXXO	IS/OS	+50/-50

16674.2	3'0" x 8'0"	X	IS/OS	+50/-50
16674.4	6'0" x 8'0"	XX	IS/OS	+50/-50
16674.6	3'0" x 8'0"	O	Fixed	+50/-50
16674.6	6'0" x 8'0"	OX	IS/OS	+45/-45
16674.6	9'0" x 8'0"	OXO	IS/OS	+45/-45
16674.8	9'0" x 8'0"	OXX	IS/OS	+45/-45
16674.8	12'0" x 8'0"	OXXO	IS/OS	+45/-45

Pro Series Fiberglass Smooth and Textured) WBDR Impact Rated Glazed Doors

FL Number	Maximum Door Size	Unit Config	Swing	DP Rating
16674.1	3'0" x 6'8"	X	IS/OS	+50/-50
16674.3	6'0" x 6'8"	XX	IS/OS	+50/-50
16674.5	6'0" x 6'8"	OX	IS/OS	+50/-50
16674.5	9'0" x 6'8"	OXO	IS/OS	+50/-50
16674.7	9'0" x 6'8"	OXX	IS/OS	+50/-50
16674.7	12'0" x 6'8"	OXXO	IS/OS	+50/-50

16674.1	3'0" x 8'0"	X	IS/OS	+50/-50
16674.3	6'0" x 8'0"	XX	IS/OS	+50/-50
16674.5	6'0" x 8'0"	OX	IS/OS	+45/-45
16674.5	9'0" x 8'0"	OXO	IS/OS	+45/-45
16674.7	9'0" x 8'0"	OXX	IS/OS	+45/-45
16674.7	12'0" x 8'0"	OXXO	IS/OS	+45/-45

Pro Series Fiberglass Smooth and Textured) WBDR Non-Impact Rated Opaque (Solid) Doors

FL Number	Maximum Door Size	Unit Config	Swing	DP Rating
13541.1	3'0" x 6'8"	X	IS/OS	+50/-50
13541.3	6'0" x 6'8"	XX	IS/OS	+50/-50
13541.5	6'0" x 6'8"	OX	IS/OS	+50/-50
13541.5	9'0" x 6'8"	OXO	IS/OS	+50/-50
13541.7	9'0" x 6'8"	OXX	IS/OS	+50/-50
13541.7	12'0" x 6'8"	OXXO	IS/OS	+50/-50

13541.1	3'0" x 8'0"	X	IS/OS	+50/-50
13541.3	6'0" x 8'0"	XX	IS/OS	+50/-50
13541.5	6'0" x 8'0"	OX	IS/OS	+45/-45
13541.5	9'0" x 8'0"	OXO	IS/OS	+45/-45
13541.7	9'0" x 8'0"	OXX	IS/OS	+45/-45
13541.7	12'0" x 8'0"	OXXO	IS/OS	+45/-45

Pro Series Fiberglass Smooth and Textured) WBDR Non-Impact Rated Glazed Doors

FL Number	Maximum Door Size	Unit Config	Swing	DP Rating
13541.2	3'0" x 6'8"	X	IS/OS	+50/-50
13541.4	6'0" x 6'8"	XX	IS/OS	+50/-50
13541.6	3'0" x 6'8"	O	Fixed	+65/-65
13541.6	6'0" x 6'8"	OX	IS/OS	+50/-50
13541.6	9'0" x 6'8"	OXO	IS/OS	+50/-50
13541.8	9'0" x 6'8"	OXX	IS/OS	+50/-50
13541.8	12'0" x 6'8"	OXXO	IS/OS	+50/-50

13541.2	3'0" x 8'0"	X	IS/OS	+50/-50
13541.4	6'0" x 8'0"	XX	IS/OS	+50/-50
13541.6	3'0" x 8'0"	O	Fixed	+50/-50
13541.6	6'0" x 8'0"	OX	IS/OS	+45/-45
13541.6	9'0" x 8'0"	OXO	IS/OS	+45/-45
13541.8	9'0" x 8'0"	OXX	IS/OS	+45/-45
13541.8	12'0" x 8'0"	OXXO	IS/OS	+45/-45