

Project:

Type:

Qty:




FEATURES

- Modular design, field replaceable LED module, trim, beam lens, and accessories.
- Interchangeable secondary reflector options for glare control and maximum visual comfort.
- Quiet ceiling achieved through deep regress.
- Precise light control, 20°/30°/40°/60° Reflector and TIR lens options in 15°/24°/36°/50°
- Offered standard with flicker free dimming to .1%.

Type IC rated - approved for direct contact with insulation.
No IC housing needed.

SPECIFICATIONS



Input Voltage	100-277V AC
Wattage	15W / 20W
Delivered Lumens	1160Lm - 1600Lm
LED	<3-Step MacAdam Ellipse (2-Step Available)
CCT	27K, 30K,35K,40K(other CCTs available)
CRI	>90Ra
Adjustability	Max Tilt Angle 30° / Horizontal Rotation Angle 355°<19
Lamp Life	50,000Hr
Environment	IP44 / IP54 upon request
Heat Sink	Aluminum body with oxidized powder coating
Trim	Die-cast Aluminum
Operating Temp	-4°F-104°F

Order Code

ORDER CODE EXAMPLE: GO2-3-RT-F-WD-LO-27K-R40-BK-SF-ELV-NC

Series	Size	Trim			Wattage	CCT	Beam Angle								
Go2	3 3.0"	RT	Round Trimmed	F	Fixed	Standard Trim	LO 15W / 1200lm HO 20W / 1600lm	27K 2700K 30K 3000K 35K 3500K 40K 4000K TW Tunable White 2700K-6500K WD Warm Dim 3000K-1800K	Reflector Lens	OR	TIR Lens				
		RL	Round Trimless	A	Adjustable				NR	Narrow Trim	R20	20 Degree	15D	15 Degree	
		ST	Square Trimmed	W	Wall wash				WD	Wide Trim	R30	30 Degree	24D	24 Degree	
		SL	Square Trimless	S*	Shower Trim						R40	40 Degree	36D	36 Degree	
				*Non-conductive trim for shower					Leave blank for standard, trimless or square trim options			R60	60 Degree	50D	50 Degree
												R90	90 Degree		
												*Choose between reflector lens or TiR lens, For 10 Degree Optic, inquire with factory.			

FINISH	OPTICAL ACCESSORIES	ENVIRONMENT	DIMMING	INSTALATION TYPE	EMERGENCY BACKUP
Reflector	Trim				
WH White	W White	SF Soft Focus	ELV Phase/Triac (3%)	NC New Construction Tray	EM10 10W/90 Min
BK Black	B Black	SL Solite Lens	D10 0-10V (.1%)	RM Remodel (no NC Tray)	
SV Sliver	GW Golden Wheat	HL Hexcell Louver	DAL DALI	AT/CP Airtight/Chicago Plenum	
SG Specular Gold	RAL# Custom	LS Linear Spread		WC Wood Ceiling	
SB Specular Black					
GW Golden Wheat					
		Leave blank if *dry o damp location (IP44)*			
		WET for exterior wet locations (under covered ceiling only)			

Project:

Type:

Qty:

TRIM OPTIONS

3.19"



Narrow Trim

3.35"



Standard Trim

3.74"



Wide Trim

4.72"



Round Trimless

3.54"



Square Trim

5.35"



Square Trimless

REFLECTOR OPTIONS



White



Black



Silver



Golden Wheat



Specular



Specular Black



Specular Gold

OPTICAL LENS



Soft Focus



Honeycomb



Linear Spread



Solite

PERFORMANCE

90 CRI / 2700K	15 Degree	24 Degree	36 Degree	50 Degree
15W	1160Lm	1180Lm	1200Lm	1220Lm
20W	1520Lm	1540Lm	1560Lm	1580Lm

90 CRI / 3000K	15 Degree	24 Degree	36 Degree	50 Degree
15W	1180Lm	1200Lm	1220Lm	1240Lm
20W	1540Lm	1560Lm	1580Lm	1600Lm

Preliminary, pre-launch test-data. Delivered lumen values +/- 5%. Optical filters will reduce delivered lumen values


Project:

Type:


Qty:

MOUNTING OPTIONS

NC - New Construction Frame-In Tray





Standard bar hanger (included)
Mounting Length 14 3/4" - 26".
Extension kit can be ordered separately.



Commercial bar hanger #1487
Butterfly and Caterpillar brackets available





New Construction & Remodel Mounting





Note:
Small fixture housing and driver enclosure box assembly can be used for both new construction and remodel. For remodel application, no new construction tray is needed.
The ceiling cutout opening will be too small to fit your hand through it. So it is very important that the LED driver remains accessible by removing the lighting fixture, thus allowing you to inspect the connectors or LED driver at any time without physically damaging your ceiling or other building materials.
This mounting allows for installation from below the ceiling access and full serviceability of the LED driver and driver/junction box.

LED Driver Enclosure and Junction Box



2-sectional driver and wiring box will ship when the AT/CP option is selected. Also can be used for plenum space issues.

Chicago Plenum / Airtight



Length	Width	Height
11 3/4"	8 1/2"	4 3/4"
		6 3/4"

Project:

Type:

Qty:


EMERGENCY

PRIMARY SPECIFICATIONS

Output Power Max	Input Power	Input Current Max	Emergency Operating Time	Battery	Input Voltage	Output Voltage	Ambient Operating Temperature	UL Listed for Us and Canada
10W	4W	60 mA	90 min.	LiFePO ₄ 24 Hour recharge 7 to 10 year Life expectancy	120-277 Vac 50/60Hz	12-55 V ¹	0 °C through 55 °C	ULand cUL (UL924) Emergency LED Driver

Dimensions / Weight

Length	9.5"	Height	8.9"
Width	1.7"	Mounting Length	
Weight	2.09 lb		



REMOTE TEST SWITCH

The remote test switch may be mounted adjacent to the LED fixture by others.

EMERGENCY BATTERY ACCESS

Above ceiling access is recommended for ease of service, but LED fixture sizes of 4" and larger are capable of below ceiling access. IC/ICAT/CP box and ITS option require an access panel in the ceiling (or other form of access) adjacent to the installation location of the emergency battery.

REMOTE LOCATION

Maximum remote mounting distance of the emergency driver shall be 50 feet. Remote location wiring provided by others. Follow all local and national electric/building codes.

WALL PLATE ACCESSORIES

