

Project:

Type:

Qty:



Order Code

ORDER CODE EXAMPLE: LPMINI-36W-35K-30D-B-D10-120V-MA*

SERIES	SERIES	CCT	BEAM ANGLE	FINISH	DIMMING	FINISH	ACCESSORIES
LP-MINI	11.81" (9W)	27K 2700K	20D 20 Degree	B Black	OO ON/OFF	120V 120V only	MA* Mounting accessories, specify option(A–F) AG* Anti-glare accessories, specify option A or B.
	23.62" (18W)	30K 3000K	30D 30 Degree	W White	D10 0-10V	UNV 100-277V	
	47.24" (36W)	35K 3500K	45D 45 Degree	GR Grey	DAL DALI		
		40K 4000K	25D*40D 25*40D Degree		TRI TRIAC		
		50K 5000K	30D*50D 30*50D Degree				
		57K 5700K					
		65K 6500K					
		TW Tunable White 2700K-6500K					
		WD Warm Dim 3000K-1800K					

Project:

Type:

Qty:

DIMENSIONS & VIEWS

Mounting Accessories (no additional cost), select type

A

B

Designed for applications requiring precise angle adjustments, this adjustable mounting bracket offers up to 180° rotation for optimal positioning

C

Adjustable mounting bracket engineered for precise angle adjustments, offering up to 180° rotation for optimal positioning

D

Mounting Accessories(order separately)

Adjustable mounting system engineered for precision landscape lighting applications

E

Versatile extended mounting arm, providing optimal positioning for any wall installation

F

Anti-glare Accessories (order separately)

11.81" / 23.62" / 47.24"
Precision-engineered symmetric anti-glare louver for LineaPro Mini, delivering refined illumination control.

A

11.81" / 23.62" / 47.24"
Asymmetric anti-glare louver designed for LineaPro Mini.

B

Project:

Type:


Qty:

DIMENSIONS & VIEWS

Typical Wiring Schematic

Leading Wiring Option One (0-10V / DALI)

Featuring a precision-engineered T-joint with integrated power and data cables for seamless connectivity.




Leading Wiring Option Two (0-10V / DALI)

Integrated power and data cables for streamlined connectivity and installation.




Leading Wiring Option Three (0-10V / DALI)

Precision T-joint with customizable bare wire lengths. Please consult factory for tailored cable specifications.




Power Injection Option One

Power injection with integrated power-leading cable for seamless energy distribution.



Power Injection Option Two

Precision T-joint with customizable bare power wire length. *Please consult factory for tailored cable specifications.



Extension Cable:



DMX Terminator (IP66):

