

# Unique Designs™

Unique Design™ mats feature subtle patterns to enhance any interior while capturing dirt and disguising stains. The curved corners improve the aesthetics, giving the mats more of a retail look.

## Features & Benefits

- 100% nitrile rubber backing for increased slip and skid resistance.
- Certified “high traction” by the National Floor Safety Institute.

## Specifications

Yarn: Acid Dyed Continuous Filament Nylon.

Twist: Each strand of yarn contains two plies of fiber that have been twisted individually 5.0 turns per inch. The yarn is then heat set to permanently maintain the hard twist.

Weight: 26 oz. per square yard (884 grams per square meter).

Static Control: Rated at less than 1KV on AATCC134 electrostatic propensity test. Satisfies IBM test requirements.

Primary Backing: Freudenberg LUTRADUR® Polyester Spunbond Non-woven Fabric 3.8 oz./square yard (130 grams per square meter.)

Rubber Backing: 100% nitrile rubber for maximum oil resistance, weight reduction and flexibility. Compression molded with reinforced borders are on all four sides. Border thickness: 94 Mils. Body Thickness: 52 Mils.

Flammability: Exceeds requirements for FF2-70 – standard for surface flammability of small carpets.



3605 White Avenue,  
Eau Claire, WI 54701

2941 Center Court,  
Eagan, MN 55121