

# Classic Brush™

The most efficient floor mat you'll ever find. Engineered for supreme scraper action it maintains a very favorable image of your entrance.

- Extra-coarse monofilament nylon fibers combined with traditional solution dyed fibers create excellent scraping and wiping action for maximum soil stopping power.
- Impervious to bleach, sunlight and repeated washing.
- 100% Nitrile rubber backing for increased slip and skid resistance.
- Certified “high traction” by the National Floor Safety Institute.

## Features & Benefits

- Designed with coarse, abrasive nylon fibers combined with traditional solution-dyed carpet to create superior scrubbing action and capture the removed soil.
- The beautiful tweed color patterns hide soil from view.
- Safe to use around sensitive electronic equipment thanks to static-dissipative nylon yarn.
- Manufactured with 100% nitrile rubber backing, the mat resists curling and cracking in all types of conditions.

## Applications

- Inside Entrance Mat
- Vestibule Mat
- Reception Desk Mat

## Specifications

Yarn: Continuous Filament SDN, Type 6 Nylon. Rhodia Continuous Filament SDN, Type 6,6 Nylon.

Twist: Each yarn is twisted at 5.5 turns per inch. The yarn is then heat set to permanently maintain the hard twist.

Weight: 27 oz. per square yard (920 grams per square meter)

Static Control: ClassicSolutions and SolutionsPlus mats are rated at less than 1KV on AATCC134 electrostatic propensity test. Satisfies IBM test requirements.

Primary Backing: Freudenberg LUTRADUR® Polyester Spunbond Non-woven Fabric 3.8 oz./square yard (130 grams per square meter)

Rubber Backing: 100% nitrile rubber for maximum oil resistance, weight reduction and flexibility. Compression molded with reinforced borders on all four sides. Border Thickness: 100 Mils. Body Thickness: 65 Mils.

Flammability: Exceeds requirements for FF2-70 - standard for surface flammability of small carpets