



Shell Spirax HD 85W-140

Heavy Duty Automotive Gear Oil

Shell Spirax HD 85W-140 is an extreme-pressure (EP) automotive hypoid gear oil designed to exceed the latest performance standards for heavy duty, severe service.

DESIGNED TO MEET CHALLENGES

Performance, Features & Benefits

- Superior load carrying ability**
 The EP additives contained in Shell Spirax HD 85W-140 provides excellent, long lasting protection against scuffing and minimize wear, even in the toughest operating conditions.
- Superior thermal and oxidation stability**
 Shell Spirax HD 85W-140 provides superior resistance to high temperature decomposition (breakdown). Even when operating conditions approach 150°C, Shell Spirax HD 85W-140 provides excellent performance, resisting temperature degradation. This improved thermal and oxidation stability helps ensure that deposits do not form around seals and helps maintain clean bearing surfaces to minimize wear.
- All-season service**
 Depending on the ambient temperatures involved, Shell Spirax HD 85W-140 provides potential one grade, all-season operation. They can eliminate the need for seasonal changes and reduce the number of gear oils required.
- Potential for fuel economy**
 Shell Spirax HD multigrade and low temperature range features lessen frictional energy loss which improves fuel economy.

Main Applications



Shell Spirax HD oils are designed for service in the drive-train gears of heavily loaded equipment and passenger vehicles. They are recommended for the lubrication of hypoid, spur, bevel, helical, spiral-bevel and worm gears in differentials, transmissions, final drives, transfer cases, and steering mechanisms.

Shell Spirax HD 85W-140 is a premium all-season, multigrade gear oil designed to exceed Original Equipment Manufacturers' lubrication requirements under today's increased temperature and loads.

Specifications, Approvals & Recommendations

- API GL-4, GL-5
- API MT-1
- SAE J 2360
- Mack GO-H approved
- Mack GO-J approved
- Meets MIL-L-2105D (obsolete)
- Meets MIL-PRF-2105E (obsolete)

For a full listing of equipment approvals and recommendations, please consult your local Shell Technical Help Desk.

Typical Physical Characteristics

Properties			Method	Shell Spirax HD
SAE Viscosity Grade				85W-140
Density	@15°C	kg/m3	ASTM D1298	901
Colour, ASTM			ASTM D1500	4
Pour Point			ASTM D97	-12
Flash Point (COC)			ASTM D92	200
Kinematic Viscosity			ASTM D445	411

Properties		Method	Shell Spirax HD
Kinematic Viscosity	cSt	ASTM D445	29.7
Brookfield Viscosity	cP	ASTM D2983	79000
Channel Point	°C		<-20
Viscosity Index		ASTM D2270	103

These characteristics are typical of current production. Whilst future production will conform to Shell's specification, variations in these characteristics may occur.

Health, Safety & Environment

• Health and Safety

Shell Spirax HD 85W-140 is unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of personal hygiene are maintained.

Avoid contact with skin. Use impervious gloves with used oil. After skin contact, wash immediately with soap and water.

Guidance on Health and Safety is available on the appropriate Material Safety Data Sheet, which can be obtained from <http://www.epc.shell.com/>

• Protect the Environment

Take used oil to an authorised collection point. Do not discharge into drains, soil or water.

Additional Information

• Advice

Advice on applications not covered here may be obtained from your Shell representative.