



Install: Accessory ROPS Harness

Accessory ROPS Harness Kit P/N's (See Kit Table)

WORK INSTRUCTION OVERVIEW

⚠ WARNING

- DO NOT ATTEMPT THIS PROCEDURE IF YOU DO NOT HAVE PROPER TOOLS, TRAINING, AND FACILITIES.
- Read and follow all instructions provided when installing this product. Failure to do so may result in placing occupants at risk of serious injury or death.
- To protect bystanders and the service technician(s), shut vehicle off, remove the Ignition Key and secure vehicle to prevent unintended movement.
- Never operate the vehicle in excess of manufacturer's specifications.

NOTICE

- For Sound Bar with KC 40" Light Bar installations use Harness;
 - Part Number - **S-1801CUA00021N**
- For Light Bar Only Harness installations use Harness;
 - Part Number - **S-1801CUA00031N**
- For Sound Bar Only Harness installations use Harness;
 - Part Number - **S-1801CUA00041N**

TOOLS REQUIRED

- Protective Eye-wear

TORQUE SPECIFICATION

None

KIT COMPONENT TABLE

Kit Component	Description	Qty
	Accessory ROPS Harness Combo Light Bar and Sound Bar P/N: S-1801CUA00021N	1
	Accessory ROPS Harness Light Bar - Only P/N: S-1801CUA00031N	1
	Accessory ROPS Harness Sound Bar - Only P/N: S-1801CUA00041N	1

INSTALLATION PROCEDURE

1. Disconnect the standard Accessory Harness from the protective cap, located behind the Dash Panel on the passenger side.



2. Plug connector for ROPS Harness into this plug under passenger side Dash Panel.



3. Route ROPS Harness along passenger side of vehicle, attaching (5) Medal Panel Clips to edge.





Install: Accessory ROPS Harness

Accessory ROPS Harness Kit P/N's (See Kit Table)

4. Route ROPS Harness along vehicle passenger side between body roll-cage and netting.



5. Route ROPS Harness along side of passenger seat.



6. Route ROPS Harness to front bottom of B pillar behind seat belt and attach first Ribbed Push clip.



7. Route ROPS Harness up inside B pillar, under existing hook and loop fasteners.



8. Attach second Ribbed Push Clip to top front B pillar into position shown.

NOTICE Routing complete for Sound Bar, follow remaining steps for Light - Bar Harness routing.



9. Route ROPS Harness along inside top side ROP to front A pillar and secure with (2) Zip Ties.



10. Use (2) zip ties to secure ROPS Harness to B pillar top and bottom. Trim excess from zip ties.

