

ROLL-UP DOOR ORDER FORM

Date:		Ship To (if different):		
Sold To:				
Contact:		P.O. Numbers:		
Phone:		QTY:		
Email:				
SELECT DOOR BUILD OPTIONS ALL DOORS ARE SHIPPED IN TWO SECTIONS FOR EFFICIENT SHIPPING AND INSTALLATION	☐ Evact Size - Mar	ges shipped loose on o nufactured to size, fu		nmodate trim-down
□ Steel Clad Roll-Up Door Includes e-coat/powder coat hinges with 2" nylon rollers, removable end hinges steel clad panels, rubber head seal, e-coat/powder coat spring assisted steel lock, one-piece bottom seal, 7 x 19 cables, stainless steel rivets, e-coat/powder coat heavy duty lift handle and pull strap assembly. TRACK/OPERATOR □ 2" Track □ Operator SIDE SEALS (may ship separately) □ STANDARD Rubber □ Dual Durometer	Advanced Roll-U Engineered with adva panels that resist deni moisture, and corrosic powder coat hinges v removable end hinge rubber head seal, e-c spring assisted steel bottom seal, 7 x 19 cc steel rivets, e-coat/p duty lift handle and p TRACK/OPERATOR 2" Track Operator* Highly Recommend - I the lightweight perform SIDE SEALS (may shi STANDARD Rubb Dual Durometer OTHER Forklift Plate	p Composite Door nced composite ting, puncturing, on. Includes e-coat/ with 2" nylon rollers, es steel clad panels, coat/powder coat lock, one-piece ables, stainless owder coat heavy oull strap assembly. R Designed to match mance of ComposiTrak	Precision Recessed Wood Door - 1" Includes recessed galvanized hinges with 1" steel rollers, routed interlocking tongue and groove panels, aluminum head seal retainer, zinc-plated spring assisted steel lock, galvanized bottom seal retainer, 7 x 19 cables, zinc-plated heavy duty lift handle and pull strap assembly. Flush Mount Wood Door - 2" Includes flush e-coat hinges with 2" nylon rollers, routed interlocking tongue and groove panels, aluminum head sear retainer, e-coat spring assisted steel lock, aluminum bottom seal retainer, 7 x 19 cables, e-coat heavy duty lift handle and pull strap assembly. WOOD DOOR FINISH Primed ready-to-paint Pre-painted white with clear UV finish TRACK/OPERATOR Track Operator SIDE SEALS (may ship separately) STANDARD Rubber Dual Durometer RIVETS Zinc-Plated Steel Stainless Steel Stainless Steel	

REQUIRED: SEE BACK FOR PROVIDING DIMENSION INFORMATION

CONVERTING FROM A SWING DOOR?

DON'T FORGET A CONVERSION KIT

☐ for 7" header (Dry Freight Standard)

☐ for 9" header



ROLL-UP DOOR ORDER FORM

DO YOU KNOW YOUR CURRENT DOOR WIDTH & HEIGHT?


If so, please provide them here if you would like your door made to the same exact dimensions provided.

	х	
CURRENT DOOR WIDTH	ł	CURRENT DOOR HEIGHT

PLEASE PROVIDE DIMENSIONS IN .25" INCREMENTS


All new doors are made for net opening width, NOT wall-to-wall dimensions. If you have special conditions, please indicate or attach an additional sketch for engineer review.

TOP VIEW



For standard rear frames, we will add **2.25"** for door opening widths and subtract **.50"** to the opening height dimension provided. If a non-standard rear frame the overall width will be determined by the track spacing provided.

SIDE VIEW



YOUR DOOR(S) WILL BE MANUFACTURED AT:	NON-CATALOG DOORS ARE NON-RETURNABLE AND CANNOT BE CANCELED.		
OVERALL OVERALL DOOR WIDTH DOOR HEIGHT	OFFICE USE ONLY: P/N		
THIS BOX MUST BE COMPLETED BEFORE YOUR ORDER CAN BE PROCESSED. All dimensions should be in .25" increments.	Multiple part numbers may be necessary. SPECIAL INSTRUCTIONS		
Customer Authorized Signature Must be signed before order can be processed			