



OVERVIEW

Stik-Ons are 12 gauge steel insulation pins which are permanently staked through 2" x 2" galvanized steel base plates. A pressure-sensitive adhesive backing provides a permanent bond between the Stik-Ons and ductwork. Each case includes self-locking companion clips. Each Stik-On has 2 clearance holes in the baseplate to allow additional reinforcement with a #8 self-tapping screw when needed. Stik-Ons can be used to hold all low and medium density insulation and insulation board where the temperature will not exceed 150°F (65°C.).

PART NUMBERS

| | |
|--------|------------------------------|
| 308155 | 1 Case w/ (500) ¾" Stik-Ons |
| 308156 | 1 Case w/ (500) 1¼" Stik-Ons |
| 308158 | 1 Case w/ (500) 1¾" Stik-Ons |
| 308159 | 1 Case w/ (500) 2" Stik-Ons |
| 308160 | 1 Case w/ (500) 2½" Stik-Ons |

FEATURES AND BENEFITS

- Reinforced baseplate
- Low carbon steel 12 gauge pin allows easier bending of pin
- Paper backing easy to remove
- Includes self-locking companion clips
- Clearance holes allow adding #8 self-tapping screw for additional support
- Sharp diamond point to easily pierce through most insulation substrates

TYPICAL PROPERTIES AND CHARACTERISTICS

| | |
|-------------------------|----------------------------------|
| Temperature Range | Not to exceed 150°F (65°C) |
| Application Temperature | 40°F to 150°F (4°C to 65°C) |
| Holding Power | 3 lbs./unit |
| Approximate Shelf Life | 2 years @ 70°F (21°C) and 50% RH |

APPLICATION

Clean the surface of the duct where contact is to be made, so that it is free of oil, grease, rust, dust, and dirt. Peel off the paper backing and apply firmly to duct. Insulation can be applied immediately. Secure insulation in place using the included companion clips and the unused portion of the pin can be bent or cut.

