

## Flexible Stainless-Steel Plumbing Connectors



- Reliable, trouble-free service- Inner core of non-toxic polymer withstands temperatures of 33°F (1°C) to 174°F (99°C)
- Leak proof seal- High quality outer braid of stainless steel and exclusive crimp-on fittings for maximum performance
- Quick and easy installation- No special tools; no soldering
- No pipe bending- Flexible connectors simplify installation- even in cramped spaces
- Chrome plated nut
- These products are NSF approved
- LEAD FREE

### Faucet

| PART NO. | OD x FIP    | LENGTH | CTN/MSTR |
|----------|-------------|--------|----------|
| S04200   | 3/8" x 1/2" | 9      | 25/100   |
| S04201   | 3/8" x 1/2" | 12     | 25/100   |
| S04202   | 3/8" x 1/2" | 16     | 25/100   |
| S04203   | 3/8" x 1/2" | 20     | 25/100   |
| S04204   | 3/8" x 1/2" | 30     | 25/50    |
| S04205   | 3/8" x 1/2" | 36     | 25/100   |
| S04206   | 1/2" x 1/2" | 12     | 25/100   |
| S04207   | 1/2" x 1/2" | 16     | 25/100   |
| S04208   | 1/2" x 1/2" | 20     | 25/100   |
| S04209   | 1/2" x 1/2" | 30     | 25/50    |
| S04210   | 1/2" x 1/2" | 36     | 25/100   |

### Faucet

| PART NO. | FIP x FIP   | LENGTH | CTN/MSTR |
|----------|-------------|--------|----------|
| S04211   | 1/2" x 1/2" | 12     | 25/100   |
| S04212   | 1/2" x 1/2" | 16     | 25/175   |
| S04213   | 1/2" x 1/2" | 20     | 25/100   |
| S04214   | 1/2" x 1/2" | 30     | 25/50    |
| S04215   | 1/2" x 1/2" | 36     | 25/50    |

## Flexible Stainless-Steel Plumbing Connectors



- Reliable, trouble-free service- Inner core of non-toxic polymer withstands temperatures of 33°F (1°C) to 174°F (99°C)
- Leak proof seal- High quality outer braid of stainless steel and exclusive crimp-on fittings for maximum performance
- Quick and easy installation- No special tools; no soldering
- No pipe bending- Flexible connectors simplify installation- even in cramped spaces
- LEAD FREE

### Ballcock

| PART NO. | OD x BC                  | LENGTH | CTN QTY |
|----------|--------------------------|--------|---------|
| S04216   | 3/8" x 7/8"              | 9      | 25/100  |
| S04217   | 3/8" x 7/8"              | 12     | 25/100  |
| S04218   | 3/8" x 7/8"              | 16     | 25/100  |
| S04219   | 3/8" x 7/8"              | 20     | 25/100  |
| S04220   | 1/2" x 7/8"              | 9      | 25/100  |
| S04221   | 1/2" x 7/8"              | 12     | 25/100  |
| S04222   | 1/2" x 7/8"              | 16     | 25/100  |
| S04223   | 1/2" x 7/8"              | 20     | 25/100  |
| S04255   | 3/8" x 7/8" w/ brass nut | 12     | 25/100  |

### Ballcock

| PART NO. | FIP x BC    | LENGTH | CTN QTY |
|----------|-------------|--------|---------|
| S04224   | 1/2" x 7/8" | 9      | 25/100  |
| S04225   | 1/2" x 7/8" | 12     | 25/100  |
| S04226   | 1/2" x 7/8" | 20     | 25/100  |

### Ballcock

| PART NO. | FLARE x BC  | LENGTH | CTN QTY |
|----------|-------------|--------|---------|
| S04280   | 1/2" x 7/8" | 20     | 25/100  |
| S04285   | 3/8" x 7/8" | 20     | 25/50   |

### Washing Machine

| PART NO. | FEM HOSE x FEM HOSE | LENGTH | CTN QTY |
|----------|---------------------|--------|---------|
| S04227   | 3/4" x 3/4"         | 48     | 5/50    |
| S04228   | 3/4" x 3/4"         | 60     | 5/175   |
| S04229   | 3/4" x 3/4"         | 72     | 5/50    |

### Icemaker

| PART NO. | OD x OD     | LENGTH | CTN QTY |
|----------|-------------|--------|---------|
| S04230   | 1/4" x 1/4" | 12     | 5/50    |
| S04231   | 1/4" x 1/4" | 60     | 5/50    |
| S04232   | 1/4" x 1/4" | 84     | 5/50    |