### M18 FLIEL

## 3/8" Impact Wrench w/ Friction Ring w/ ONE-KEY™ Kit

2758-22, 2758-22CT (2758-20 Tool-Only)

#### Specifications:

•	
Fastening Torque	210 ft-lbs
Nut-Busting Torque	210 ft-lbs
IPM	0 – 3,200
RPM	0 – 2,500
DRIVE CONTROL™	4-Mode (Customizable)
Anvil Type	3/8" Friction Ring
Length / Weight	5.9" / 4.2 lbs



**Includes: 2758-22** (2) M18<sup>™</sup> REDLITHIUM<sup>™</sup> XC5.0 Battery Packs; 2758-22CT (2) M18<sup>™</sup> REDLITHIUM<sup>™</sup> CP2.0 Battery Packs: **All Kits Include:** Belt Clip, Bit Holder, Multi-Voltage

# Charger, Carrying Case

# 3/8" Compact Impact Wrench w/ Friction Ring Kit

2754-22, 2754-22CT (2754-20 Tool-Only)

#### **Specifications:**

210 ft-lbs
210 ft-lbs
0 – 3,200
0 – 2,500
4-Mode
3/8" Friction Ring
5.9" / 4.2 lbs

**Includes: 2754-22** (2) M18<sup>™</sup> REDLITHIUM<sup>™</sup> XC5.0 Battery Packs; 2754-22CT (2) M18™ REDLITHIUM™ CP2.0 Battery Packs; All Kits Include: Belt Clip, Bit Holder, Multi-Voltage Charger, Carrying Case

#### M18™ 3/8" Compact **Impact Wrench Kit**

2658-22, 2658-22CT (2658-20 Tool-Only)

# Specifications:

•	
Fastening Torque	167 ft-lbs
Nut-Busting Torque	167 ft-lbs
IPM	0 – 3,350
RPM	0 – 2,450
Anvil Type	3/8" Friction Ring
Length / Weight	6.0" / 4.1 lbs

**Includes: 2658-22** (2) M18<sup>™</sup> REDLITHIUM<sup>™</sup> XC3.0 Battery Packs; **2658-22CT** (2) M18™ REDLITHIUM™ CP1.5 Battery Packs; All Kits Include: Belt Clip, Multi-Voltage Charger, Carrying Case

# M18 FUEL 1/2" Mid-Torque Impact Wrench w/ Pin Detent Kit 2860-22 (2860-20 Tool-Only)

#### Specifications:

specifications.		
Fastening Torque	450 ft-lbs	
Nut-Busting Torque	600 ft-lbs	
IPM	0 – 3,000	
RPM	0 – 2,400	
Anvil Type	1/2" Pin Detent	
Length / Weight	6.7" / 5.3 lbs	

Includes: (2) M18™ REDLITHIUM™ XC5.0 Battery Packs, Belt Clip, Multi-Voltage Charger, Carrying Case



# M18 FUEL 1/2" Mid-Torque Impact **Wrench w/ Friction Ring Kit** 2861-22 (2861-20 Tool-Only)

### Specifications:

M18 FUEL

Fastening Torque	450 ft-lbs
Nut-Busting Torque	600 ft-lbs
IPM	0 – 3,000
RPM	0 – 2,400
Anvil Type	1/2" Friction Ring
Length / Weight	6.7" / 5.3 lbs

**Includes:** (2) M18<sup>™</sup> REDLITHIUM<sup>™</sup> XC5.0 Battery Packs, Belt Clip, Multi-Voltage Charger, Carrying Case



Fastening Torque	450 ft-lbs
Nut-Busting Torque	600 ft-lbs
IPM	0 – 3,200
RPM	0 – 2,300
DRIVE CONTROL™	3-Mode
Anvil Type	3/8" Friction Ring
Length / Weight	6.7" / 5.3 lbs

**Includes: 2852-22** (2) M18™ REDLITHIUM™ XC5.0 Battery Packs; **2852-22CT** (2) M18™ REDLITHIUM™ CP2.0 Battery Packs; All Kits Include: Belt Clip, Multi-Voltage Charger, Carrying Case





3/4" High Torque Impact Wrench w/ Friction Ring w/ ONE-KEY™ Kit

2864-22 (2864-20 Tool-Only)

#### Specifications:

Opeomodions:		
Fastening Torque	1,200 ft-lbs	
Nut-Busting Torque	1,600 ft-lbs	
IPM	0 – 1,850	
RPM	0 – 1,850	
DRIVE CONTROL™	4 Modes (Customizable)	
Length / Weight	8.6" / 7.9 lbs	

**Includes:** (2) M18<sup>™</sup> REDLITHIUM<sup>™</sup> XC5.0 Battery Packs, Belt Clip, Multi-Voltage Charger, Carrying Case

## M18™ 3/4" High Torque Impact Wrench w/ Friction Ring Kit

2664-22 (2664-20 Tool-Only)

#### **Specifications:**

-		
Fastening Torque	525 ft-lbs	
Breakaway Torque	700 ft-lbs	
IPM	0 – 2,200	
RPM	0 – 1,900	
Anvil Type	3/4" Friction Ring	
Length / Weight	9.0" / 6.8 lbs	

Includes: (2) M18™ REDLITHIUM™ XC3.0 Battery Packs, Multi-Voltage Charger, Carrying Case

# M18™ 1/2" High Torque Impact Wrench w/ Pin Detent Kit

2662-22 (2662-20 Tool-Only)

#### Specifications:

opoomoanomo.	
Fastening Torque	450 ft-lbs
Breakaway Torque	640 ft-lbs
IPM	0 – 2,200
RPM	0 – 1,900
Anvil Type	1/2" Pin Detent
Length / Weight	8.9" / 6.7 lbs

Includes: (2) M18™ REDLITHIUM™ XC3.0 Battery Packs, Multi-Voltage Charger, Carrying Case

# 

# 1/2" High Torque Impact Wrench w/ Friction Ring w/ ONE-KEY™ Kit

2863-22 (2863-20 Tool-Only)

#### Specifications:

specifications.	
Fastening Torque	1,000 ft-lbs
Nut-Busting Torque	1,400 ft-lbs
IPM	0 – 2,100
RPM	0 – 1,750
DRIVE CONTROL™	4-Modes (Customizable)
Anvil Type	1/2" Friction Ring
Length / Weight	8.4" / 7.6 lbs

**Includes:** (2) M18<sup>™</sup> REDLITHIUM<sup>™</sup> XC5.0 Battery Packs, Multi-Voltage Charger, Carrying Case

# M18 FUEL

# 1/2" High Torque Impact Wrench w/ Pin Detent w/ ONE-KEY™ Kit

2862-22 (2862-20 Tool-Only)

#### Specifications

Opcomoducióno.		
Fastening Torque	750 ft-lbs	
Nut-Busting Torque	1,100 ft-lbs	<u> </u>
IPM	0 – 2,400	
RPM	0 – 1,800	4
DRIVE CONTROL™	4-Modes (Customizable)	\
Anvil Type	1/2" Pin Detent	
Length / Weight	8.1" / 7.2 lbs	

**Includes:** (2) M18<sup>™</sup> REDLITHIUM<sup>™</sup> XC5.0 Battery Packs, Multi-Voltage Charger, Carrying Case

# M18 FUEL

# 1/2" High Torque Impact Wrench w/ Friction Ring Kit

2767-22 (2767-20 Tool-Only)

# Specifications:

Fastening Torque	1,000 ft-lbs
Nut-Busting Torque	1,400 ft-lbs
IPM	0 – 2,100
RPM	0 – 1,750
DRIVE CONTROL™	4-Modes w/ Bolt Removal Mode
Anvil Type	1/2" Friction Ring
Length / Weight	8.4" / 7.5 lbs

**Includes:** (2) M18<sup>™</sup> REDLITHIUM<sup>™</sup> XC5.0 Battery Packs, Multi-Voltage Charger, Carrying Case

### M18 FUEL 1/2" High Torque Impact **Wrench w/ Pin Detent Kit**

2766-22 (2766-20 Tool-Only)

# Specifications

Specifications:	
Fastening Torque	750 ft-lbs
Nut-Busting Torque	1,100 ft-lbs
IPM	0 – 2,400
RPM	0 – 1,850
DRIVE CONTROL™	4-Modes w/ Bolt Removal Mode
Anvil Type	1/2" Pin Detent
Length / Weight	8.1" / 7.1 lbs

Includes: (2) M18™ REDLITHIUM™ XC5.0 Battery Packs. Multi-Voltage Charger, Carrying Case

# M18™ 1/2" High Torque Impact Wrench w/ Friction Ring Kit

2663-22 (2663-20 Tool-Only)

# Specifications:

-	
Fastening Torque	450 ft-lbs
Breakaway Torque	640 ft-lbs
IPM	0 – 2,200
RPM	0 – 1,900
Anvil Type	1/2" Friction Ring
Length / Weight	8.9" / 6.7 lbs

**Includes:** (2) M18<sup>™</sup> REDLITHIUM<sup>™</sup> XC3.0 Battery Packs, Multi-Voltage Charger, Carrying Case



