

# Radiant and hydronic piping systems

## Non-barrier tubing

Uponor AquaPEX white tubing is suitable for use in hydronic heating applications where the system contains no ferrous corrodible components or where any ferrous components are isolated from the tubing.

Uponor AquaPEX white tubing is manufactured and listed to ASTM F876 and F877 and CSA B137.5, certified to NSF Standards 14 and 61 and listed by the Hydrostatic Stress Board of PPI at 200°F at 80psi, 180°F at 100psi and 73.4°F at 160psi.

Uponor AquaPEX white tubing is marked with the PEX 5106 designation as required by the most recent edition of ASTM F876-15a, indicating it exceeds ASTM F876 chlorine-resistance requirements for continuous-recirculation systems operating up to 140°F while also affording a one-month UV-resistance level.

### Uponor AquaPEX white coils



| Part no. | Part description                        | Coils/pallet |
|----------|-----------------------------------------|--------------|
| F1040250 | ¼" Uponor AquaPEX White, 100-ft. coil   | 50           |
| F1090375 | ⅜" Uponor AquaPEX White, 400-ft. coil   | 18           |
| F1120375 | ⅜" Uponor AquaPEX White, 1,000-ft. coil | 12           |
| F1040500 | ½" Uponor AquaPEX White, 100-ft. coil   | 22           |
| F1060500 | ½" Uponor AquaPEX White, 300-ft. coil   | 18           |
| F1100500 | ½" Uponor AquaPEX White, 500-ft. coil   | 12           |
| F1120500 | ½" Uponor AquaPEX White, 1,000-ft. coil | 8            |
| F1060625 | ⅝" Uponor AquaPEX White, 300-ft. coil   | 12           |
| F1120625 | ⅝" Uponor AquaPEX White, 1,000-ft. coil | 5            |
| F1040750 | ¾" Uponor AquaPEX White, 100-ft. coil   | 22           |
| F1060750 | ¾" Uponor AquaPEX White, 300-ft. coil   | 9            |
| F1100750 | ¾" Uponor AquaPEX White, 500-ft. coil   | 8            |
| F1041000 | 1" Uponor AquaPEX White, 100-ft. coil   | 12           |
| F1061000 | 1" Uponor AquaPEX White, 300-ft. coil   | 5            |
| F1101000 | 1" Uponor AquaPEX White, 500-ft. coil   | 6            |
| F1061250 | 1¼" Uponor AquaPEX White, 100-ft. coil  | 7            |
| F1021250 | 1¼" Uponor AquaPEX White, 300-ft. coil  | 2            |
| F1061500 | 1½" Uponor AquaPEX White, 100-ft. coil  | 7            |
| F1021500 | 1½" Uponor AquaPEX White, 300-ft. coil  | 2            |
| F1062000 | 2" Uponor AquaPEX White, 100-ft. coil   | 5            |
| F1052000 | 2" Uponor AquaPEX White, 200-ft. coil   | 3            |
| F1022000 | 2" Uponor AquaPEX White, 300-ft. coil   | 2            |
| F1062500 | 2½" Uponor AquaPEX White, 100-ft. coil  | 1            |
| F1022500 | 2½" Uponor AquaPEX White, 300-ft. coil  | 1            |
| F1063000 | 3" Uponor AquaPEX White, 100-ft. coil   | 1            |
| F1023000 | 3" Uponor AquaPEX White, 300-ft. coil   | 1            |