

For 50 years, we've been the innovators in subfloor prep. With our new line of innovative, cost effective solutions for commercial projects, we're offering more ways than ever to help you get the job done right. Every time. **THE LEADERS. THE INNOVATORS. THE NAME YOU CAN TRUST.**

### CONCRETE FLOOR PREP SOLUTIONS



## MAXXON<sup>®</sup> COMMERCIAL Unglued

### PRODUCT DESCRIPTION

Adhesive remover effective in the removal of pressure sensitive adhesives (PSAs) and other flooring mastics, glues and adhesives (water-based and non-water-based).

### INFO

Dry Time: Typically 2-4 hours  
Coverage: 80-100 ft<sup>2</sup> /gal  
One kit covers 320-400 ft<sup>2</sup>  
Packaging: 4 gal kit



## MAXXON<sup>®</sup> COMMERCIAL Profile

### PRODUCT DESCRIPTION

Concrete cleaner and profiler designed to purge contaminants from concrete surface, while creating a CSP of 1-4 with no shotblasting. Biodegradable, clean with water.

### INFO

Dwell Time: 15 min for surface cleaning  
(approx) 2 hours to CSP 2  
Coverage: 225-250 ft<sup>2</sup>/gal or  
900-1,000 ft<sup>2</sup>/bucket  
Packaging: 4 gal bucket



## MAXXON<sup>®</sup> COMMERCIAL Isolate

### PRODUCT DESCRIPTION

A two-part, water-based epoxy that isolates chemically-abated slabs, and other contaminants in concrete slabs. Also prevents the migration of moisture vapor from adversely affecting floor coverings.

### INFO

Dry Time: 4-6 hours  
Coverage: 150 ft<sup>2</sup>/gal or 600 ft<sup>2</sup>/kit  
Packaging: 4 gal bucket



## MAXXON<sup>®</sup> COMMERCIAL Unset

### PRODUCT DESCRIPTION

Thinset remover effective in the removal of many types of polymer-modified thinset\* and broadloom carpet adhesives\*\*.

### INFO

Dwell Time: \*Min. 4 hours to overnight,  
\*\*Min. 30 minutes to overnight  
Spread Rate: No specific coverage recommendation  
– Apply until substrate is saturated  
Packaging: 4 gal bucket

### UNDERLAYMENTS & PATCH PRODUCTS



## MAXXON<sup>®</sup> COMMERCIAL Level EZ<sup>™</sup>

### PRODUCT DESCRIPTION

A low-prep, hydraulic cement-based underlayment that provides a strong, durable, smooth surface for floor coverings. Can be poured or pumped. UL Fire Rated.

### INFO

Installation Depth: Featheredge to 2"  
Compressive Strength: Minimum 5,000 psi  
Coverage at 1/4": 21 ft<sup>2</sup>  
Packaging: 50 lb bag



## MAXXON<sup>®</sup> COMMERCIAL EZ Crete<sup>™</sup>

### PRODUCT DESCRIPTION

A low-prep, cost-effective cementitious underlayment for leveling, smoothing and repairing interior gypsum and concrete subfloors. UL Fire Rated.

### INFO

Installation Depth: 3/8" to 3"  
Compressive Strength: Minimum 4,000 psi  
Coverage at 3/8": 16 ft<sup>2</sup>  
Packaging: 50 lb bag



## MAXXON<sup>®</sup> COMMERCIAL Low Density Fill<sup>™</sup>

### PRODUCT DESCRIPTION

An ultra-lightweight proprietary cement with lightweight aggregate that is easy to place and can be sloped with no thickness limitation. Ready to be capped with a Maxxon underlayment the next day.

### INFO

Density: 28-32 pcf  
Coverage at 2": 9 ft<sup>2</sup>  
Packaging: 40 lb bag



## MAXXON<sup>®</sup> COMMERCIAL Skim Fill<sup>™</sup>

### PRODUCT DESCRIPTION

A self-drying, polymer-modified cement patch designed to skim coat, smooth and fill imperfections in interior subfloors.

### INFO

Compressive Strength: 4,000 psi  
Flooring Install: 30-60 min  
Coverage at 1/8": 60-72 ft<sup>2</sup>  
Packaging: 20 lb bag



## MAXXON<sup>®</sup> COMMERCIAL Gyp-Fix EZ<sup>®</sup> Patch

### PRODUCT DESCRIPTION

A high-strength, patch or skim coat over interior gypsum, concrete, and all subfloors. UL Fire Rated to maintain fire code.

### INFO

Compressive Strength: Minimum 4,000 psi  
Coverage at 1/8": 31 ft<sup>2</sup>  
Packaging: 25 lb bag

# MOISTURE MITIGATION



## MAXXON<sup>®</sup> COMMERCIAL MVP One

### PRODUCT DESCRIPTION

Ready-to-use, single-component moisture barrier and primer. Two-coat application dries in 60 minutes per coat. Meets ASTM E96 and mitigates up to 100% RH, 25 lbs MVER, and pH of 14.

### INFO

Total Coverage: 1,250 ft<sup>2</sup>  
for 2-coat system  
Packaging: 5 gal bucket



## MAXXON<sup>®</sup> COMMERCIAL MVP Two-Part Epoxy

### PRODUCT DESCRIPTION

Two-part epoxy moisture barrier. Meets ASTM E96 and mitigates up to 100% RH, 25 lbs MVER, and pH of 14.

### INFO

Total Coverage: 375 ft<sup>2</sup>  
Packaging: 3 gal kit



## MAXXON<sup>®</sup> COMMERCIAL MVP SMART Primer

### PRODUCT DESCRIPTION

A spray-applied curing agent and moisture barrier for concrete. Used as part of the Maxxon SMART System to expedite new concrete construction.

### INFO

Dry Time: 30 min – 2 hours  
(based on thickness)  
Coverage: 175 ft<sup>2</sup>/gal  
Packaging: 4 gal bucket

# PRIMERS



## MAXXON<sup>®</sup> COMMERCIAL Fortify™

### PRODUCT DESCRIPTION

A high-performance primer to consolidate soft or dusty gypsum underlayments, strengthening and readying the surface for a Maxxon<sup>®</sup> underlayment.

### INFO

Total Coverage: 400 ft<sup>2</sup> as consolidator  
Packaging: 5 gal bucket



## MAXXON<sup>®</sup> COMMERCIAL Multi-Use Acrylic

### PRODUCT DESCRIPTION

Primes concrete, gypsum, and wood subfloor before application of a Maxxon underlayment.

### INFO

Total Coverage: Up to 2,100 ft<sup>2</sup>  
*Varies by application*  
Packaging: 5 gal bucket



## MAXXON<sup>®</sup> COMMERCIAL Gypsum Overspray

### PRODUCT DESCRIPTION

Seals Maxxon underlayments before the installation of glue down finished floor goods.

### INFO

Total Coverage: 10,500 ft<sup>2</sup>  
Packaging: 5 gal bucket

# COATINGS



## MAXXON<sup>®</sup> COMMERCIAL HydroCoat

### PRODUCT DESCRIPTION

A two-part water-based epoxy coating, with excellent adhesion to both old and green concrete. It has low odor, good chemical resistance, and dries to a walkable surface in 12 hours.

### INFO

Foot Traffic: After 12 hours  
Coverage w/ One Coat: 350–450 ft<sup>2</sup>/gal or  
1,400–1,800 ft<sup>2</sup>/kit  
Packaging: 4 gal bucket



## MAXXON<sup>®</sup> COMMERCIAL HydroSeal

### PRODUCT DESCRIPTION

A two-part water-based, UV color stable urethane floor coating. HydroSeal develops a hard, wear-resistant, thin film topcoat as part of a two-coat system over HydroCoat water-based epoxy.

### INFO

Light Traffic: 24–48 hours (at 73 °F [22.8 °C])  
Coverage: 400 ft<sup>2</sup>/gal, or 1,600 ft<sup>2</sup>/kit  
Packaging: 4 gal bucket

# SOUND CONTROL



## MAXXON<sup>®</sup> COMMERCIAL Acousti-Top<sup>®</sup>

### PRODUCT DESCRIPTION

A topical sound control mat designed for use over concrete, existing gypsum or lightweight concrete. Code compliant sound control at <1/16". Loose lay or glue down.

### INFO

Roll coverage: 708 ft<sup>2</sup>  
Weight: 45 lbs  
Sound: 50 IIC



## MAXXON<sup>®</sup> COMMERCIAL Acousti-Top<sup>®</sup> Adhesive

### PRODUCT DESCRIPTION

Pressure sensitive adhesive used to bond Acousti-Top<sup>®</sup> sound mat to concrete or gypsum subfloors.

### INFO

Total Coverage: 1,250 ft<sup>2</sup>  
Packaging: 5 gal bucket