

PRODUCT DATA SHEET

EDGE GRIP FASCIA

Edge Grip Fascia is a low profile retainer bar and fascia assembly used with either an adhered or mechanically attached Sika Roof System, which clamps the roof membrane against the building to help prevent leaks and blow-offs.

PRODUCT INFORMATION

USES

Edge Grip Fascia's unique design provides a clean option for the building's roof edge.

AREAS OF APPLICATION

- Building Edge
- Parapet Wall

FEATURES / BENEFITS

- Labor savings during installation
- Aesthetic appeal
- High corrosion resistance
- Strong wind resistance

CODES / APPROVALS

- ANSI/SPRI ES-1 tested (part #'s 375, 525 and 675)

PRODUCT DATA

FORM

COMPOSITION

Edge Grip Fascia is a two part assembly with a rigid retainer base plate with pre-punched .392 in (9.93 mm) holes for fasteners at 12" (304.8 mm) on center and decorative snap on fascia cover with concealed splice plates.

Fascia: Formed Aluminum 0.04 in (1.00 mm), 0.05 in (1.25 mm),
or 0.063 in (1.60 mm)

Galvanized Steel 24 ga Kynar 500 coated

Base Plate:

Formed Aluminum 0.05 in (1.25 mm)

Galvanized Steel 20 ga

COLOR

Varies

DIMENSIONS

Length: 10 ft (3.04 m)

Fascia Heights: 3.75 in (9.5 cm), 5.25 in (13.3 cm), 6.75 in (17.1 cm), or 8 in (20.3 cm)

PACKAGING

The entire Edge-Grip's assembly is packaged in job specific crates to provide maximum protection during transit.

SYSTEM INFORMATION

INSTALLATION

Position the membrane (non-feltbacked) over the roof edge and down outside face of wall, covering treated wood nailer(s) completely. The edge of the membrane should extend over the face of the building approx. 3" (76.2 mm) and be secured with the retainer bar. Hot-air weld all seams making sure there are no voids in welds. Make sure the retainer bar is clean and free of dirt or dust. Apply a 3/8 in. (10 mm) bead of multi-purpose sealant to the intersection of the right angle on the bar. Install bar from right to left as seen from rooftop lapping joints 1 in. (25 mm). Fasten bar 12 in. (305 mm) o.c. through slots using fasteners provided. Field cut sections as necessary. Install joint covers between each fascia section. Hook the joint cover from the top and allow it to hang down the face of the retainer. Do not hook on the drip. Install fascia by hooking the back flange over the top of the retainer. Leave a 1/4" gap for thermal movement.

AVAILABILITY

From Authorized Applicators when used within Sarnafil or Sikaplan roofing and waterproofing systems.

MAINTENANCE

Standard maintenance of roofs should include regular inspection of flashings, drains and termination sealants at least twice a year and after each storm.

WARRANTY

As a Sika supplied accessory, Edge Grip Fascia is covered under Sika Corporation warranties.

LEGAL NOTES

All information provided by Sika Corporation ("Sika") concerning Sika products, including but not limited to, any recommendations and advice relating to the application and use of Sika products, is given in good faith based on Sika's current experience and knowledge of its products when properly stored, handled and applied under normal conditions in accordance with Sika's instructions. In practice, the differences in materials, substrates, storage and handling conditions, actual site conditions and other factors outside of Sika's control are such that Sika assumes no liability for the provision of such information, advice, recommendations or instructions related to its products, nor shall any legal relationship be created by or arise from the provision of such information, advice, recommendations or instructions related to its products. The user of the Sika product(s) must test the product(s) for suitability for the intended application and purpose before proceeding with the full application of the product(s). Sika reserves the right to change the properties of its products without notice. All sales of Sika product(s) are subject to its current terms and conditions of sale which are available at usa.sarnafil.sika.com or by calling 800-451-2504.

Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's most current Product Data Sheet, product label and Safety Data Sheet which are available online at usa.sarnafil.sika.com or by calling Sika's Technical Service Department at 800-451-2504. Nothing contained in any Sika materials relieves the user of the obligation to read and follow the warnings and instruction for each Sika product as set forth in the current Product Data Sheet, product label and Safety Data Sheet prior to product use.

Sika warrants this product for one year from date of installation to be free from manufacturing defects and to meet the technical properties on the current Product Data Sheet if used as directed within shelf life. User determines suitability of product for intended use and assumes all risks. Buyer's sole remedy shall be limited to the purchase price or replacement of product exclusive of labor or cost of labor.

NO OTHER WARRANTIES EXPRESS OR IMPLIED SHALL APPLY INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES. SIKA SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

SIKA CORPORATION – ROOFING

UNITED STATES

100 Dan Road
Canton, MA 02021
800-451-2504 (p)
781-828-5365 (f)
usa.sarnafil.sika.com
webmaster.sarnafil@us.sika.com

SIKA CANADA INC.

6915 Davand Drive
Mississauga, ON L5T 1L5
905-795-3177 (p)
905-795-3192 (f)
can.sika.com
marketing.construction@ca.sika.com