



PRODUCT DATA SHEET

LIQUID FLASHING CATALYST

Liquid Flashing Catalyst is a reactive agent based on dibenzoyl peroxide to induce curing of Sika's Liquid Flashing SW, Liquid Flashing WW, and Liquid Flashing Primer when mixed.

PRODUCT INFORMATION

USES

Catalyst for Liquid Flashing SW, Liquid Flashing WW, and Liquid Flashing Primer

AREAS OF APPLICATION

- Details that are difficult to flash with a sheet membrane
- Angle Iron
- I-Beam
- Close Multiple Conduits
- Wooden Surfaces
- Concrete Surfaces

FEATURES / BENEFITS

- Easy to mix

PRODUCT DATA

FORM

COMPOSITION

Powder

COLOR

White

VOC CONTENT

2.6 g/L (Liquid Flashing Primer + Liquid Flashing Catalyst Combined)
4.2 g/L (Liquid Flashing SW/WW + Liquid Flashing Catalyst Combined)

PACKAGING

3.5 oz (0.1 kg) packets, 10 tablespoons per packet, 50 packets per box

PRIOR TO EACH USE OF ANY SIKA PRODUCT, THE USER MUST ALWAYS READ AND FOLLOW THE WARNINGS AND INSTRUCTIONS ON THE PRODUCT'S MOST CURRENT PRODUCT DATA SHEET, PRODUCT LABEL AND SAFETY DATA SHEET WHICH ARE AVAILABLE ONLINE AT USA.SARNAFIL.SIKA.COM OR BY CALLING SIKA SARNAFIL'S TECHNICAL SERVICE DEPARTMENT AT 800-451-2504. NOTHING CONTAINED IN ANY SIKA MATERIALS RELIEVES THE USER OF THE OBLIGATION TO READ AND FOLLOW THE WARNINGS AND INSTRUCTIONS FOR EACH SIKA PRODUCT AS SET FORTH IN THE CURRENT PRODUCT DATA SHEET, PRODUCT LABEL AND SAFETY DATA SHEET PRIOR TO PRODUCT USE.

STORAGE**STORAGE CONDITIONS**

Store in a cool, dry, ventilated area away from flame sources. Do not store in direct sunlight or in temperatures above 86°F (30°C). Store away from reducing agents, strong oxidizers, acids, alkalis and accelerators.

SHELF LIFE

Liquid Flashing Catalyst has a shelf life of up to 12 months in the original unopened packet when properly stored, sealed and unmixed.

SYSTEM INFORMATION**APPLICATION INSTRUCTIONS****MIXING**

Thoroughly mix the entire pail of Liquid Flashing SW, Liquid Flashing WW, or Liquid Flashing Primer with a slow-speed (200 to 400 rpm) mechanical mixer (electric drill with a mixing paddle) for two minutes.

After stirring, pour 1 liter of Liquid Flashing into a clean plastic container.

Add 2 level tablespoons of Liquid Flashing Catalyst to Liquid Flashing SW or 4 level tablespoons to Liquid Flashing WW. Mix using a slow-speed mechanical mixer with a separate mixing paddle for two minutes (do not use mixing paddle after the addition of catalyst to mix open entire pail of Liquid Flashing).

The amount of Liquid Flashing Catalyst used may alter depending on ambient and surface temperatures, the values given are based on the mid-range temperatures to provide an approximate pot life of 10 - 15 minutes after mixing.

COVERAGE

The amount of Liquid Flashing Catalyst used will vary depending on the Liquid Flashing product, ambient temperature and volume.

Product	Ambient Temperature	Volume	Liquid Flashing Catalyst Dosage
Liquid Flashing SW	59°F-104°F (15°C-40°C)	1 Liter	2 Tablespoons (20g)
Liquid Flashing WW	23°F-68°F (-5°C-20°C)	1 Liter	4 Tablespoons (40g)
Liquid Flashing Primer	68°F-95°F (20°C-35°C)	1 Liter	2 Tablespoons (20g)
	32°F-68°F (0°C-20°C)	1 Liter	4 Tablespoons (40g)

PRIOR TO EACH USE OF ANY SIKA PRODUCT, THE USER MUST ALWAYS READ AND FOLLOW THE WARNINGS AND INSTRUCTIONS ON THE PRODUCT'S MOST CURRENT PRODUCT DATA SHEET, PRODUCT LABEL AND SAFETY DATA SHEET WHICH ARE AVAILABLE ONLINE AT USA.SARNAFIL.SIKA.COM OR BY CALLING SIKA SARNAFIL'S TECHNICAL SERVICE DEPARTMENT AT 800-451-2504. NOTHING CONTAINED IN ANY SIKA MATERIALS RELIEVES THE USER OF THE OBLIGATION TO READ AND FOLLOW THE WARNINGS AND INSTRUCTIONS FOR EACH SIKA PRODUCT AS SET FORTH IN THE CURRENT PRODUCT DATA SHEET, PRODUCT LABEL AND SAFETY DATA SHEET PRIOR TO PRODUCT USE.

PRODUCT LIMITATIONS**LIMITATIONS**

Precautions should be taken to prevent odors and/or vapors from entering the building/structure, including but not limited to turning off and sealing air intake vents or other means of ingress for odors and/or vapors into the building/structure during product application and cure.

WARNING: May cause fire if stored in direct sunlight or in temperatures above 86°F (30°C), store away from reducing agents, strong oxidizers, acids, alkalis and accelerators, always store loose packets in closed containers in a cool, ventilated and dry location away from heat sources.

AVAILABILITY

From Sika Corporation – Roofing Authorized Applications for use within Sarnafil or Sikaplan systems.

MAINTENANCE

Standard maintenance of Sarnafil or Sikaplan systems should include regular inspection of flashings, drains, and termination sealants at least twice a year and after each storm.

WARRANTY

As a Sika supplied accessory, Liquid Flashing Catalyst is covered under Sika Corporation warranties up to twenty (20) years in duration.

LEGAL NOTES

All information provided by Sika Corporation ("Sika") concerning Sika products, including but not limited to, any recommendations and advice relating to the application and use of Sika products, is given in good faith based on Sika's current experience and knowledge of its products when properly stored, handled and applied under normal conditions in accordance with Sika's instructions. In practice, the differences in materials, substrates, storage and handling conditions, actual site conditions and other factors outside of Sika's control are such that Sika assumes no liability for the provision of such information, advice, recommendations or instructions related to its products, nor shall any legal relationship be created by or arise from the provision of such information, advice, recommendations or instructions related to its products. The user of the Sika product(s) must test the product(s) for suitability for the intended application and purpose before proceeding with the full application of the product(s). Sika reserves the right to change the properties of its products without notice. All sales of Sika product(s) are subject to its current terms and conditions of sale which are available at usa.sarnafil.sika.com or by calling 800-451-2504.

Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's most current Product Data Sheet, product label and Safety Data Sheet which are available online at usa.sarnafil.sika.com or by calling Sika's Technical Service Department at 800-451-2504. Nothing contained in any Sika materials relieves the user of the obligation to read and follow the warnings and instruction for each Sika product as set forth in the current Product Data Sheet, product label and Safety Data Sheet prior to product use.

Sika warrants this product for one year from date of installation to be free from manufacturing defects and to meet the technical properties on the current Product Data Sheet if used as directed within shelf life. User determines suitability of product for intended use and assumes all risks. Buyer's sole remedy shall be limited to the purchase price or replacement of product exclusive of labor or cost of labor.

NO OTHER WARRANTIES EXPRESS OR IMPLIED SHALL APPLY INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES. SIKA SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

SIKA CORPORATION – ROOFING**UNITED STATES**

100 Dan Road
Canton, MA 02021
800-451-2504 (p)
781-828-5365 (f)
usa.sarnafil.sika.com
webmaster.sarnafil@us.sika.com

SIKA CANADA INC.

6915 Davand Drive
Mississauga, ON L5T 1L5
905-795-3177 (p)
905-795-3192 (f)
can.sika.com
marketing.construction@ca.sika.com

PRIOR TO EACH USE OF ANY SIKA PRODUCT, THE USER MUST ALWAYS READ AND FOLLOW THE WARNINGS AND INSTRUCTIONS ON THE PRODUCT'S MOST CURRENT PRODUCT DATA SHEET, PRODUCT LABEL AND SAFETY DATA SHEET WHICH ARE AVAILABLE ONLINE AT USA.SARNAFIL.SIKA.COM OR BY CALLING SIKA SARNAFIL'S TECHNICAL SERVICE DEPARTMENT AT 800-451-2504. NOTHING CONTAINED IN ANY SIKA MATERIALS RELIEVES THE USER OF THE OBLIGATION TO READ AND FOLLOW THE WARNINGS AND INSTRUCTIONS FOR EACH SIKA PRODUCT AS SET FORTH IN THE CURRENT PRODUCT DATA SHEET, PRODUCT LABEL AND SAFETY DATA SHEET PRIOR TO PRODUCT USE.

Product Data Sheet
Liquid Flashing Catalyst
4-19-18, VERSION #3

North America
Flashing

