

# PRODUCT DATA SHEET

## SIKAPLAN<sup>®</sup> TERMINATION BAR

Sikaplan Termination Bar is an extruded aluminum termination bar with a mill finish used to terminate Sikaplan roofing membranes at walls and roof edges. It is 3/4 in (19 mm) wide, 0.090 in (2.3 mm) thick and has a 3/16 in (4.8 mm) lip formed at a 45° angle. Each termination bar is 10 ft (3.05 m) long with oval holes punched 6 in (152 mm) on center.

### PRODUCT INFORMATION

#### USES

To terminate Sikaplan roofing membranes at walls and roof edges.

#### AREAS OF APPLICATION

- Wall terminations
- Roof edge terminations
- Other approved Sikaplan flashing details

#### FEATURES / BENEFITS

- Convenient punched ¼ in x ⅜ in (6.4 mm x 9.5 mm) oval holes spaced 6 in (152 mm) on center
- Preformed 45° lip

### PRODUCT DATA

#### FORM

#### COMPOSITION

Extruded aluminium (6063 T6 alloy) with a mill finish

#### PACKAGING

25 – 10 foot bars per tube (250 ft, 76.2 m), 29 lbs (13.2 kg) per tube, 10 tubes per pallet (2500 ft, 762 m)

### SYSTEM INFORMATION

#### APPLICATION INSTRUCTIONS

#### APPLICATION

Install Sikaplan Termination Bar with a ¼ in (6 mm) gap between adjoining bars. Cut Sikaplan Termination Bar at inside and outside corners. Do not bend around corners. Fasten Sikaplan Termination Bar with approved fasteners 12 in (305 mm) on center and within 1 in (25 mm) of each bar end. Refer to specific Sikaplan detail drawings.

#### COVERAGE

10 linear feet (3.05 m) per bar

#### PRODUCT LIMITATIONS

#### LIMITATIONS

For use with Sikaplan roof membranes. Refer to specific Sikaplan detail drawings.

<b>AVAILABILITY</b>	From Sika Corporation – Roofing Authorized Applications for use within Sikaplan systems.
<b>MAINTENANCE</b>	Standard maintenance of Sarnafil or Sikaplan systems should include regular inspection of flashings, drains, and termination sealants at least twice a year and after each storm.
<b>WARRANTY</b>	As a Sika supplied accessory, Sikplan Termination Bar is covered under Sika Corporation warranties.

**LEGAL NOTES**

All information provided by Sika Corporation (“Sika”) concerning Sika products, including but not limited to, any recommendations and advice relating to the application and use of Sika products, is given in good faith based on Sika’s current experience and knowledge of its products when properly stored, handled and applied under normal conditions in accordance with Sika’s instructions. In practice, the differences in materials, substrates, storage and handling conditions, actual site conditions and other factors outside of Sika’s control are such that Sika assumes no liability for the provision of such information, advice, recommendations or instructions related to its products, nor shall any legal relationship be created by or arise from the provision of such information, advice, recommendations or instructions related to its products. The user of the Sika product(s) must test the product(s) for suitability for the intended application and purpose before proceeding with the full application of the product(s). Sika reserves the right to change the properties of its products without notice. All sales of Sika product(s) are subject to its current terms and conditions of sale which are available at [usa.sarnafil.sika.com](http://usa.sarnafil.sika.com) or by calling 800-451-2504.

**Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product’s most current Product Data Sheet, product label and Safety Data Sheet which are available online at [usa.sarnafil.sika.com](http://usa.sarnafil.sika.com) or by calling Sika’s Technical Service Department at 800-451-2504. Nothing contained in any Sika materials relieves the user of the obligation to read and follow the warnings and instruction for each Sika product as set forth in the current Product Data Sheet, product label and Safety Data Sheet prior to product use.**

Sika warrants this product for one year from date of installation to be free from manufacturing defects and to meet the technical properties on the current Product Data Sheet if used as directed within shelf life. User determines suitability of product for intended use and assumes all risks. Buyer’s sole remedy shall be limited to the purchase price or replacement of product exclusive of labor or cost of labor.

**NO OTHER WARRANTIES EXPRESS OR IMPLIED SHALL APPLY INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES. SIKA SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.**

<b>SIKA CORPORATION – ROOFING</b>	<b>UNITED STATES</b>	<b>SIKA CANADA INC.</b>
	100 Dan Road Canton, MA 02021 800-451-2504 (p) 781-828-5365 (f) <a href="http://usa.sarnafil.sika.com">usa.sarnafil.sika.com</a> <a href="mailto:webmaster.sarnafil@us.sika.com">webmaster.sarnafil@us.sika.com</a>	6915 Davand Drive Mississauga, ON L5T 1L5 905-795-3177 (p) 905-795-3192 (f) <a href="http://can.sika.com">can.sika.com</a> <a href="mailto:marketing.construction@ca.sika.com">marketing.construction@ca.sika.com</a>