

# PRODUCT DATA SHEET

## WALL GRIP COPING

Wall Grip Coping is a metal coping with hold down cleats and metal drain chairs for capping almost any parapet. Wall Grip Coping is used with either an adhered or mechanically attached Sika Sarnafil Roof System to secure and protect membrane flashings.

### PRODUCT INFORMATION

#### USES

For capping almost any parapet

#### AREAS OF APPLICATION

- Capping
- Mechanically Fastened Systems
- Adhered Systems

#### FEATURES / BENEFITS

- Eliminates caulked joints
- True welded radius, matching corners, end caps, and other accessories are factory fabricated
- Supplied stainless steel fasteners and pre-punched holes for proper attachment and fast installation
- utilizes a metal chair which functions as both a gutter chair to channel water and as an internal splice plate in the same color and finish as the coping cap

#### TESTS

#### STANDARDS / APPROVALS

- UL ANSI/SPRI ES-1 Roof Edge Standard Test Protocol RE-3 for coping
- FM

### PRODUCT DATA

#### FORM

#### COMPOSITION

Wall Grip Coping is formed from .063 in (1.60 mm) or .050 in (1.25 mm) aluminum; 24ga. galv. steel with Kynar 500® coating. Cleats are 20ga. galvanized steel. Chairs are metal in the same color and finish as the coping cap. Fabricated to the wall width required between 6 in and 32 in. Face and back leg are 4 in (102mm) nominal length with tested approvals up to 6" (152mm).

#### COLOR

Mill Finish, Kynar 500 Colors, Clear Anodize, Bronze Anodize

#### DIMENSIONS

Length: 10 ft (3 m)

#### PACKAGING

The entire Wall Grip Coping assembly is packaged in job specific crates to provide maximum protection during transportation.

---

**TECHNICAL DATA**

TYPICAL PHYSICAL PROPERTIES		
Standard Sizes	Material	Gauge
Wall Sizes – 6 in - 32 in	Aluminum	Standard is 0.050 in & 0.063 in
Standard Leg Size – 4 in Minimum Leg Size – 2.125 in Maximum Leg Size – 12 in	Galvanized Steel	Standard is 24 Gauge up to 24 in wall
Miter Leg Lengths < 16 in wall = 23.25 in 17 in – 23 in Wall = 29.25 in 24 in – 32 in = Custom Length	Copper & Stainless Steel by Request	Other Metal Thicknesses by Request

---

**SYSTEM INFORMATION****INSTALLATION**

The substrate should be flat and level from front to back. Shim areas not level.

The first cleat/chair set should be installed with the center line of the cleat set to the miter leg length and 24 in (300mm) from the end of a wall. Install cleats/chairs sets at all corners and ends first, then work along the wall to the center locating sets every 60" on center for walls less than 17 in and 40 in on center for walls 17 in – 32 in. Adjust the cleat location in the middle of a run to fit a short coping length. This procedure will provide a symmetrical appearance of the installed coping. Install metal gutter chair/concealed joint covers at joint locations. Hook coping face leg over the cleat face (front) leg and swing over the top. Snap the roof side (back) leg by pressing firmly down on the back edge directly over the cleat chair sets. Allow 1/8 in (3mm) gap, ¼ in (6mm) in colder weather, at each joint.

**AVAILABILITY**

From Sika Corporation – Roofing Authorized Applications for use within Sarnafil or Sikaplan systems.

**MAINTENANCE**

Standard maintenance of Sarnafil or Sikaplan systems should include regular inspection of flashings, drains, and termination sealants at least twice a year and after each storm.

**WARRANTY**

As a Sika supplied accessory, Wall Grip Coping is covered under Sika Corporation warranties.

---

---

**LEGAL NOTES**

All information provided by Sika Corporation ("Sika") concerning Sika products, including but not limited to, any recommendations and advice relating to the application and use of Sika products, is given in good faith based on Sika's current experience and knowledge of its products when properly stored, handled and applied under normal conditions in accordance with Sika's instructions. In practice, the differences in materials, substrates, storage and handling conditions, actual site conditions and other factors outside of Sika's control are such that Sika assumes no liability for the provision of such information, advice, recommendations or instructions related to its products, nor shall any legal relationship be created by or arise from the provision of such information, advice, recommendations or instructions related to its products. The user of the Sika product(s) must test the product(s) for suitability for the intended application and purpose before proceeding with the full application of the product(s). Sika reserves the right to change the properties of its products without notice. All sales of Sika product(s) are subject to its current terms and conditions of sale which are available at [usa.sarnafil.sika.com](http://usa.sarnafil.sika.com) or by calling 800-451-2504.

Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's most current Product Data Sheet, product label and Safety Data Sheet which are available online at [usa.sarnafil.sika.com](http://usa.sarnafil.sika.com) or by calling Sika's Technical Service Department at 800-451-2504. Nothing contained in any Sika materials relieves the user of the obligation to read and follow the warnings and instruction for each Sika product as set forth in the current Product Data Sheet, product label and Safety Data Sheet prior to product use.

Sika warrants this product for one year from date of installation to be free from manufacturing defects and to meet the technical properties on the current Product Data Sheet if used as directed within shelf life. User determines suitability of product for intended use and assumes all risks. Buyer's sole remedy shall be limited to the purchase price or replacement of product exclusive of labor or cost of labor.

**NO OTHER WARRANTIES EXPRESS OR IMPLIED SHALL APPLY INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES. SIKA SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.**

---

**SIKA CORPORATION – ROOFING****UNITED STATES**

100 Dan Road  
Canton, MA 02021  
800-451-2504 (p)  
781-828-5365 (f)  
[usa.sarnafil.sika.com](http://usa.sarnafil.sika.com)  
[webmaster.sarnafil@us.sika.com](mailto:webmaster.sarnafil@us.sika.com)

**SIKA CANADA INC.**

6915 Davand Drive  
Mississauga, ON L5T 1L5  
905-795-3177 (p)  
905-795-3192 (f)  
[can.sika.com](http://can.sika.com)  
[marketing.construction@ca.sika.com](mailto:marketing.construction@ca.sika.com)

---