

# PRODUCT DATA SHEET

## SIKACOAT® W400

Sikacoat® W400 is a low viscosity detergent wash intended for application to all types of roof surfaces prior to power washing. Sikacoat W400 lifts dirt and grease from the surface of the roof. Sikacoat W400 is formulated from surfactants and alkaline cleaning agents. Sikacoat W400 must be used to clean all EPDM surfaces before the application of a Sikacoat base coat.

### PRODUCT INFORMATION

#### USES

Sikacoat W400 is used to clean all EPDM surfaces prior to installing the Sikacoat roof coating system. It is also used to clean all types of roof surfaces prior to power washing.

#### AREAS OF APPLICATION

- EPDM when using the Sikacoat roof coating system
- All types of roof surfaces for general cleaning

#### FEATURES / BENEFITS

- Effective roof cleaning agent
- Spray apply with a garden sprayer
- Fast acting

### PRODUCT DATA

#### FORM

#### COMPOSITION

Liquid concentrate

#### COLOR

Yellow

#### VOC CONTENT

0 g/l

#### PACKAGING

5 gallon (18.9 L) pails, 45 lbs (20.4 kg) per pail, 36 pails per pallet

#### STORAGE

#### STORAGE CONDITIONS

Store materials in a dry area between 40°F (5°C) and 100°F (38°C) with careful handling to prevent damage to products. Do not store at high temperatures or in direct sunlight. Keep lids tightly closed when not in use. Protect all materials from freezing and other damage during transit, handling, storage, and installation.

PRIOR TO EACH USE OF ANY SIKA PRODUCT, THE USER MUST ALWAYS READ AND FOLLOW THE WARNINGS AND INSTRUCTIONS ON THE PRODUCT'S MOST CURRENT PRODUCT DATA SHEET, PRODUCT LABEL AND SAFETY DATA SHEET WHICH ARE AVAILABLE ONLINE AT [USA.SARNAFIL.SIKA.COM](http://USA.SARNAFIL.SIKA.COM) OR BY CALLING SIKA SARNAFIL'S TECHNICAL SERVICE DEPARTMENT AT 800-451-2504. NOTHING CONTAINED IN ANY SIKA MATERIALS RELIEVES THE USER OF THE OBLIGATION TO READ AND FOLLOW THE WARNINGS AND INSTRUCTIONS FOR EACH SIKA PRODUCT AS SET FORTH IN THE CURRENT PRODUCT DATA SHEET, PRODUCT LABEL AND SAFETY DATA SHEET PRIOR TO PRODUCT USE.

	<p><b>SHELF LIFE</b></p> <p>12 months if stored properly in original unopened, sealed and undamaged packaging.</p>
<b>TECHNICAL DATA</b>	<p><b>TYPICAL PHYSICAL PROPERTIES*</b></p> <p>pH: 11</p> <p>*Results may differ based upon statistical variations depending upon mixing methods and equipment, temperature, application methods, test methods, actual site conditions and curing conditions.</p>
<b>SYSTEM INFORMATION</b>	
<b>APPLICATION INSTRUCTIONS</b>	<p><b>MIXING</b></p> <p>Mix one part Sikacoat W400 with four parts water. Improper dilution will affect performance.</p> <p><b>APPLICATION</b></p> <p>Apply properly diluted Sikacoat W400 with a garden type sprayer in sufficient quantity to wet out the surface for a minimum of 15 minutes without drying. Power wash Sikacoat W400 from the roof followed by a final clean water rinse. Follow all local and federal environmental regulations regarding wash water capture and disposal.</p> <p><b>COVERAGE</b></p> <p>The typical coverage rate is 500 square feet per gallon (12.25 m<sup>2</sup>/L) of properly diluted Sikacoat W400.</p>
<b>PRODUCT LIMITATIONS</b>	<p><b>LIMITATIONS</b></p> <p>Precautions should be taken to prevent odors and/or vapors from entering the building/structure, including but not limited to turning off and sealing air intake vents or other means of ingress for odors and/or vapors into the building/structure during product application and cure.</p> <ul style="list-style-type: none"> <li>• Sikacoat W400 when used will cause the roof surface to be wet. Roof surfaces may be slippery when wet. All applicable OSHA requirements for safe work practices must be followed.</li> <li>• Avoid contact with paint, siding and vegetation. If contact occurs flush with water until Sikacoat W400 is removed and substantially diluted.</li> </ul>
<b>AVAILABILITY</b>	From Authorized Applicators when used within Sikacoat roofing systems.
<b>MAINTENANCE</b>	Standard maintenance of roofs should include regular inspection of flashings, drains and termination sealants at least twice a year and after each storm.
<b>WARRANTY</b>	As a Sika supplied accessory, Sikacoat W400 is covered under Sika Corporation warranties.

PRIOR TO EACH USE OF ANY SIKA PRODUCT, THE USER MUST ALWAYS READ AND FOLLOW THE WARNINGS AND INSTRUCTIONS ON THE PRODUCT'S MOST CURRENT PRODUCT DATA SHEET, PRODUCT LABEL AND SAFETY DATA SHEET WHICH ARE AVAILABLE ONLINE AT USA.SARNAFIL.SIKA.COM OR BY CALLING SIKA SARNAFIL'S TECHNICAL SERVICE DEPARTMENT AT 800-451-2504. NOTHING CONTAINED IN ANY SIKA MATERIALS RELIEVES THE USER OF THE OBLIGATION TO READ AND FOLLOW THE WARNINGS AND INSTRUCTIONS FOR EACH SIKA PRODUCT AS SET FORTH IN THE CURRENT PRODUCT DATA SHEET, PRODUCT LABEL AND SAFETY DATA SHEET PRIOR TO PRODUCT USE.

---

**LEGAL NOTES**

All information provided by Sika Corporation ("Sika") concerning Sika products, including but not limited to, any recommendations and advice relating to the application and use of Sika products, is given in good faith based on Sika's current experience and knowledge of its products when properly stored, handled and applied under normal conditions in accordance with Sika's instructions. In practice, the differences in materials, substrates, storage and handling conditions, actual site conditions and other factors outside of Sika's control are such that Sika assumes no liability for the provision of such information, advice, recommendations or instructions related to its products, nor shall any legal relationship be created by or arise from the provision of such information, advice, recommendations or instructions related to its products. The user of the Sika product(s) must test the product(s) for suitability for the intended application and purpose before proceeding with the full application of the product(s). Sika reserves the right to change the properties of its products without notice. All sales of Sika product(s) are subject to its current terms and conditions of sale which are available at [usa.sarnafil.sika.com](http://usa.sarnafil.sika.com) or by calling 800-451-2504.

**Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's most current Product Data Sheet, product label and Safety Data Sheet which are available online at [usa.sarnafil.sika.com](http://usa.sarnafil.sika.com) or by calling Sika's Technical Service Department at 800-451-2504. Nothing contained in any Sika materials relieves the user of the obligation to read and follow the warnings and instruction for each Sika product as set forth in the current Product Data Sheet, product label and Safety Data Sheet prior to product use.**

Sika warrants this product for one year from date of installation to be free from manufacturing defects and to meet the technical properties on the current Product Data Sheet if used as directed within shelf life. User determines suitability of product for intended use and assumes all risks. Buyer's sole remedy shall be limited to the purchase price or replacement of product exclusive of labor or cost of labor.

**NO OTHER WARRANTIES EXPRESS OR IMPLIED SHALL APPLY INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES. SIKA SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.**

---

**SIKA CORPORATION – ROOFING****UNITED STATES**

100 Dan Road  
Canton, MA 02021  
800-451-2504 (p)  
781-828-5365 (f)  
[usa.sarnafil.sika.com](http://usa.sarnafil.sika.com)  
[webmaster.sarnafil@us.sika.com](mailto:webmaster.sarnafil@us.sika.com)

**SIKA CANADA INC.**

6915 Davand Drive  
Mississauga, ON L5T 1L5  
905-795-3177 (p)  
905-795-3192 (f)  
[can.sika.com](http://can.sika.com)  
[marketing.construction@ca.sika.com](mailto:marketing.construction@ca.sika.com)

---

**PRIOR TO EACH USE OF ANY SIKA PRODUCT, THE USER MUST ALWAYS READ AND FOLLOW THE WARNINGS AND INSTRUCTIONS ON THE PRODUCT'S MOST CURRENT PRODUCT DATA SHEET, PRODUCT LABEL AND SAFETY DATA SHEET WHICH ARE AVAILABLE ONLINE AT [USA.SARNAFIL.SIKA.COM](http://USA.SARNAFIL.SIKA.COM) OR BY CALLING SIKA SARNAFIL'S TECHNICAL SERVICE DEPARTMENT AT 800-451-2504. NOTHING CONTAINED IN ANY SIKA MATERIALS RELIEVES THE USER OF THE OBLIGATION TO READ AND FOLLOW THE WARNINGS AND INSTRUCTIONS FOR EACH SIKA PRODUCT AS SET FORTH IN THE CURRENT PRODUCT DATA SHEET, PRODUCT LABEL AND SAFETY DATA SHEET PRIOR TO PRODUCT USE.**

