



1. Identification

Product name	:	Vapor Retarder Primer SB
Supplier	:	Sika Corporation
Address	:	201 Polito Avenue Lyndhurst, NJ 07071 USA www.sikausa.com
Telephone	:	(201) 933-8800
Telefax	:	(201) 804-1076
Emergency telephone	:	CHEMTREC: 800-424-9300 INTERNATIONAL: 703-527-3887 ehs@sika-corp.com
Recommended use of the chemical and restrictions on use	:	For further information, refer to the product technical data sheet.

2. Hazards identification

GHS Classification

Flammable liquids, Category 2	H225: Highly flammable liquid and vapor.
Skin irritation, Category 2	H315: Causes skin irritation.
Eye irritation, Category 2A	H319: Causes serious eye irritation.
Carcinogenicity, Category 2	H351: Suspected of causing cancer.
Specific target organ systemic toxicity - single exposure, Category 3, Central nervous system	H336: May cause drowsiness or dizziness.

GHS Label element

Hazard pictograms	:	
Signal Word	:	Danger
Hazard Statements	:	H225 Highly flammable liquid and vapor. H315 Causes skin irritation. H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness. H351 Suspected of causing cancer.
Precautionary Statements	:	Prevention: P201 Obtain special instructions before use. P202 Do not handle until all safety precautions have been read and understood. P210 Keep away from heat/sparks/open flames/hot surfaces.



No smoking.
P233 Keep container tightly closed.
P240 Ground/bond container and receiving equipment.
P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment.
P242 Use only non-sparking tools.
P243 Take precautionary measures against static discharge.
P261 Avoid breathing dust/ fume/ gas/ mist/ vapors/ spray.
P264 Wash skin thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves/ eye protection/ face protection.
P281 Use personal protective equipment as required.

Response:

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308 + P313 IF exposed or concerned: Get medical advice/ attention.
P332 + P313 If skin irritation occurs: Get medical advice/ attention.
P337 + P313 If eye irritation persists: Get medical advice/ attention.
P362 Take off contaminated clothing and wash before reuse.
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.
P403 + P235 Store in a well-ventilated place. Keep cool.
P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Warning : Reports have associated repeated and prolonged exposure to some of the chemicals in this product with permanent brain, liver, kidney and nervous system damage. Intentional misuse by deliberate concentration and inhalation of vapors may be harmful or fatal.

See Section 11 for more detailed information on health effects and symptoms.
There are no hazards not otherwise classified that have been identified during the classification process.
There are no ingredients with unknown acute toxicity used in a mixture at a concentration \geq 1%.

3. Composition/information on ingredients

Hazardous ingredients



Chemical Name	CAS-No.	Concentration (%)
naphtha (petroleum), hydrotreated light (C7-C8 Alkanes/ Cycloalkanes)	64742-49-0	>= 50 - <= 100 %
acetone	67-64-1	>= 25 - < 50 %

may contain: n-heptane (CAS:142-82-5), n-hexane (CAS:110-54-3)

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

4. First aid measures

- If inhaled : Move to fresh air.
Consult a physician after significant exposure.
- In case of skin contact : Take off contaminated clothing and shoes immediately.
Wash off with soap and plenty of water.
If symptoms persist, call a physician.
- In case of eye contact : Immediately flush eye(s) with plenty of water.
Remove contact lenses.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
- If swallowed : Clean mouth with water and drink afterwards plenty of water.
Do NOT induce vomiting.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
Obtain medical attention.
- Most important symptoms and effects, both acute and delayed : irritant effects

Respiratory disorder
Excessive lachrymation
Erythema
Dermatitis
Loss of balance
Vertigo
See Section 11 for more detailed information on health effects and symptoms.

Causes skin irritation.
Causes serious eye irritation.
May cause drowsiness or dizziness.
Suspected of causing cancer.
- Protection of first-aiders : Move out of dangerous area.
Consult a physician.
Show this material safety data sheet to the doctor in attendance.
- Notes to physician : Treat symptomatically.



5. Fire-fighting measures

- Suitable extinguishing media : Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical
- Unsuitable extinguishing media : Water
High volume water jet
- Specific hazards during fire fighting : Do not use a solid water stream as it may scatter and spread fire.
- Specific extinguishing methods : Use water spray to cool unopened containers.
Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
- Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus.

6. Accidental release measures

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Remove all sources of ignition.
Deny access to unprotected persons.
Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low areas.
- Environmental precautions : Prevent product from entering drains.
If the product contaminates rivers and lakes or drains inform respective authorities.
Local authorities should be advised if significant spillages cannot be contained.
- Methods and materials for containment and cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

7. Handling and storage

- Advice on safe handling : Do not breathe vapors or spray mist.
Avoid exceeding the given occupational exposure limits (see section 8).
Do not get in eyes, on skin, or on clothing.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Take precautionary measures against static discharge.
Open drum carefully as content may be under pressure.
Take necessary action to avoid static electricity discharge



(which might cause ignition of organic vapors).
Follow standard hygiene measures when handling chemical products.

Conditions for safe storage : Store in original container.
Store in cool place.
Keep in a well-ventilated place.
Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Observe label precautions.
Store in accordance with local regulations.

Materials to avoid : No data available

8. Exposure controls/personal protection

Component	CAS-No.	Basis **	Value	Exposure limit(s)* / Form of exposure
naphtha (petroleum), hydrotreated light (C7-C8 Alkanes/ Cycloalkanes)	64742-49-0	OSHA Z-1	TWA	500 ppm 2,000 mg/m3
acetone	67-64-1	ACGIH	TWA	500 ppm
		ACGIH	STEL	750 ppm
		OSHA Z-1	TWA	1,000 ppm 2,400 mg/m3
		OSHA P0	TWA	750 ppm 1,800 mg/m3
		OSHA P0	STEL	1,000 ppm 2,400 mg/m3

*The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

**Basis

ACGIH. Threshold Limit Values (TLV)

OSHA P0. Table Z-1, Limit for Air Contaminat (1989 Vacated Values)

OSHA P1. Permissible Exposure Limits (PEL), Table Z-1, Limit for Air Contaminant

OSHA P2. Permissible Exposure Limits (PEL), Table Z-2

OSHA Z3. Table Z-3, Mineral Dust

Engineering measures : Use of adequate ventilation should be sufficient to control worker exposure to airborne contaminants. If the use of this product generates dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure below any recommended or statutory limits.



The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits.

Personal protective equipment

- Respiratory protection : Use a properly fitted NIOSH approved air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.
- The filter class for the respirator must be suitable for the maximum expected contaminant concentration (gas/vapor/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-contained breathing apparatus must be used.
- Hand protection
Remarks : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.
- Eye protection : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary.
- Skin and body protection : Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.
- Hygiene measures : Avoid contact with skin, eyes and clothing.
Wash hands before breaks and immediately after handling the product.
Remove respiratory and skin/eye protection only after vapors have been cleared from the area.
Remove contaminated clothing and protective equipment before entering eating areas.
Wash thoroughly after handling.

9. Physical and chemical properties

- Appearance : liquid
- Color : red
- Odor : strong solvent
- Odor Threshold : No data available
- Flash point : -9 °F (-23 °C)
Method: ASTM D 93
- Ignition temperature : No data available
- Decomposition temperature : No data available



Lower explosion limit (Vol%)	: 1.1 %(V)
Upper explosion limit (Vol%)	: 7.4 %(V)
Flammability (solid, gas)	: No data available
Oxidizing properties	: No data available
Autoignition temperature	: No data available
pH	: No data available
Melting point/range / Freezing point	: No data available
Boiling point/boiling range	: No data available
Vapor pressure	: 26.000 mmHg (34.6637 hpa)
Density	: ca.0.77 g/cm ³ at 68 °F (20 °C)
Water solubility	: Note: insoluble
Partition coefficient: n- octanol/water	: No data available
Viscosity, dynamic	: No data available
Viscosity, kinematic	: > 20.5 mm ² /s at 104 °F (40 °C)
Relative vapor density	: No data available
Evaporation rate	: No data available
Burning rate	: No data available
Volatile organic compounds (VOC) content	: 500 g/l

10. Stability and reactivity

Reactivity	: No dangerous reaction known under conditions of normal use.
Chemical stability	: The product is chemically stable.
Possibility of hazardous reactions	: Stable under recommended storage conditions. Vapors may form explosive mixture with air.
Conditions to avoid	: Heat, flames and sparks.
Incompatible materials	: No data available



11. Toxicological information

Not classified based on available information.

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitization

Skin sensitization: Not classified based on available information.

Respiratory sensitization: Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Suspected of causing cancer.

IARC Not applicable

NTP Not applicable

Reproductive toxicity

Not classified based on available information.

STOT-single exposure

May cause drowsiness or dizziness.

STOT-repeated exposure

Reports have associated repeated and prolonged exposure to some of the chemicals in this product with permanent brain, liver, kidney and nervous system damage. Intentional misuse by deliberate concentration and inhalation of vapors may be harmful or fatal.

Aspiration toxicity

Not classified based on available information.

12. Ecological information

Other information	Do not empty into drains; dispose of this material and its container in a safe way. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. May be harmful to the environment if released in large quantities. Water polluting material.
-------------------	--

Component:

acetone	67-64-1	<u>Toxicity to fish:</u> LC50 Species: Fish Dose: > 5,000 mg/l Exposure time: 96 h
---------	---------	--

Toxicity to daphnia and other aquatic invertebrates:

EC50
 Species: Daphnia
 Dose: 12.700 mg/l
 Exposure time: 48 h

Toxicity to algae:

ErC50
 Species: Pseudokirchneriella subcapitata (green algae)
 Dose: > 530 mg/l
 Exposure time: 96 h

13. Disposal considerations**Disposal methods**

- Waste from residues : Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.
- Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information**DOT**

UN number	1133
Description of the goods	Adhesives
Class	3
Packing group	II
Labels	3
Emergency Response	128
Guidebook Number	

IATA

UN number	1133
Description of the goods	Adhesives (naphtha (petroleum), hydrotreated light (C7-C8 Alkanes/ Cycloalkanes))
Class	3
Packing group	II
Labels	3
Packing instruction (cargo aircraft)	364
Packing instruction (passenger aircraft)	353
Packing instruction (passenger aircraft)	Y341

IMDG

UN number	1133
-----------	------

Vapor Retarder Primer SB

Revision Date 08/04/2015

Print Date 08/07/2015

Description of the goods	ADHESIVES (naphtha (petroleum), hydrotreated light (C7-C8 Alkanes/ Cycloalkanes))
Class	3
Packing group	II
Labels	3
EmS Number 1	F-E
EmS Number 2	S-D
Marine pollutant	yes

DOT: For Limited Quantity exceptions reference 49 CFR 173.150 (b)

IMDG: For Limited Quantity special provisions reference IMDG Code Chapter 3.4

Special precautions for user

No data available

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

15. Regulatory information

TSCA list : All chemical substances in this product are either listed on the TSCA Inventory or are in compliance with a TSCA Inventory exemption.

EPCRA - Emergency Planning and Community Right-to-Know**CERCLA Reportable Quantity**

This material does not contain any components with a CERCLA RQ.

SARA304 Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards : Acute Health Hazard
Fire Hazard

SARA 302 : No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313 : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

Clean Air Act**Ozone-Depletion Potential**

This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

Vapor Retarder Primer SB

Revision Date 08/04/2015

Print Date 08/07/2015

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 12 (40 CFR 61).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

California Prop 65

This product does not contain any chemicals known to the State of California to cause cancer, birth, or any other reproductive defects.

16. Other information**HMIS Classification**

Health	*	2
Flammability		3
Physical Hazard		0
Personal Protection		X

Caution: HMIS® rating is based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® rating is not required on SDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® rating is to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). Please note HMIS® attempts to convey full health warning information to all employees.

Notes to Reader

The information contained in this Safety Data Sheet applies only to the actual Sika Corporation ("Sika") product identified and described herein. This information is not intended to address, nor does it address the use or application of the identified Sika product in combination with any other material, product or process. All of the information set forth herein is based on technical data regarding the identified product that Sika believes to be reliable as of the date hereof. Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's current Product Data Sheet, product label and Safety Data Sheet for each Sika product, which are available at web site and/or telephone number listed in Section 1 of this SDS.

SIKA MAKES NO WARRANTIES EXPRESS OR IMPLIED AND ASSUMES NO LIABILITY ARISING FROM THIS INFORMATION OR ITS USE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES AND SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

All sales of Sika products are subject to its current terms and conditions of sale available at www.sikausa.com or 201-933-8800.

Revision Date 08/04/2015

Material number: 499886