

World Class Roofing and Waterproofing

## ROOFING TECHNICAL BULLETIN

#05-13

To: Roofing Consultants

**Authorized Roofing Applicators** 

Sika Sarnafil Sales Staff & Sales Representatives

Sika Sarnafil Regional Technical Staff Sika Sarnafil Customer Service Staff

Sika Sarnafil Services Staff Sika Sarnafil Marketing

From: Sika Sarnafil Technical Service Department

Date: May 3, 2013

**Subject: Sikaplan Perimeter Fixation** 

Currently our requirement for perimeter securement on Sikaplan projects is a minimum of two 5ft (1.5m) wide perimeter sheets. Sika Sarnafil is now accepting the practice for allowing one single 5ft (1.5m) wide perimeter sheet with Sarnafast systems and a 5ft (1.5m) wide perimeter area with RhinoBond systems (to be done in conjunction with required RhinoBond fixation patterns for the field, perimeters, and corners). The following highlights criteria which must be met and followed.

- 1) Only to be used on **non FM insured** Sikaplan projects.
- 2) Only to be used on buildings with a max building height of up to 40ft (12.2m) regardless of plan dimensions.
- 3) Only to be used on approved steel decks of 22ga or heavier, structural concrete, or ½in or greater plywood (plywood must be a min. of 5 plies).
- 4) Only to be used on projects covered by Sikaplan Standard and System warranties (not applicable to "NDL" type warranties or greater than Gale Force winds).

It is up to the designer and/or the contractor to verify and/or confirm code compliance.

For further information regarding these changes please contact Sika Sarnafil's technical department.



