



DSDO-15R 15 MINUTE FE/BR OPAQUE DOUBLE DOOR

- A.F.F. = ABOVE FINISHED FLOOR
- C.O. = CLEAR OPENING
- CUST. = CUSTOMER
- D.O. = DOOR OPENING
- EXT. = EXTERIOR
- F.F. = FINISHED FRAME
- INT. = INTERIOR
- LOC. = LOCATION
- No. = NUMBER
- PO. = PURCHASE ORDER
- QTY. = QUANTITY
- R.O. = ROUGH OPENING
- V.O. = VISION OPENING
- WO. = WORK ORDER

DOS MODEL No. GDDO-15R-R0S-01
ROSS MODEL No. DSDO-15R-X-01
GLAZING No. N/A

ITEM	QTY.	PART NO.	DESCRIPTION
4	1	15MIN DD OP 800	TUBE SUBFRAME ASSEMBLY AND WELD
3	1	15MIN DD OP 300	FRAME ASSEMBLY AND WELD
2	1	15MIN DD OP 200	INACTIVE LEAF ASSEMBLY
1	1	15MIN DD OP 100	ACTIVE LEAF ASSEMBLY

SCALE			ROSS TECHNOLOGY CORP. ARCHITECTURAL SECURITY LEOLA, PA. 17540	
TOLERANCES	ANGULAR (DEG/MIN)	± 0'30"	CUSTOMER	
	LINEAR (FRAC)	± 1/16		
	LINEAR (DEC)	.X ± .06	W.O #	
		.XX ± .03		
		.XXX ± .015		
DRAWN BY	CHKD BY	CNC NO.	TITLE DSDO-15R 15 MINUTE FE/BR / OPAQUE DOUBLE DOOR	
DATE	DATE	DISK #	DWG. NO. DSDO-15R CAD	REV