



TYPICAL FRAME JAMB SECTION - WITH EMBED - 2X SCALE

DSSO-15R 15 MINUTE FE/BR OPAQUE DOOR

- A.F.F. = ABOVE FINISHED FLOOR
- C.O. = CLEAR OPENING
- CUST. = CUSTOMER
- D.O. = DOOR OPENING
- EXT. = EXTERIOR
- F.F. = FINISHED FRAME
- INT. = INTERIOR
- LOC. = LOCATION
- No. = NUMBER
- PO. = PURCHASE ORDER
- QTY. = QUANTITY
- R.O. = ROUGH OPENING
- V.O. = VISION OPENING
- WO. = WORK ORDER

ROSS MODEL No. DSSO-15R-X-01
DOS MODEL No. GDO-15R-R0S-01
GLAZING No. N/A

ITEM	QTY.	PART NO.	DESCRIPTION
3	1	15MIN OP 800	SUB FRAME
2	1	15MIN OP 200	FRAME ASSEMBLY AND WELD
1	1	15MIN OP 100	DOOR ASSEMBLY AND WELD

			SCALE		ROSS TECHNOLOGY CORP. ARCHITECTURAL SECURITY LEOLA, PA. 17540	
TOLERANCES	ANGULAR (DEG/MIN)	± 0'30"	CUSTOMER			
	LINEAR (FRAC)	± 1/16				
	LINEAR (DEC)	.X ± .06 .XX ± .03 .XXX ± .015	DRAWN BY		CHKD BY	CNC NO.
DATE	DATE	DISK #	DWG. NO. DSSO-15R CAD		REV	