



OPD-2133A (FIRE) 60 MINUTE FE/BR OPAQUE DOUBLE FIRE DOOR

A.F.F. = ABOVE FINISHED FLOOR  
 C.O. = CLEAR OPENING  
 CUST. = CUSTOMER  
 D.O. = DOOR OPENING  
 EXT. = EXTERIOR  
 F.F. = FINISHED FRAME  
 INT. = INTERIOR  
 LOC. = LOCATION  
 No. = NUMBER  
 PO. = PURCHASE ORDER  
 QTY. = QUANTITY  
 R.O. = ROUGH OPENING  
 V.O. = VISION OPENING  
 WO. = WORK ORDER

ROSS No. OPD-2133A FIRE  
 MODEL No. GDD-60R-ROS-01F

3	1	60MIN DD OP 800	SUB FRAME
2	1	60MIN DD OP 200	L-FRAME ASSEMBLY AND WELD
1	1	60MIN DD OP 100	DOOR ASSEMBLY AND WELD
ITEM	QTY.	PART NO.	DESCRIPTION

		SCALE		<b>ROSS TECHNOLOGY CORP.</b> <b>ARCHITECTURAL SECURITY</b> LEOLA, PA. 17540	
TOLERANCES	ANGULAR (DEG/MIN)	± 0'30"			
	LINEAR (FRAC)	± 1/16			
	LINEAR (DEC)	.X ± .06 .XX ± .03 .XXX ± .015			
DRAWN BY	CHKD BY	CNC NO.	TITLE		
DATE	DATE	DISK #	OPD-2133A 60 MIN. FE/BR/OPAQUE DOUBLE FIRE DOOR		
			DWG. NO.	REV	
			OPD-2133A (FIRE) CAD		