

<b>Project:</b>	<b>Quantity:</b>
<b>Model #:</b>	<b>Approval:</b>

# CFD-3RR 81" Triple Solid Door Reach-In Refrigerator



## FEATURES

- ▶ Holds Temperature Between -33°F to 41°F
- ▶ Adjustable PVC Coated Shelves
- ▶ Stainless Steel Construction
- ▶ Preinstalled Casters with Brakes
- ▶ Self-closing Door with 90° Stay Open Feature
- ▶ Electronic Control System
- ▶ Hydro-Carbon R290 Refrigerant
- ▶ cETLus, ETL-S, NSF

This triple door reach-in refrigerator with 72 cu. ft. capacity features a heavy duty stainless steel construction ensuring many years of dependability in even the most difficult commercial settings. Insulated self-closing lockable doors allow CFD models to hold safe temperatures in the hottest kitchens. Includes 9 wire shelves with a versatile shelf slide design. Fits full-size hotel pans in either orientation. Lockable heavy duty wheels come standard. This unit uses HYDRO-CARBON R290 refrigerant, which is environmentally friendly and more efficient than R134a/R404a refrigerant.

- ▶ ETL Certified
- ▶ ETL Sanitation
- ▶ NSF Compliant



## WARRANTY

Coldline products are backed by a 1 Year / 5 Year limited manufacturer warranty. The unit itself and parts within are guaranteed against manufacturing defects for a period of 1 year. The compressor is guaranteed for an additional 4 years. Extended warranty is available. Glass, due to its fragile nature, is not included under warranty coverage. Always inspect your delivery for freight damage before you accept it. Freight damage will not be considered a manufacturing defect and should be refused or remedied through a claim with the carrier.



<b>Project:</b>	<b>Quantity:</b>
<b>Model #:</b>	<b>Approval:</b>

## TECHNICAL DATA

### DIMENSIONS

Exterior Dimensions	80.9"L x 32.2"D x 82.5"H
Interior Dimensions	76.4"L x 27"D x 60.3"H
Packaging Dimensions	83.3"L x 34"D x 84.5"H
Net Volume	72 cu. ft.
Unit Weight	615 lb.
Shipping Weight	693 lb.

### ELECTRICAL

Voltage	115
Hertz	60
Phase	1
Amps	9
Plug Type	NEMA 5-15P
Power Cord Length	96"

### COOLING

Temperature Range	-33°F - 41°F
Refrigerant	R290
Max. Ambient Temp	90°F
Defrosting	Automatic
Temperature Controller	Digital
Horsepower	3/4

### CONSTRUCTION

Exterior Material	430 Stainless Steel
Interior Material	304 Stainless Steel
Insulation Material	Foamed-in-Place Polyurethane
Shelf Size	6 Qty: 20.9"L x 25.2"D 3 Qty: 22.1"L x 25.2"D
Shelf Material	Epoxy Coated Wire
Shelf Load Capacity	120 lb.

## DIAGRAM

### MODEL: CFD-3RR

