



Dimmer Compatibility List for Lotus LED Recessed Lights

LLL Model:		LL2G	LL3G	LL4G	LRG6	LL4R	LL6R	LY4RCS	LB4R	LY82RCD	LL8R	LL10R		
		LRG2	LRG3	LRG4	LB6R	LL4S	LL6S		LY4S					
		LSG2	LSG3	LY41RCD LY6RCS	LY61RCD LY6S / LL6S LL4RRG / LL4RR LL4SRG / LL4SR		LL6RRG / LL6RR LL6SRG / LL6SR		LL4S LL4S LL4RBX					
DIMMING MODE		TRIAC DIMMABLE - FORWARD PHASE AND REVERSE PHASE SUPPORTED										0-10V		
WATTAGE		5W	7.5W	11.4W	15W	13.5W	17W	9W	11W	33W	40W	50W		
DEFAULT DRIVER INPUT		120V										120V - 277V		
OPTIONAL DRIVER INPUT		N/A	277V - 347V - NOT DIMMABLE									347V		
BRAND	FAMILY	DIMMER MODEL	RECOMMENDED NUMBER OF FIXTURES PER DIMMER AT 80% OF THE DIMMER CAPACITY											
LUTRON	SKYLARK SKYLARK CONTOUR DIVA ARIADNI TOGGLER MAESTRO C-L PANEL MODULE Caseta	SCL-153P-XX STCL-153P-XX DVCL-153PH-XX AYCL-153P-XX YGCL-153H-XX MACL-153M-XX PHPM-PA with Grafik Eye QS Main Unit PHPM-WBX with 3-wire fluorescent control HW/LP-RPM-4A-120 Wireless	150	1-24	1-16	1-10	1-8	1-9	1-7	1-13	1-11	1-3	N/A	
	DIVA ARIADNI	DVCL-253PH-XX AYCL-253P-XX	250	2-40	2-26	1-18	1-13	1-15	1-12	1-22	1-18	1-6		
	Heavy Loads: use RRD-6CL to control PHPM-PA phase adaptive power module		up to 1600											
	Electronic Low Voltage	DVELV-303P	300	2-40	2-26	1-18	1-13	1-15	1-12	1-22	1-18	1-6		
LEVITON	ILLUMATECH SURESLIDE DECORA	IPL06 6674 6618 6633	150	1-24	1-16	1-10	1-8	1-9	1-7	1-13	1-11	1-3		
		DSL06-1LZ	300	2-40	2-26	1-18	1-13	1-15	1-12	1-22	1-18	1-6		
COOPER	CORE DEVINE SLIDE DEVINE AL SERIES	DLC03P-W DAL06P SAL06P2	300	2-40	2-26	1-18	1-13	1-15	1-12	1-22	1-18	1-6		
Dimmer with Occupancy/Vacancy Sensor														
Lutron	Maestro	MSCL-OP153M(H) MSCL-VP153M(H)	150	1-24	1-16	1-10	1-8	1-9	1-7	1-13	1-11	1-3	N/A	
ANY 0-10V DIMMER			N/A									UNLIMITED		